# **Applications of DAS in Linear Infrastructure** Monitoring

#### Subjects: Geology

Contributor: Hong-Hu Zhu, Wei Liu, Tao Wang, Jing-Wen Su, Bin Shi

Linear infrastructures, such as railways, tunnels, and pipelines, play essential roles in economic and social development worldwide. Distributed acoustic sensing (DAS) is an emerging sensing technology that has rapidly developed in recent years. Due to its unique advantages in long-distance, high-density, and real-time monitoring, DAS arrays have shown broad application prospects in many fields, such as oil and gas exploration, seismic observation, and subsurface imaging. In the field of linear infrastructure monitoring, DAS has gradually attracted the attention of researchers and practitioners.

distributed acoustic sensing (DAS) linear infrastructure

field monitoring

### 1. Introduction

Linear infrastructures, such as railways, highways, pipelines, tunnels, embankments and power transmission lines, are a general type of civil infrastructures with long spans. They have the characteristics of long lengths, wide distribution ranges, and long service lives and they are widely distributed in complex and changeable natural environments. They form the backbone of society and play important roles in economic and social development. However, due to the influence of geohazards, earthquakes, corrosion, aging, human activities, and other multiple factors, linear infrastructures face the potential risk of structural deterioration and damage during their service lives <sup>[1]</sup>. In the past few decades, accidental extraordinary events among linear infrastructures in long-term operations have aroused widespread concern. For instance, water, oil, and gas pipelines have sometimes been damaged by nearby earthworks, landslides, and third-party invasions <sup>[2][3]</sup>; some dramatic traffic disasters have been caused by rail rust and land subsidence; in some countries, border protection walls and barriers have been damaged by illegal immigration. Therefore, to ensure the safe and reliable operation of linear infrastructures and prevent potential threats in the long run, robust and efficient monitoring systems are required.

The establishment of monitoring and early warning systems for linear infrastructures is key to ensuring their health conditions and reducing the occurrence of disasters. At present, linear engineering monitoring mainly relies on manual inspections and field monitoring. The former is relatively expensive and intermittent 4. For the latter, the commonly used methods are categorized into two types, i.e., remote sensing and contact monitoring methods. Interferometric synthetic aperture radar (InSAR) and global navigation satellite systems (GNSS) are two popular remote sensing technologies with millimeter-level accuracy for displacement monitoring <sup>[5][6]</sup>. In recent years, unstaffed aerial vehicle (UAV) photogrammetry and terrestrial laser scanning (TLS) have provided effective solutions for ground surface deformation monitoring with higher accuracy <sup>[7]</sup>. Although these technologies can

obtain large-scale deformation data, monitoring is periodic and only applicable to surface deformations. For subsurface monitoring, a series of geotechnical instruments have been developed, e.g., extensometers, inclinometers, tiltmeters, and piezometers <sup>[8]</sup>. These can be installed in boreholes of different depths or directly fixed on linear infrastructures to carry out performance monitoring. In this way, the automatic and continuous monitoring of key physical parameters can be enabled, as well as early warnings of abnormal states or accidents. However, most of the instruments are based on single-point measurements and struggle to realize long-distance monitoring. For the above reasons, powerful and robust monitoring technologies for linear infrastructures are urgently needed to provide accurate and comprehensive measurements in real time.

Distributed acoustic sensing (DAS) is a new type of fiber-optic sensing technology that has rapidly developed in recent years. It not only has the advantages of ordinary fiber-optic sensing technologies (e.g., anti-electromagnetic interference, corrosion resistance, slenderness, and flexibility) but it can also measure dynamic strains (e.g., vibrations and sound waves) along fiber paths in a long-distance, fully distributed, and real-time manner <sup>[9]</sup>. In the past decade, there have been many successful applications of DAS in the field of geophysical detection, such as vertical seismic profile (VSP) acquisition <sup>[10][11][12]</sup>, hydraulic fracturing monitoring <sup>[13][14][15]</sup>, earthquake observation <sup>[16][17][18]</sup>, and structural detection and imaging <sup>[19][20][21]</sup>. In the fields of acoustics <sup>[22][23]</sup> and biology <sup>[24][25]</sup>, DAS has also shown its powerfulness. With the rapid development of demodulation techniques, the applications of DAS have gradually extended from land to ocean <sup>[26][27][28]</sup>, glaciers <sup>[29][30]</sup>, and volcanoes <sup>[31][32]</sup>.

For linear infrastructures, DAS provides a novel monitoring solution. The large-scale, long-distance, and real-time sensing capabilities of DAS mean that it has unreplaceable advantages for field monitoring. In addition, fiber-optic cables have strong environmental adaptability and can easily collect huge monitoring data along their fiber lengths. Therefore, DAS can be tailored for monitoring linear infrastructures in complex and harsh environments. In recent years, researchers and practitioners worldwide have carried out a large number of field investigations on linear infrastructures using DAS, such as pipeline leakage monitoring <sup>[33][34]</sup> and rail track health monitoring <sup>[35][36]</sup>. **Figure 1** briefly shows some current and potential application scenarios of DAS for monitoring linear infrastructures and related geohazards.



**Figure 1.** Current and potential application scenarios of DAS for monitoring linear infrastructures and geohazards. Adapted with permission from Ref. <sup>[37]</sup>. 2017, MDPI publisher.

## 2. Railway Safety Monitoring

#### 2.1. Train Positioning and Speed Monitoring

Railway management departments worldwide need to accurately monitor train positioning and speed information to ensure the safety of trains. In train positioning and speed monitoring, track circuit technology is widely used <sup>[38]</sup>. However, in some extreme weather conditions, such as super-strong lightning, track circuit technology may not work properly. Other sensing technologies also have application limitations. For instance, global positioning systems (GPS) have weak sensing capabilities in closed environments, such as tunnels, and cannot obtain accurate train motion information.

The development of DAS has provided a new solution for train positioning and speed monitoring. The advantages of DAS (strong anti-electromagnetic interference, high temporal resolution, etc.) can make up for the shortcomings of existing monitoring technologies. DAS systems are also convenient to use to perform field monitoring by just

connecting a sensing cable to an interrogation unit, as shown in **Figure 2**. Since trains generate strong vibration signals during the running process, sensing cables close to trains vibrate strongly, while sensing cables far away from the trains are undisturbed and only record background noise. Therefore, the position and running speed of trains can be easily determined by analyzing the recorded data from the cables at each position.



Figure 2. Schematic diagram of train positioning and speed monitoring based on DAS.

As early as 2014, Peng et al. conducted a field study <sup>[39]</sup>. They laid a 10.2 km sensing cable along a track to record vibration signals as trains were moving. From the DAS data, the position and running speed of trains at various time points could be clearly seen, demonstrating the feasibility of DAS for train positioning and speed monitoring. Since then, an increasing number of field trials have been carried out [40][41][42]. However, utilizing DAS for train positioning and speed monitoring also faces some challenges; for instance, how to bury sensing cables near tracks without affecting railway transportation and how to guickly extract effective information from continuous monitoring data. To process sensing data accurately and quickly, a variety of intelligent algorithms have been developed [36][42] [43]. He et al. proposed an improved Canny algorithm for precise train positioning and the feasibility of this algorithm has been verified through field experiments [43]. The results showed that the positioning error is less than 10 m. The same authors also proposed a cubical smoothing algorithm with a five-point approximation to denoise vibration signals and shorten the calculation time. Wiesmeyr et al. proposed a real-time train tracking algorithm that runs on the basis of 1 s signals without delay <sup>[36]</sup>. This algorithm combines machine learning techniques, such as principal component analysis (PCA) and support vector machines (SVMs), with image processing methods, such as edge monitoring and Kalman filtering. The field implementation results showed that this real-time tracking algorithm achieves 98% accuracy. For the burial of fiber-optic cables, Vidovic et al. proposed the use of existing fiber-optic cables near tracks for monitoring, which could greatly reduce monitoring costs [44]. However, the key point is to accurately locate the buried positions, especially those of the winding parts and redundant parts of cables. In addition, "tap tests" must be performed to obtain the corresponding relationships between the spatial positions of fiber-optic cables and channel numbers, which take considerable time to process. Vidovic et al. suggested the use of train platforms, bridges, and other positions as reference points in engineering practice [44].

#### 3. Rail Track Health Monitoring

Ever-increasing railway traffic not only drives social and economic development but also aggravates the wear and tear of tracks. At present, rail track health monitoring mostly relies on manual inspections and conventional deformation monitoring devices, such as track inspection vehicles, accelerometers, and strain gauges near the tracks. However, both manual monitoring and track inspection vehicle monitoring have certain monitoring periods and it is impossible to evaluate the health status of tracks in real time. Some sensors, such as accelerometers and strain gauges, cannot be deployed around tracks in a large-scale and intensive manner for monitoring due to their high prices.

Some researchers have proposed the use of distributed fiber-optic sensing (DFOS) technologies to evaluate the health status of tracks, such as Brillouin optical time domain analysis (BOTDA) <sup>[45]</sup> and optical frequency domain reflectometry (OFDR) <sup>[46]</sup>. These sensing technologies have a high sampling density and can obtain huge amounts of information on the health status of tracks. However, BOTDA cannot realize real-time sensing and OFDR has limitations in detection distance. On the contrary, DAS has the potential to greatly extend detection distances with super-high sensitivity, which could provide an ideal solution to track health monitoring.

In recent years, many successful trials have been introduced [40][41][42]. Milne et al. pointed out that DAS can be used to measure track deflections and sleeper end loads [35]. They pasted sensing cables under rails and performed back calculations using the track strain data that were recorded by the sensing cables, as shown in Figure 3. To verify the feasibility of this measurement method, the results from the DAS, strain gauges, and digital image correlation (DIC) were compared, which showed good consistency. Guo et al. developed an intelligent detection method for track slab deformation based on a random forest model and carried out field experiments to verify it [47]. The test results showed that this intelligent algorithm can effectively identify deformations in track slabs and the recognition rate reaches 96.09%. Wang et al. also pointed out that DAS has the potential to detect track health status [48]. They used deep convolutional networks to detect the health status of tracks and conducted field experiments to verify them. The test results showed that the accuracy of the recognition method reaches 98.04%. The above experimental results demonstrate the application potential of DAS in the field of track health monitoring. However, these applications also face some challenges. On the one hand, some trace vibration characteristics that could identify issues may be submerged within strong external noise. On the other hand, analyzing the health status of tracks based on artificial intelligence technology requires a large amount of labeled data, which is difficult to obtain <sup>[48]</sup>. In the future, researchers should work closely with railway departments to develop intelligent algorithms with stronger denoising and higher recognition capabilities. In addition, researchers could also combine DAS with other technologies to jointly monitor the health of railway tracks in order to compensate for the lower detection ability of a single detection technology, thereby breaking through the abovementioned developmental bottlenecks.



**Figure 3.** Schematic diagram of fiber-optic cable layout and sensing. Reprinted with permission from Ref. <sup>[35]</sup>. 2020, Elsevier. In the figure,  $\varphi$  represents the phase information, *L* is the length, and  $\Delta L$  is the change in length.

#### 4. Roadbed Velocity Structure Imaging

When trains are running at high speeds, some of their energy is transmitted in the form of seismic waves due to the extrusion, friction, and collision between the trains and the tracks. The seismic waves excited by trains are good active source seismic wave fields, which contain the structural and dynamic characteristics of the tracks and roadbeds <sup>[49][50][51]</sup>. By analyzing changes in seismic waves, structural defects in roadbeds can be monitored and disaster warnings for high-speed railways can be realized.

Restricted by multiple factors, such as cost, power, and burial location, it is difficult for traditional seismic sensing devices (nodal seismographs, narrowband geophones, broadband seismographs, etc.) to be deployed on a large scale and for long periods of time along railways. DAS breaks through the above limitations nicely. The detection units on fiber-optic cables do not need to be powered separately, only the interrogation units need to be supplied with power. In addition, there is a large number of existing communication fiber-optic cables along railways. As long as the cables are connected to interrogation units, researchers can form long-distance, real-time and dense seismic sensing networks. Recently, researchers have monitored and analyzed seismic signals generated by moving trains with the aid of DAS <sup>[52][53]</sup>. Shao et al. extracted surface wave signals from DAS records through seismic interference technology and then used the multi-analysis surface wave (MASW) method to carry out

inversion work. Finally, they successfully obtained the shallow shear wave velocity structure under a roadbed, which fully demonstrates the feasibility of DAS in roadbed velocity structure imaging <sup>[52]</sup>.

However, research in this field is still in its infancy. On the one hand, trains are moving sources and the seismic waves they excite are very complex. On the other hand, DAS is only sensitive to seismic waves that propagate in specific directions due to its direction sensitivity. The above factors limit the further development of DAS in the field. It is believed that with the continuous deepening of research, these bottlenecks can be broken through and DAS can be integrated with high-speed rail seismology in the future.

#### 5. Highway Traffic Monitoring

Highway traffic is an essential part of people's lives. To monitor highway traffic, a variety of fixed (radar guns, road sensors, cameras, etc.) and mobile (vehicle GPS, mobile phones, etc.) monitoring technologies have been developed in recent years. The former can provide high-resolution monitoring data but their installation and maintenance costs are high and their space coverage is relatively low. The latter have high space coverage but their data collection frequency is low, so they cannot perform real-time monitoring and may also involve personal privacy problems <sup>[54]</sup>. Therefore, new traffic monitoring systems are urgently required.

DAS systems could provide an alternative for highway traffic monitoring. Because fiber-optic cables are buried under roads, this detection method has strong concealment qualities and the cables embedded underground can avoid physical damage during long-term monitoring. In recent years, there have been several good examples of applying DAS to highway traffic monitoring <sup>[55][56][57]</sup>. Wang et al. monitored the Pasadena Rose Parade using a communication cable under the road <sup>[58]</sup>. By analyzing the vibration information collected by the cable, they successfully identified traffic characteristic signals, such as pedestrians, motorcycles, and floats (**Figure 4**). They also proposed a method to measure road traffic flow and speed and analyzed urban road traffic conditions before and after the outbreak of COVID-19 <sup>[54]</sup>. The results are shown in **Figure 5**. It can be clearly seen that the overall traffic flow in the city decreased after the outbreak of COVID-19, while the speed increased. They also compared the monitoring results from DAS to those from other monitoring technologies and found that they had good consistency, which successfully proves the feasibility of DAS in highway traffic monitoring. Catalano et al. proposed the application of the Hough transform to vehicle counting and demonstrated an algorithm for the automatic detection and counting of vehicles <sup>[59]</sup>. Field tests showed that the accuracy rate of the algorithm reaches 73%.



**Figure 4.** Seismic records (10.0–50.0 Hz) showing the vibrations caused by motorcycles, floats, and bands. Reprinted with permission from Ref. <sup>[58]</sup>. 2020, Seismological Society of America.



**Figure 5.** (a) A map showing the changes in average daily traffic volume before and after lockdown using DASbased transportation analysis; (b) a map showing the degree of change in mean traffic speed before and after lockdown using DAS-based transportation analysis <sup>[54]</sup>.

Although DAS has great application potential in highway traffic monitoring, it also faces many challenges. For instance, the deformation coupling of fiber-optic cables in some highway sections is limited and it is impossible to accurately record the vibration signals generated by traveling vehicles as during heavy traffic congestion periods, it is difficult to accurately distinguish the vibration signals generated by each type of vehicle, which would adversely affect the traffic flow statistics.

### 6. Pipeline Safety Monitoring

As safe and cheap transportation devices, pipelines are widely used for the transportation of oil, natural gas, and other products. The real-time monitoring of pipeline operation status can effectively maintain pipeline safety and prolong pipeline service life. DFOS is a technology that developed rapidly in the 1980s. It has been widely used in pipeline safety monitoring in recent years. For instance, distributed temperature sensing (DTS) technology is used to monitor pipeline leakages <sup>[60][61]</sup> and distributed strain sensing (DSS) technology is used to monitor pipeline deformations <sup>[62][63][64]</sup>. However, they are static monitoring technologies and cannot perform the real-time and dynamic monitoring of pipelines. The vigorous development of DAS has provided new ideas and solutions for the dynamic monitoring of pipelines.

#### 7. Tunnel Structure Health Monitoring

As essential public transportation facilities, tunnels can greatly shorten driving distances, save transportation costs, and protect ecological environments. However, in the process of tunnel construction, geological disasters, such as water leakages and floods, often occur <sup>[65]</sup>. These incidents pose a serious threat to the health of tunnels. Therefore, there is an urgent need for real-time and comprehensive evaluation technologies to monitor tunnel health status.

DAS provides a brand new tool for tunnel health monitoring <sup>[66][67][68]</sup>. Based on a scattering-enhanced fiber-optic DAS system, Hu et al. performed the intelligent monitoring of a tunnel ring <sup>[67]</sup>. They laid cables on a steel ring structure to monitor vibration frequency. Using the monitoring data, they assessed and classified the health status of the steel ring based on machine learning algorithms. The recognition accuracy of the final test was as high as 97.8%, indicating that DAS can be used to monitor the health condition of tunnel structures.

Aiming to mitigate potential disaster events during tunnel construction, Zhang et al. proposed a DAS-based disturbance event identification method <sup>[68]</sup>. They laid cables along a tunnel lining and used a random forest algorithm to analyze the DAS data. They successfully identified various vibration events during tunnel construction, including unexpected disasters, such as rockfalls. Its recognition accuracy rate is as high as 92.31%.

https://encyclopedia.pub/entry/33946

### 8. Border Security Monitoring

In this era of cross-border terrorism and illegal immigration, many countries around the world are actively seeking ways to effectively protect their borders. Traditional border security technologies (radars, electro-optical/infrared, fencing, etc.) have shortcomings, such as being susceptible to electromagnetic and terrain interference and requiring the frequent maintenance of detection devices. DAS offers a new approach to border security. It can perform long-distance detection, classification, and localization, which enables timely responses to various border intrusion events (as shown in **Figure 6**). In addition, DAS provides low-noise and high-spatial resolution acoustic and seismic sensing that can detect and identify personnel, vehicle, and even aircraft intrusions. Therefore, DAS-based border security technology is regarded as a future development direction in the border security field.



Figure 6. Smart border security system. Reprinted with permission from Ref. <sup>[69]</sup>. 2020, SCITEPRESS.

Duckworth et al. investigated DAS responses to different intrusion events and found that DAS can not only capture the vibration signals of personnel footsteps but also respond well to intrusion events that are difficult to detect using conventional security technologies, such as digging, gunshots, underground excavation, and aircraft intrusion <sup>[70]</sup>. This fully demonstrates the application potential of DAS in border intrusion monitoring. However, there are some challenges; for instance, how to quickly discover and locate intrusion events within huge amounts of monitoring data and how to eliminate the interference of non-human invasion events (such as animal activities). To solve the above challenges, on the one hand, artificial intelligence technology (machine learning, deep learning, etc.) could be used to improve the efficiency of data processing or on the other hand, comprehensive analysis platforms for multivariate data (DAS data, radar data, video surveillance data, etc.) could be developed to analyze multivariate information and make comprehensive decisions in order to reduce the false positive and false negative rates of intrusion events.

#### **10. Other Applications**

In addition to the applications listed above, there are some other cases that use DAS to monitor linear infrastructures. For instance, cables buried in airport runways can be used for aircraft monitoring <sup>[71]</sup>. A pioneering work was carried out by the scientific research team of Beijing Jiaotong University. They presented an aircraft acoustic signal detection system based on DAS and analyzed the seismic waves excited by aircrafts. The 5 Hz region was shown to be the most meaningful frequency range. Researchers have also focused on the health monitoring of wind turbine towers and proposed methods to detect the structural phenomena associated with loose bolts and material damage within the towers <sup>[72]</sup>. Based on the amplitude, frequency, power spectrum, and other characteristics of the data, loose bolts and material damage within towers can be monitored, which is of great significance for the maintenance of wind towers.

#### References

- Dadfar, B.; El Naggar, M.H.; Nastev, M. Quantifying exposure of linear infrastructures to earthquake-triggered transverse landslides in permafrost thawing slopes. Can. Geotech. J. 2017, 54, 1002–1012.
- 2. Geertsema, M.; Schwab, J.; Blais-Stevens, A.; Sakals, M. Landslides impacting linear infrastructure in west central British Columbia. Nat. Hazards 2009, 48, 59–72.
- 3. Quinn, P.; Hutchinson, D.; Diederichs, M.; Rowe, R. Regional-scale landslide susceptibility mapping using the weights of evidence method: An example applied to linear infrastructure. Can. Geotech. J. 2010, 47, 905–927.
- 4. Harvey, R.R.; McBean, E.A. Comparing the utility of decision trees and support vector machines when planning inspections of linear sewer infrastructure. J. Hydroinform. 2014, 16, 1265–1279.
- Infante, D.; Di Martire, D.; Calcaterra, D.; Miele, P.; Scotto di Santolo, A.; Ramondini, M. Integrated procedure for monitoring and assessment of linear infrastructures safety (I-Pro MONALISA) affected by slope instability. Appl. Sci. 2019, 9, 5535.
- 6. Zhang, L.; Sun, Q.; Hu, J. Potential of TCPInSAR in monitoring linear infrastructure with a small dataset of SAR images: Application of the Donghai Bridge, China. Appl. Sci. 2018, 8, 425.
- Mills, S.J.; Ford, J.J.; Mejías, L. Vision based control for fixed wing UAVs inspecting locally linear infrastructure using skid-to-turn maneuvers. J. Intell. Robot. Syst. 2011, 61, 29–42.
- B. Dunnicliff, J. Geotechnical Instrumentation for Monitoring Field Performance; John Wiley & Sons: Hoboken, NJ, USA, 1993.
- 9. Zhan, Z. Distributed acoustic sensing turns fiber-optic cables into sensitive seismic antennas. Seismol. Res. Lett. 2020, 91, 1–15.

- 10. Lellouch, A.; Biondi, B.L. Seismic applications of downhole DAS. Sensors 2021, 21, 2897.
- Molenaar, M.M.; Hill, D.; Webster, P.; Fidan, E.; Birch, B. First downhole application of distributed acoustic sensing for hydraulic-fracturing monitoring and diagnostics. SPE Drill. Complet. 2012, 27, 32–38.
- 12. Kobayashi, Y.; Uematsu, Y.; Mochiji, S.; Xue, Z. A field experiment of walkaway distributed acoustic sensing vertical seismic profile in a deep and deviated onshore well in Japan using a fibre optic cable deployed inside coiled tubing. Geophys. Prospect. 2020, 68, 501–520.
- 13. Byerley, G.; Monk, D.; Aaron, P.; Yates, M. Time-lapse seismic monitoring of individual hydraulic frac stages using a downhole DAS array. Lead. Edge 2018, 37, 802–810.
- Karrenbach, M.; Kahn, D.; Cole, S.; Ridge, A.; Boone, K.; Rich, J.; Silver, K.; Langton, D. Hydraulic-fracturing-induced strain and microseismic using in situ distributed fiber-optic sensing. Lead. Edge 2017, 36, 837–844.
- 15. Li, L.; Tan, J.; Wood, D.A.; Zhao, Z.; Becker, D.; Lyu, Q.; Shu, B.; Chen, H. A review of the current status of induced seismicity monitoring for hydraulic fracturing in unconventional tight oil and gas reservoirs. Fuel 2019, 242, 195–210.
- 16. Lindsey, N.J.; Martin, E.R. Fiber-optic seismology. Annu. Rev. Earth Planet. Sci. 2021, 49, 309– 336.
- Lindsey, N.J.; Martin, E.R.; Dreger, D.S.; Freifeld, B.; Cole, S.; James, S.R.; Biondi, B.L.; Ajo-Franklin, J.B. Fiber-optic network observations of earthquake wavefields. Geophys. Res. Lett. 2017, 44, 11792–11799.
- Shi, B.; Wang, B.; Zhang, C.; Gu, K.; Ruan, Y.; Li, G.; Wang, Q.; Wei, G.; Zhang, D.; Zhu, H.-H.; et al. Multi-physical distributed fiber optic observation in a 3211-m-deep scientific borehole at Jiajika lithium mine, western Sichuan. Chin. Sci. Bull. 2022, 67, 2719–2726.
- Daley, T.M.; Freifeld, B.M.; Ajo-Franklin, J.; Dou, S.; Pevzner, R.; Shulakova, V.; Kashikar, S.; Miller, D.E.; Goetz, J.; Henninges, J. Field testing of fiber-optic distributed acoustic sensing (DAS) for subsurface seismic monitoring. Lead. Edge 2013, 32, 699–706.
- Dou, S.; Lindsey, N.; Wagner, A.M.; Daley, T.M.; Freifeld, B.; Robertson, M.; Peterson, J.; Ulrich, C.; Martin, E.R.; Ajo-Franklin, J.B. Distributed acoustic sensing for seismic monitoring of the near Ssurface: A traffic-noise interferometry case study. Sci. Rep. 2017, 7, 11620.
- Zeng, X.; Lancelle, C.; Thurber, C.; Fratta, D.; Wang, H.; Lord, N.; Chalari, A.; Clarke, A. Properties of noise cross-correlation functions obtained from a distributed acoustic sensing array at Garner Valley, California. Bull. Seismol. Soc. Amer. 2017, 107, 603–610.
- 22. Franciscangelis, C.; Margulis, W.; Kjellberg, L.; Soderquist, I.; Fruett, F. Real-time distributed fiber microphone based on phase-OTDR. Opt. Express 2016, 24, 29597–29602.

- 23. Tomboza, W.; Guerrier, S.; Awwad, E.; Dorize, C. High sensitivity differential phase OTDR for acoustic signals detection. IEEE Photonics Technol. Lett. 2021, 33, 645–648.
- 24. Caruso, F.; Dong, L.; Lin, M.; Liu, M.; Gong, Z.; Xu, W.; Alonge, G.; Li, S. Monitoring of a nearshore small dolphin species using passive acoustic platforms and supervised machine learning techniques. Front. Mar. Sci. 2020, 7, 267.
- 25. Wang, B.; Mao, Y.; Ashry, I.; Al-Fehaid, Y.; Al-Shawaf, A.; Ng, T.K.; Yu, C.; Ooi, B.S. Towards detecting red palm weevil using machine learning and fiber optic distributed acoustic sensing. Sensors 2021, 21, 1592.
- 26. Lindsey, N.J.; Dawe, T.C.; Ajo-Franklin, J.B. Illuminating seafloor faults and ocean dynamics with dark fiber distributed acoustic sensing. Science 2019, 366, 1103–1107.
- Williams, E.F.; Fernandez-Ruiz, M.R.; Magalhaes, R.; Vanthillo, R.; Zhan, Z.; Gonzalez-Herraez, M.; Martins, H.F. Distributed sensing of microseisms and teleseisms with submarine dark fibers. Nat. Commun. 2019, 10, 5778.
- Jousset, P.; Reinsch, T.; Ryberg, T.; Blanck, H.; Clarke, A.; Aghayev, R.; Hersir, G.P.; Henninges, J.; Weber, M.; Krawczyk, C.M. Dynamic strain determination using fibre-optic cables allows imaging of seismological and structural features. Nat. Commun. 2018, 9, 2509.
- 29. Walter, F.; Graeff, D.; Lindner, F.; Paitz, P.; Koepfli, M.; Chmiel, M.; Fichtner, A. Distributed acoustic sensing of microseismic sources and wave propagation in glaciated terrain. Nat. Commun. 2020, 11, 2436.
- 30. Booth, A.D.; Christoffersen, P.; Schoonman, C.; Clarke, A.; Hubbard, B.; Law, R.; Doyle, S.H.; Chudley, T.R.; Chalari, A. Distributed acoustic sensing of seismic properties in a borehole drilled on a fast-flowing Greenlandic outlet glacier. Geophys. Res. Lett. 2020, 47, e2020GL088148.
- Jousset, P.; Currenti, G.; Schwarz, B.; Chalari, A.; Tilmann, F.; Reinsch, T.; Zuccarello, L.; Privitera, E.; Krawczyk, C.M. Fibre optic distributed acoustic sensing of volcanic events. Nat. Commun. 2022, 13, 1753.
- Nishimura, T.; Emoto, K.; Nakahara, H.; Miura, S.; Yamamoto, M.; Sugimura, S.; Ishikawa, A.; Kimura, T. Source location of volcanic earthquakes and subsurface characterization using fiberoptic cable and distributed acoustic sensing system. Sci. Rep. 2021, 11, 6319.
- 33. Zuo, J.; Zhang, Y.; Xu, H.; Zhu, X.; Zhao, Z.; Wei, X.; Wang, X. Pipeline leak detection technology based on distributed optical fiber acoustic sensing system. IEEE Access 2020, 8, 30789–30796.
- 34. Stajanca, P.; Chruscicki, S.; Homann, T.; Seifert, S.; Schmidt, D.; Habib, A. Detection of leakinduced pipeline vibrations using fiber-optic distributed acoustic sensing. Sensors 2018, 18, 2841.
- 35. Milne, D.; Masoudi, A.; Ferro, E.; Watson, G.; Le Pen, L. An analysis of railway track behaviour based on distributed optical fibre acoustic sensing. Mech. Syst. Signal Proc. 2020, 142, 106769.

- 36. Wiesmeyr, C.; Litzenberger, M.; Waser, M.; Papp, A.; Garn, H.; Neunteufel, G.; Döller, H. Realtime train tracking from distributed acoustic sensing data. Appl. Sci. 2020, 10, 448.
- 37. Zhu, H.-H.; Shi, B.; Zhang, C.-C. FBG-based monitoring of geohazards: Current status and trends. Sensors 2017, 17, 452.
- 38. Wybo, J.-L. Track circuit reliability assessment for preventing railway accidents. Saf. Sci. 2018, 110, 268–275.
- 39. Peng, F.; Duan, N.; Rao, Y.-J.; Li, J. Real-time position and speed monitoring of trains using phase-sensitive OTDR. IEEE Photonics Technol. Lett. 2014, 26, 2055–2057.
- Cedilnik, G.; Hunt, R.; Lees, G. Advances in train and rail monitoring with DAS. In Proceedings of the 26th International Conference on Optical Fiber Sensors, Lausanne, Switzerland, 24–28 September 2018.
- 41. Wang, Z.; Lu, B.; Zheng, H.; Ye, Q.; Pan, Z.; Cai, H.; Qu, R.; Fang, Z.; Zhao, H. Novel railwaysubgrade vibration monitoring technology using phase-sensitive OTDR. In Proceedings of the 25th International Conference on Optical Fiber Sensors, Jeju, Korea, 24–28 April 2017.
- 42. Kowarik, S.; Hussels, M.-T.; Chruscicki, S.; Münzenberger, S.; Lämmerhirt, A.; Pohl, P.; Schubert, M. Fiber optic train monitoring with distributed acoustic sensing: Conventional and neural network data analysis. Sensors 2020, 20, 450.
- 43. He, M.; Feng, L.; Fan, J. A method for real-time monitoring of running trains using Φ-OTDR and the improved Canny. Optik 2019, 184, 356–363.
- 44. Vidovic, I.; Marschnig, S. Optical fibres for condition monitoring of railway infrastructure— Encouraging data source or errant effort? Appl. Sci. 2020, 10, 6016.
- 45. Minardo, A.; Porcaro, G.; Giannetta, D.; Bernini, R.; Zeni, L. Real-time monitoring of railway traffic using slope-assisted Brillouin distributed sensors. Appl. Opt. 2013, 52, 3770–3776.
- 46. Du, C.; Dutta, S.; Kurup, P.; Yu, T.; Wang, X. A review of railway infrastructure monitoring using fiber optic sensors. Sens. Actuator A-Phys. 2020, 303, 111728.
- 47. Guo, G.; Cui, X.; Du, B. Random-forest machine learning approach for high-speed railway track slab deformation identification using track-side vibration monitoring. Appl. Sci. 2021, 11, 4756.
- 48. Wang, S.; Liu, F.; Liu, B. Research on application of deep convolutional network in high-speed railway track inspection based on distributed fiber acoustic sensing. Opt. Commun. 2021, 492, 126981.
- 49. Wang, X.; Chen, W.; Wen, J.; Ning, J.; Li, J. The applications of synchrosqueezing time-frequency analysis in high-speed train induced seismic data processing. Chin. J. Geophys. 2019, 62, 2328–2335.

- 50. Wang, X.; Wang, B.; Chen, W. The second-order synchrosqueezing continuous wavelet transform and its application in the high-speed-train induced seismic signal. IEEE Geosci. Remote Sens. Lett. 2020, 18, 1109–1113.
- 51. Jiang, Y.; Bao, T.; Ning, J.; Zhang, X. Spectral characteristics of high-speed rail seismic signal under viaduct. Acta Sci. Nat. Univ. Peking 2019, 55, 829–838.
- 52. Shao, J.; Wang, Y.; Chen, L. Near-surface characterization using high-speed train seismic data recorded by a distributed acoustic sensing array. IEEE Trans. Geosci. Remote Sens. 2022, 60, 5912911.
- 53. Dumont, V.; Tribaldos, V.R.; Ajo-Franklin, J.; Wu, K. Deep learning for surface wave identification in distributed acoustic sensing data. In Proceedings of the IEEE International Conference on Big Data, Atlanta, GA, USA, 15–18 December 2020.
- 54. Wang, X.; Zhan, Z.; Williams, E.F.; Herráez, M.G.; Martins, H.F.; Karrenbach, M. Ground vibrations recorded by fiber-optic cables reveal traffic response to COVID-19 lockdown measures in Pasadena, California. Commun. Earth Environ. 2021, 2, 160.
- 55. Liu, H.; Ma, J.; Yan, W.; Liu, W.; Zhang, X.; Li, C. Traffic flow detection using distributed fiber optic acoustic sensing. IEEE Access 2018, 6, 68968–68980.
- Lindsey, N.J.; Yuan, S.; Lellouch, A.; Gualtieri, L.; Lecocq, T.; Biondi, B. City-scale dark fiber DAS measurements of infrastructure use during the COVID-19 pandemic. Geophys. Res. Lett. 2020, 47, e2020GL089931.
- 57. Chambers, K. Using DAS to investigate traffic patterns at Brady Hot Springs, Nevada, USA. Lead. Edge 2020, 39, 819–827.
- Wang, X.; Williams, E.F.; Karrenbach, M.; Herráez, M.G.; Martins, H.F.; Zhan, Z. Rose Parade seismology: Signatures of floats and bands on optical fiber. Seismol. Res. Lett. 2020, 91, 2395– 2398.
- Catalano, E.; Coscetta, A.; Cerri, E.; Cennamo, N.; Zeni, L.; Minardo, A. Automatic traffic monitoring by φ-OTDR data and Hough transform in a real-field environment. Appl. Opt. 2021, 60, 3579–3584.
- 60. Mirzaei, A.; Bahrampour, A.; Taraz, M.; Bahrampour, A.; Bahrampour, M.; Foroushani, S.A. Transient response of buried oil pipelines fiber optic leak detector based on the distributed temperature measurement. Int. J. Heat Mass Transf. 2013, 65, 110–122.
- 61. Madabhushi, S.; Elshafie, M.; Haigh, S. Accuracy of distributed optical fiber temperature sensing for use in leak detection of subsea pipelines. J. Pipeline Syst. Eng. Pract. 2014, 6, 04014014.
- 62. Lim, K.; Wong, L.; Chiu, W.K.; Kodikara, J. Distributed fiber optic sensors for monitoring pressure and stiffness changes in out-of-round pipes. Struct. Control Health Monit. 2016, 23, 303–314.

- 63. Simpson, B.; Hoult, N.A.; Moore, I.D. Distributed sensing of circumferential strain using fiber optics during full-scale buried pipe experiments. J. Pipeline Syst. Eng. Pract. 2015, 6, 04015002.
- 64. Li, H.-J.; Zhu, H.-H.; Li, Y.; Zhang, C.; Shi, B. Experimental study on uplift mechanism of pipeline buried in sand using high-resolution fiber optic strain sensing nerves. J. Rock Mech. Geotech. Eng. 2022, 14, 1304–1318.
- Huang, L.; Hao, H.; Li, X.; Li, J. Source identification of microseismic events in underground mines with interferometric imaging and cross wavelet transform. Tunn. Undergr. Space Technol. 2018, 71, 318–328.
- 66. Sun, Y.; Li, H.; Fan, C.; Yan, B.; Chen, J.; Yan, Z.; Sun, Q. Review of a specialty fiber for distributed acoustic sensing technology. Photonics 2022, 9, 277.
- 67. Hu, D.; Tian, B.; Li, H.; Fan, C.; Liu, T.; He, T.; Liu, Y.; Yan, Z.; Sun, Q. Intelligent structure monitoring for tunnel steel loop based on distributed acoustic sensing. In Proceedings of the Conference on Lasers and Electro-Optics 2021, San Jose, CA, USA, 9–14 May 2021.
- 68. Zhang, T.-Y.; Shi, B.; Zhang, C.-C.; Xie, T.; Yin, J.; Li, J.-P. Tunnel disturbance events monitoring and recognition with distributed acoustic sensing (DAS). Earth Environ. 2021, 861, 042034.
- 69. Aslangul, S.A. Detecting tunnels for border decurity based on fiber optical distributed acoustic sensor data using DBSCAN. Sensornets 2020, 1, 78–84.
- Duckworth, G.; Owen, A.; Worsley, J.; Stephenson, H. Optasense® distributed acoustic and seismic sensing performance for multi-threat, multi-environment border monitoring. In Proceedings of the 2013 European Intelligence and Security Informatics Conference, Uppsala, Sweden, 13–14 August 2013.
- 71. Cai, Y.; Ma, J.; Yan, W.; Zhang, W.; An, Y. Aircraft detection using phase-sensitive optical-fiber OTDR. Sensors 2021, 21, 5094.
- Hubbard, P.G.; Xu, J.; Zhang, S.; Dejong, M.; Luo, L.; Soga, K.; Papa, C.; Zulberti, C.; Malara, D.; Fugazzotto, F. Dynamic structural health monitoring of a model wind turbine tower using distributed acoustic sensing (DAS). J. Civ. Struct. Health Monit. 2021, 11, 833–849.

Retrieved from https://encyclopedia.pub/entry/history/show/84587