Biodiesel as Renewable Biofuel in Current Diesel Engines

Subjects: Chemistry, Applied

Contributor: Rafael Estevez , Diego Luna , Laura María Aguado Deblas , Francisco Lopez-Tenllado , Carlos Luna , , Antonio Angel Romero , Felipa M Bautista

Many countries are immersed in several strategies to reduce the carbon dioxide (CO_2) emissions of internal combustion engines. One option is the substitution of these engines by electric and/or hydrogen engines. However, apart from the strategic and logistical difficulties associated with this change, the application of electric or hydrogen engines in heavy transport, e.g., trucks, shipping, and aircrafts, also presents technological difficulties in the short-medium term. In addition, the replacement of the current car fleet will take decades. This is why the use of biofuels is presented as the only viable alternative to diminishing CO_2 emissions in the very near future. Nowadays, it is assumed that vegetable oils will be the main raw material for replacing fossil fuels in diesel engines.

biodiesel	advanced biofuel	straight vegetable oils (SVO)	Gliperol	DMC-Biod
Ecodiesel	green diesel			

1. Introduction

Nowadays, most of the countries worldwide are making an unprecedented effort to reduce anthropogenic greenhouse gas (GHG) emissions to carry out a decarbonization process, which significantly affects the energy sources applied. In this sense, the Treaty of Paris ^[1] and the European New Green Deal, as well as the REDII, aim to achieve a climate-neutral Europe by 2050 ^[2]. Therefore, several countries have also implemented their own energy and climate policy framework for 2030 and beyond, advancing in decarbonization and promoting innovation in order to achieve a viable new climate economy low in CO₂ emissions ^[3].

Considering that the choice of green hydrogen as the main energy vector for the decarbonization of the planet seems definitive, biofuels should receive a secondary role in the current research and development priorities of transportation, including cars, trucks, ships, planes, etc. However, the transition from current energy sources to this new technology requires a period of several decades, in accordance with the planning carried out by the same countries involved in these international agreements ^[4].

Notwithstanding the possibility of building a transport fleet operating with new technologies and being neutral in CO_2 emissions, it is mandatory to consider the temporary rate of the substitution of current vehicles working with internal combustion engines (ICEs) in order to avoid an economic chaos of unpredictable consequences. In this sense, the replacement of the enormous number of vehicles that operate with ICEs needs to be carried out in such

a way that they can continue operating throughout their useful life with diesel fuels or, alternatively, with biofuels with similar properties. This fact does not constitute a trivial problem due to the very high number of vehicles currently in use and the fact that those vehicles that are being built now and in the next two or three decades must be added to the list ^[5]. Consequently, the reduction in emissions in this long transition period involves a reduction in fossil fuels and increase in other fuels that allow for their operation in ICEs, together with the incorporation of hydrogen-powered engines and other emerging technologies. In this way, a smooth transition to a scenario without fossil fuels could be foreseen ^[6].

In this sense, biofuels can be easily integrated into the logistics of the global transportation system. In fact, the goal pursued by EU is that biofuels constitute 30% of all fuels by 2030 ^[Z]. Despite this goal being easy to achieve considering the technical issues, the substitution of fossil fuels with biofuels is considered unattainable in this deadline due to the impossibility of having enough agricultural land to carry out the necessary crops, since bioethanol and biodiesel (the most widely biofuels employed) require enormous agricultural resources to fulfill these purposes ^{[8][9][10][11][12]}.

2. Strengths and Weaknesses of Biodiesel as Renewable Biofuel in Current Diesel Engines

Biodiesel is defined as a mixture of long chain fatty acid methyl esters derived from renewable lipid sources, such as vegetable oil or animal fat, that can be used in compression ignition engines with little or no modifications. Until now, the use of a homogeneous alkaline transesterification chemical process with methanol has been initially chosen to address the biodiesel production [13][14][15][16]. In fact, biodiesel is, to date, the liquid biofuel produced at a greater quantity, due to the simplicity of its chemical process and its rheological properties, like fossil diesel [17][18] ^[19]. In addition, it can be produced from different feedstocks, depending on the availability of the crop in the region. Among other advantages, biodiesel exhibits biodegradability, non-toxicity, renewability, a high cetane number, a high flash point, and its high oxygen content allows for its complete combustion in engines, reducing the amount of particulate matter, hydrocarbons, and gases, such as carbon monoxide (CO), CO₂, and sulfur oxides (SOx). Furthermore, biodiesel has a very low sulfur content and very low aromatic components, as well as other pollutant emissions. Nevertheless, a slight increase in nitrogen oxide (NOx) emissions is usually described in comparison to diesel fuel ^{[20][21][22]}. Due to the high flashpoint that biodiesel exhibits, at around 150 °C, it is very safe for transportation and storage [23][24][25]. In addition, biodiesel perfectly fits into existing engines without any modification and it can be used in its pure form or blended with petroleum-based fuels without modification of existing engines or with only minor modifications ^{[26][27][28][29][30][31]}. Moreover, biodiesel exhibits better lubricant properties than fossil diesel, which allow for the extension of the engine life, and also allow for a reduction in carbon dioxide emissions by 78% in comparison with fossil diesel. In addition, the biodegradability of biodiesel is certainly high, ranging from 80.4% to 91.2% after 30 days, whereas the biodegradability of fossil diesel is only 24.5% [32]. Taking into consideration all of the advantages abovementioned, it is understandable that biodiesel has become a research hot spot during the last years, resulting in an increase in scientific publications and patents [33]. as can be seen in Figure 1. Thus, for only microalgae biodiesel production, more than ten thousand patents have

been published in the last 20 years ^{[34][35][36]}. Furthermore, in the last twenty years, almost forty-four thousand articles have been published, producing a growing increase year after year, demonstrating the growing interest in the problem.



Figure 1. Publications found in the Web of Science database by the keywords "biodiesel" separated by document types from year 2000 to 2021.

Despite these efforts made to achieve better processes, better catalysts, and better sources of raw materials, it is currently concluded that the generation of glycerol represents a barrier that is difficult to overcome for the industrial production of biodiesel ^[37]. An alternative could be the reduction in the production cost of biodiesel. Nevertheless, the biodiesel industry strongly depends on the cost of the feedstock employed as a raw material. Despite the fact that some feedstock, such as non-edible oil and waste cooking oil, can be obtained at a good cost, they usually need a higher cost in their manufacture processing to produce standard-quality biodiesel ^{[38][39][40]}. The true magnitude of this problem has been proven in all of its consequences when the industrial-scale production of biodiesel has begun in the last three decades. The management of the huge amounts of wastes, where glycerol is the main component, is a problem with a very difficult solution ^{[41][42]}, and there are still no industrial processes capable of integrating the enormous amount of glycerol. Furthermore, this glycerol obtained as a by-product also exhibits a very low quality, since it is in a mixture with other products, such as methanol, water, salts, and some amounts of monoglycerides ^[43].

Therefore, for being employed as a biofuel, the biodiesel obtained must be cleaned and separated from these byproducts. The additional cleaning process is usually carried out by successive washing steps with water, so that a large consumption of water, energy, and time to obtain the glycerol elimination is required in order to obtain the limits established by the quality standard EN 14214 and the ASTM D6751, which are the European and the American ones, respectively ^{[44][45][46][47][48]}. These limits establish that the amount of glycerol should not exceed the 0.02% in the refined biodiesel in order to prevent its reaction with oxygen at high temperatures inside the engine, which would either produce acrolein or would polymerize generating deposits of carbonaceous compounds on the injector nozzles, pistons, and valves in the engines, consequently reducing the efficiency of the engine and its service life ^{[49][50][51]}. Therefore, it is clear that the industrial production of biodiesel requires a very complex design in order to avoid the presence of glycerol in the final biofuel ^[52], as is shown in **Figure 2**. In summary, the transesterification reaction is usually carried out in a batch reactor under constant stirring at 60 °C. Then, glycerol is separated together with the excess of methanol by decantation. Then, methanol is recovered by distillation. This crude biodiesel contains catalyst residues that must be neutralized and eliminated.



Figure 2. Standard flowchart of an alkali transesterification process in a conventional biodiesel plant, reproduced with permission of Ref. ^[52]. Copyright 2019 Elsevier.

As aforementioned, biodiesel must be subjected to several washing steps with water, although the purification process also requires a drying process in an evaporator to remove held residual water ^[44]. Alternatively, the purification of biodiesel may also be obtained by ultrafiltration and dry washing, employing fumed silica sorbent, molecular distillation, organic resins, and biomass-based adsorbent or starch and cellulose as adsorbents of impurities ^{[53][54][55][56][57][58]}. This vast number of studies devoted to obtaining methodologies that are economically viable show that this step is one of the main factors that lead to an unprofitable biodiesel production ^[59].

Consequently, there is not a practical solution for the problem associated with the destabilizing glycerol price in the global market, since there are no industrial processes capable of adsorbing the increasing glycerol production ^[60] ^[61]. To minimize this problem, multiple investigations are being carried out in order to valorize this crude glycerol ^[62] ^[62]; see **Figure 3**.



Figure 3. Different chemicals obtained to valorize crude glycerol generated in the industrial production of biodiesel, reproduced with permission of Ref. ^[62]. Copyright 2020 Elsevier.

Another element of vulnerability associated with the production of conventional biodiesel is related to the low atomic yield (or atomic efficiency) of the process. The atom yield is an important concept in green chemistry, and is far from the concept of chemical yield. In fact, a high-yielding process can still result in a substantial quantity of by-products, as is the case for biodiesel production. These green metrics are crucial for determining the sustainability and environmental impact of biodiesel production ^{[65][66][67]}.

In summary, it is commonly accepted that the greatest contribution to determining the cost of biodiesel is determined by the price of feedstock, which occupies 70% of the biodiesel production cost ^{[68][69][70]}. Therefore, independently of looking at increasing the sources of triglycerides, available at appropriate prices for their transformation into biofuels, by optimizing the parameters influencing the production process of biodiesel, costs could be reduced by up to 30%. In addition, savings could be obtained by avoiding the management of residual glycerol, obtained together with conventional biodiesel, as well as the increase of at least 10% of the final product, if it is no glycerol is generated as a by-product. Thus, the search for different renewable biofuels integrating glycerol is still encouraged, while also avoiding several collective drawbacks, such as being energy-intensive, tedious in recovering glycerol, difficult in removing the acid or base catalyst from the product, the further treatment of alkaline wastewater, and the interference of free fatty acids and water in the reaction ^[71].

References

- Obergassel, W.; Arens, C.; Hermwille, L.; Kreibich, N.; Mersmann, F.; Ott, H.E.; Wang-Helmreich, H. Phoenix from the ashes: An analysis of the Paris Agreement to the United Nations Framework Convention on Climate Change. Eur. J. Int. Law 2015, 21, 9–77.
- Chiaramonti, D.; Talluri, G.; Scarlat, N.; Prussi, M. The challenge of forecasting the role of biofuel in EU transport decarbonisation at 2050: A meta-analysis review of published scenarios. Renew. Sustain. Energy Rev. 2021, 139, 110715.
- Oberthür, S. Where to go from Paris? The European Union in climate geopolitics. Glob. Aff. 2016, 2, 119–130.
- 4. Gota, S.; Huizenga, C.; Peet, K.; Medimorec, N.; Bakker, S. Decarbonising transport to achieve Paris Agreement targets. Energy Effic. 2019, 12, 363–386.
- 5. Kalghatgi, G. Is it really the end of internal combustion engines and petroleum in transport? Appl. Energy 2018, 225, 965–974.
- 6. Sisco, M.R.; Pianta, S.; Weber, E.U.; Bosetti, V. Global climate marches sharply raise attention to climate change: Analysis of climate search behavior in 46 countries. J. Environ. Psychol. 2021,

75, 101596.

- 7. Dafnomilis, I.; Hoefnagels, R.; Pratama, Y.W.; Schott, D.L.; Lodewijks, G.; Junginger, M. Review of solid and liquid biofuel demand and supply in Northwest Europe towards 2030—A comparison of national and regional projections. Renew. Sustain. Energy Rev. 2017, 78, 31–45.
- Schreyer, F.; Luderer, G.; Rodrigues, R.; Pietzcker, R.C.; Baumstark, L.; Sugiyama, M.; Brecha, R.J.; Ueckerdt, F. Common but differentiated leadership: Strategies and challenges for carbon neutrality by 2050 across industrialized economies. Environ. Res. Lett. 2020, 15, 114016.
- 9. Gomiero, T. Large-scale biofuels production: A possible threat to soil conservation and environmental services. Appl. Soil Ecol. 2018, 123, 729–736.
- Rocha, M.H.; Capaz, R.S.; Lora, E.E.S.; Nogueira, L.A.H.; Leme, M.M.V.; Renó, M.L.G.; del Olmo, O.A. Life cycle assessment (LCA) for biofuels in Brazilian conditions: A meta-analysis. Renew. Sustain. Energy Rev. 2014, 37, 435–459.
- 11. Bindraban, P.S.; Bulte, E.H.; Conijn, S.G. Can large-scale biofuels production be sustainable by 2020? Agric. Syst. 2009, 101, 197–199.
- 12. Demirbas, A. Biofuels securing the planet's future energy needs. Energy Convers. Manag. 2009, 50, 2239–2249.
- 13. Demirbas, A. Future energy sources. In Waste Energy for Life Cycle Assessment; Springer: Berlin, Germany, 2016; pp. 33–70.
- 14. Mythili, R.; Venkatachalam, P.; Subramanian, P.; Uma, D. Production characterization and efficiency of biodiesel: A review. Int. J. Energy Res. 2014, 38, 1233–1259.
- 15. Siraj, S.; Kale, R.; Deshmukh, S. Effects of thermal, physical, and chemical properties of biodiesel and diesel blends. Am. J. Mech. Ind. Eng 2017, 2, 24–31.
- 16. Nigam, P.S.; Singh, A. Production of liquid biofuels from renewable resources. Prog. Energy Combust. Sci. 2011, 37, 52–68.
- 17. Mohiddin, M.N.B.; Tan, Y.H.; Seow, Y.X.; Kansedo, J.; Mubarak, N.; Abdullah, M.O.; San Chan, Y.; Khalid, M. Evaluation on feedstock, technologies, catalyst and reactor for sustainable biodiesel production: A review. J. Ind. Eng. Chem. 2021, 98, 60–81.
- Raheem, I.; Mohiddin, M.N.B.; Tan, Y.H.; Kansedo, J.; Mubarak, N.M.; Abdullah, M.O.; Ibrahim, M.L. A review on influence of reactor technologies and kinetic studies for biodiesel application. J. Ind. Eng. Chem. 2020, 91, 54–68.
- 19. Aydın, S. Comprehensive analysis of combustion, performance and emissions of power generator diesel engine fueled with different source of biodiesel blends. Energy 2020, 205, 118074.

- 20. Thangaraj, B.; Solomon, P.R.; Muniyandi, B.; Ranganathan, S.; Lin, L. Catalysis in biodiesel production—A review. Clean Energy 2019, 3, 2–23.
- 21. Noor, C.M.; Noor, M.; Mamat, R. Biodiesel as alternative fuel for marine diesel engine applications: A review. Renew. Sustain. Energy Rev. 2018, 94, 127–142.
- 22. Sharma, A.K.; Sharma, P.K.; Chintala, V.; Khatri, N.; Patel, A. Environment-friendly biodiesel/diesel blends for improving the exhaust emission and engine performance to reduce the pollutants emitted from transportation fleets. Int. J. Environ. Res. Public Health 2020, 17, 3896.
- 23. Álvarez, A.; Lapuerta, M.n.; Agudelo, J.R. Prediction of flash-point temperature of alcohol/biodiesel/diesel fuel blends. Ind. Eng. Chem. Res. 2019, 58, 6860–6869.
- 24. Do Nascimento, D.C.; Carareto, N.D.D.; Neto, A.M.B.; Gerbaud, V.; da Costa, M.C. Flash point prediction with UNIFAC type models of ethylic biodiesel and binary/ternary mixtures of FAEEs. Fuel 2020, 281, 118717.
- Hazrat, M.; Rasul, M.; Khan, M.; Mofijur, M.; Ahmed, S.; Ong, H.C.; Vo, D.-V.N.; Show, P.L. Techniques to improve the stability of biodiesel: A review. Environ. Chem. Lett. 2021, 19, 2209– 2236.
- 26. Chandran, D. Compatibility of diesel engine materials with biodiesel fuel. Renew. Energy 2020, 147, 89–99.
- Chidambaranathan, B.; Gopinath, S.; Aravindraj, R.; Devaraj, A.; Krishnan, S.G.; Jeevaananthan, J. The production of biodiesel from castor oil as a potential feedstock and its usage in compression ignition Engine: A comprehensive review. Mater. Today Proc. 2020, 33, 84–92.
- Jayakumar, M.; Karmegam, N.; Gundupalli, M.P.; Gebeyehu, K.B.; Asfaw, B.T.; Chang, S.W.; Balasubramani, R.; Awasthi, M.K. Heterogeneous base catalysts: Synthesis and application for biodiesel production—A review. Bioresour. Technol. 2021, 331, 125054.
- 29. Alagumalai, A.; Mahian, O.; Hollmann, F.; Zhang, W. Environmentally benign solid catalysts for sustainable biodiesel production: A critical review. Sci. Total Environ. 2021, 768, 144856.
- 30. Vignesh, P.; Kumar, A.P.; Ganesh, N.S.; Jayaseelan, V.; Sudhakar, K. A review of conventional and renewable biodiesel production. Chin. J. Chem. Eng. 2020, 40, 1–17.
- 31. Chozhavendhan, S.; Singh, M.V.P.; Fransila, B.; Kumar, R.P.; Devi, G.K. A review on influencing parameters of biodiesel production and purification processes. Curr. Res. Green Sustain. Chem. 2020, 1, 1–6.
- 32. Syafiuddin, A.; Hao, C.J.; Yuniarto, A.; Hadibarata, T. The current scenario and challenges of biodiesel production in Asian countries: A review. Bioresour. Technol. Rep. 2020, 12, 100608.
- 33. Zhang, M.; Gao, Z.; Zheng, T.; Ma, Y.; Wang, Q.; Gao, M.; Sun, X. A bibliometric analysis of biodiesel research during 1991–2015. J. Mater. Cycles Waste Manag. 2018, 20, 10–18.

- 34. Li, D.; Du, W.; Fu, W.; Cao, X. A Quick Look Back at the Microalgal Biofuel Patents: Rise and Fall. Front. Bioeng. Biotechnol. 2020, 8, 1035.
- 35. Mahlia, T.; Syazmi, Z.; Mofijur, M.; Abas, A.P.; Bilad, M.; Ong, H.C.; Silitonga, A. Patent landscape review on biodiesel production: Technology updates. Renew. Sustain. Energy Rev. 2020, 118, 109526.
- 36. Rawat, J.; Gupta, P.K.; Pandit, S.; Priya, K.; Agarwal, D.; Pant, M.; Thakur, V.K.; Pande, V. Latest Expansions in Lipid Enhancement of Microalgae for Biodiesel Production: An Update. Energies 2022, 15, 1550.
- Bazooyar, B.; Shariati, A.; Hashemabadi, S.H. Economy of a utility boiler power plant fueled with vegetable oil, biodiesel, petrodiesel and their prevalent blends. Sustain. Prod. Consum. 2015, 3, 1–7.
- Aghbashlo, M.; Peng, W.; Tabatabaei, M.; Kalogirou, S.A.; Soltanian, S.; Hosseinzadeh-Bandbafha, H.; Mahian, O.; Lam, S.S. Machine learning technology in biodiesel research: A review. Prog. Energy Combust. Sci. 2021, 85, 100904.
- 39. Gebremariam, S.; Marchetti, J. Economics of biodiesel production. Energy Convers. Manag. 2018, 168, 74–84.
- 40. Rochelle, D.; Najafi, H. A review of the effect of biodiesel on gas turbine emissions and performance. Renew. Sustain. Energy Rev. 2019, 105, 129–137.
- 41. Nda-Umar, U.; Ramli, I.; Taufiq-Yap, Y.; Muhamad, E. An Overview of Recent Research in the Conversion of Glycerol into Biofuels, Fuel Additives and other Bio-Based Chemicals. Catalysts 2019, 9, 15.
- 42. Quispe, C.A.; Coronado, C.J.; Carvalho, J.A., Jr. Glycerol: Production, consumption, prices, characterization and new trends in combustion. Renew. Sustain. Energy Rev. 2013, 27, 475–493.
- 43. Smirnov, A.A.; Selishcheva, S.A.; Yakovlev, V.A. Acetalization catalysts for synthesis of valuable oxygenated fuel additives from glycerol. Catalysts 2018, 8, 595.
- 44. Atadashi, I.; Aroua, M.K.; Aziz, A.A.; Sulaiman, N. The effects of water on biodiesel production and refining technologies: A review. Renew. Sustain. Energy Rev. 2012, 16, 3456–3470.
- 45. Gomes, M.G.; Santos, D.Q.; de Morais, L.C.; Pasquini, D. Purification of biodiesel by dry washing, employing starch and cellulose as natural adsorbents. Fuel 2015, 155, 1–6.
- Squissato, A.L.; Fernandes, D.M.; Sousa, R.M.; Cunha, R.R.; Serqueira, D.S.; Richter, E.M.; Pasquini, D.; Munoz, R.A. Eucalyptus pulp as an adsorbent for biodiesel purification. Cellulose 2015, 22, 1263–1274.
- 47. Tajziehchi, K.; Sadrameli, S. Optimization for free glycerol, diglyceride, and triglyceride reduction in biodiesel using ultrafiltration polymeric membrane: Effect of process parameters. Process Saf.

Environ. Prot. 2021, 148, 34-46.

- 48. Govindaraju, R.; Chen, S.-S.; Wang, L.-P.; Chang, H.-M.; Pasawan, M. Significance of Membrane Applications for High-Quality Biodiesel and Byproduct (Glycerol) in Biofuel Industries. Curr. Pollut. Rep. 2021, 7, 128–145.
- 49. Li, R.; Liang, N.; Ma, X.; Chen, B.; Huang, F. Free glycerol removal from biodiesel using anion exchange resin as a new type of adsorbent. Ind. Eng. Chem. Res. 2018, 57, 17226–17236.
- 50. Shahbaz, K.; Mjalli, F.; Hashim, M.; AlNashef, I. Using deep eutectic solvents based on methyl triphenyl phosphunium bromide for the removal of glycerol from palm-oil-based biodiesel. Energy Fuels 2011, 25, 2671–2678.
- Reis, M.; Cardoso, V. Biodiesel production and purification using membrane technology. In Membrane Technologies for Biorefining; Elsevier: Amsterdam, The Netherlands, 2016; pp. 289– 307.
- 52. Karmakar, B.; Halder, G. Progress and future of biodiesel synthesis: Advancements in oil extraction and conversion technologies. Energy Convers. Manag. 2019, 182, 307–339.
- 53. Catarino, M.; Ferreira, E.; Dias, A.P.S.; Gomes, J. Dry washing biodiesel purification using fumed silica sorbent. Chem. Eng. J. 2020, 386, 123930.
- 54. Rodriguez, N.E.; Martinello, M.A. Molecular distillation applied to the purification of biodiesel from ethanol and soybean oil. Fuel 2021, 296, 120597.
- Limmun, W.; Sansiribhan, S. Water-spray washing technique as a purification process in the production of biodiesel. In E3S Web of Conferences; EDP Sciences: Les Ulis, France, 2020; p. 3006.
- 56. Sokač, T.; Gojun, M.; Tušek, A.J.; Šalić, A.; Zelić, B. Purification of biodiesel produced by lipase catalysed transesterification by ultrafiltration: Selection of membranes and analysis of membrane blocking mechanisms. Renew. Energy 2020, 159, 642–651.
- 57. Sandouqa, A.; Al-Shannag, M.; Al-Hamamre, Z. Biodiesel purification using biomass-based adsorbent manufactured from delignified olive cake residues. Renew. Energy 2020, 151, 103–117.
- 58. De Jesus, S.S.; Ferreira, G.F.; Maciel, M.R.W.; Maciel Filho, R. Biodiesel purification by column chromatography and liquid-liquid extraction using green solvents. Fuel 2019, 235, 1123–1130.
- Suthar, K.; Dwivedi, A.; Joshipura, M. A review on separation and purification techniques for biodiesel production with special emphasis on Jatropha oil as a feedstock. Asia-Pac. J. Chem. Eng. 2019, 14, e2361.
- 60. Abomohra, A.E.-F.; Elsayed, M.; Esakkimuthu, S.; El-Sheekh, M.; Hanelt, D. Potential of fat, oil and grease (FOG) for biodiesel production: A critical review on the recent progress and future

perspectives. Prog. Energy Combust. Sci. 2020, 81, 100868.

- Anuar, M.R.; Abdullah, A.Z. Challenges in biodiesel industry with regards to feedstock, environmental, social and sustainability issues: A critical review. Renew. Sustain. Energy Rev. 2016, 58, 208–223.
- Kaur, J.; Sarma, A.K.; Jha, M.K.; Gera, P. Valorisation of crude glycerol to value-added products: Perspectives of process technology, economics and environmental issues. Biotechnol. Rep. 2020, 27, e00487.
- 63. Kosamia, N.M.; Samavi, M.; Uprety, B.K.; Rakshit, S.K. Valorization of biodiesel byproduct crude glycerol for the production of bioenergy and biochemicals. Catalysts 2020, 10, 609.
- 64. Ripoll, M.; Betancor, L. Opportunities for the valorization of industrial glycerol via biotransformations. Curr. Opin. Green Sustain. Chem. 2021, 28, 100430.
- 65. Martinez-Guerra, E.; Gude, V.G. Assessment of sustainability indicators for biodiesel production. Appl. Sci. 2017, 7, 869.
- 66. Gude, V.G.; Martinez-Guerra, E. Green chemistry with process intensification for sustainable biodiesel production. Environ. Chem. Lett. 2018, 16, 327–341.
- Shaheen, A.; Sultana, S.; Lu, H.; Ahmad, M.; Asma, M.; Mahmood, T. Assessing the potential of different nano-composite (MgO, Al2O3-CaO and TiO2) for efficient conversion of Silybum eburneum seed oil to liquid biodiesel. J. Mol. Liq. 2018, 249, 511–521.
- 68. Yan, Y.; Li, X.; Wang, G.; Gui, X.; Li, G.; Su, F.; Wang, X.; Liu, T. Biotechnological preparation of biodiesel and its high-valued derivatives: A review. Appl. Energy 2014, 113, 1614–1631.
- 69. Yaqoob, H.; Teoh, Y.H.; Sher, F.; Farooq, M.U.; Jamil, M.A.; Kausar, Z.; Sabah, N.U.; Shah, M.F.; Rehman, H.Z.U.; Rehman, A.U. Potential of waste cooking oil biodiesel as renewable fuel in combustion engines: A Review. Energies 2021, 14, 2565.
- 70. Kemp, W.H. Biodiesel: Basics and Beyond: A Comprehensive Guide to Production and Use for the Home and Farm; Aztext Press: Tamworth, Australia, 2006.
- Abd Manaf, I.S.; Embong, N.H.; Khazaai, S.N.M.; Rahim, M.H.A.; Yusoff, M.M.; Lee, K.T.; Maniam, G.P. A review for key challenges of the development of biodiesel industry. Energy Convers. Manag. 2019, 185, 508–517.

Retrieved from https://encyclopedia.pub/entry/history/show/55175