Biomethane Production of Distillery Stillage

Subjects: Environmental Sciences | Energy & Fuels Contributor: Katarzyna Bułkowska

Distillery stillage has a high energy potential (13.6 MJ/kg TS, 10.4 MJ/kg COD), which indicates that it can be processed via anaerobic digestion and is a suitable substrate for conversion into energy. Distillery stillage consists of compounds that are easily biodegraded during anaerobic digestion, such as proteins, lipids, and carbohydrates. Among the carbohydrates, the concentration of cellulose can be on the level of 32.2%, hemicelluloses—20.9%, and lignin—3.2% in the distillery stillage obtained from maize.

Keywords: biomethane ; bioelectrochemical treatment ; Distillery Stillage

1. Introduction

The management of industrial waste is a principal area of development in the world, as industrial waste contains a wide variety of organic and inorganic pollutants that have a negative impact on the environment. The distillery industry is one of the main sources of environmental pollution, but also one of the key factors contributing to the development of the global economy. Only 5% of the world's ethanol production comes from chemical synthesis. More than 95% of ethanol is produced from agricultural raw materials. Of these, sugar-based raw materials account for approximately 42% of the ethanol produced, and non-sugar raw materials (mainly starch-based) account for approximately 58% [1]. Ethanol is produced from cereals (mainly rye, corn, triticale, and wheat), root crops (mainly potatoes), molasses, and other agricultural raw materials ^[2]. The production of alcohol is constantly growing because it is used in many industries, including the chemical, pharmaceutical, cosmetic, beverage, food, and perfume industries. In addition, the European Union program obliges Member States to use biofuels as transport fuels (their share should amount to 14% in 2025 and 19.7% in 2030) [3]. Along with the increase in the demand for alcohol, the amount of byproducts (termed distillery stillage), which may be up to 15 times greater than the amount of alcohol produced, is also increasing ^[4]. Treatment of distillery byproducts is a priority area for environmental protection because untreated byproducts that are released into the environment increase water pollution, adversely affect aquatic life, and reduce soil alkalinity. The literature indicates that the most promising option for utilization of distillery byproducts is to valorize them as a renewable feedstock for recovery of energy and biobased materials, thus enabling integration of remediation and recovery of resources. In this biorefinery approach, appropriate technologies are required, including methanogenesis, photosynthesis, photofermentation, dark fermentation, and bioelectrogenesis, which are made possible by the versatile metabolisms of biocatalytic microorganisms.

2. Processing of Distillery Stillage—Biomethane Production

The degradation of substrates with a high protein content results in a high level of ammonium (NH_4^+-N) in the residue, which causes process instability and reduced biogas/methane production ^[5]. At a NH_4^+-N concentration above 3 g/L, acetate degradation changes from acetotrophic methanogenesis to syntrophic acetate oxidation ^{[6][7]}. The syntrophic cooperation between syntrophic acetate-oxidizing (SAO) bacteria and hydrotrophic methanogens means that the oxidation of acetate is combined with hydrogen consumption. Cocultures of SAO bacteria and methanogens usually have a lower growth rate than acetic methanogens, which decreases biogas production.

Another ingredient influencing anaerobic digestion is sulfuric acid, which is used to regulate the pH during alcohol production. This contributes to the high concentration of sulfates in distillery stillage ^[8]. Sulfate-reducing bacteria convert sulfates into sulfides ^[9]. Degradation of amino acids releases sulfides from the amino acids, methionine and cysteine, which results in the release of organic sulfur in the form of sulfides. Sulfides cause corrosion, decrease the bioavailability of trace elements essential for microbial activity by forming complexes with metals, and inhibit the growth of micro-organisms and the consumption of organic compounds (mainly alcohols, volatile fatty acids (VFAs)) and hydrogen, which could be used for biogas production ^{[10][11]}.

Anaerobic digestion of distillery stillage produces digested sludge, which is rich in nutrients ^[12] and can be used as manure. Before the treated effluent can be released into the environment, it requires further treatment. The major challenges in treating this anaerobically digested effluent are the removal of color and inorganic compounds.

2.1. Bioreactors and Operational Parameters

Conventional anaerobic digestion systems require a long hydraulic retention time (HRT) of approximately 30–40 days, which means that they need to be modified to prevent biomass from leaching from the reactors.

Distillery stillage has been treated in various types of anaerobic digesters, including a sequencing batch reactor (ASBR), an up-flow anaerobic sludge blanket reactor (UASB), an anaerobic continuous stirred tank reactor (CSTR), an anaerobic baffled reactor (ABR), a down-flow stationary fixed film (DSFF), and an anaerobic membrane bioreactor (ANBR), with COD removal ranging from 82 to 99% and an organic loading rate (OLR) ranging from 2.9 to 29 kg COD/(m^3 ·d) ^{[13][14][15]} [16][17][18][19][20].

As an example, the ASBR allowed a soluble COD removal efficiency greater than 98% to be obtained at an OLR of 8.6 kg COD/(m^3 ·d) at an HRT of 2.2 days ^[13]. Melamane et al. ^[21] reported the application of the down-flow fluidization technology for the anaerobic digestion of distillery stillage, in which 85% total organic carbon (TOC) removal was achieved at an OLR of 4.5 kg TOC/(m^3 ·d). However, UASB reactors are the most used high-rate digesters for anaerobic treatment of various types of industrial wastewaters. In a UASB treating distillery wastewater, COD removal efficiency of over 90% was reported ^[22]. In another anaerobic treatment method, fluidized bed reactors contained appropriate media, such as sand, gravel, or plastics, for bacterial attachment and growth. A two-stage process with an anaerobic filter, followed by a UASB reactor was investigated by Blonskaja et al. ^[23]. The acidogenic and methanogenic phases were separated, ensuring better conditions for the methanogens. COD removal was 54 and 93% in these stages, respectively. In general, such two-stage systems were found to enable better conditions for the methanogenic phase, thus being more suitable for anaerobic digestion of distillery waste ^[24].

In the conventional CSTR systems, the purpose of anaerobic digestion is to maintain the stable process conditions, along with shortening the HRT, because this allows conversion of a higher amount of distillery stillage to energy. Lee et al. ^[14] examined the shortening HRT in a CSTR during the anaerobic digestion of distillery stillage obtained at corn ethanol production. The results showed no differences in volatile solid (VS) reduction (82–83%) in the reactor, with HRTs ranging from 25 to 40 days. The maximum rate of the methane production of 1.41 L CH₄/(L·d) was produced at 25-day HRT, whereas the maximum methane yield of approximately 0.63 L CH₄/g VS was achieved at HRTs between 30 and 40 days. Simulation results using a kinetic model indicated that the reactor needs to be operated for longer than 23 days to achieve 80% of the maximum methane yield.

The increase in process efficiency in the conventional CSTRs can be achieved by increasing the temperature, which also leads to shortening the HRT. Anaerobic digestion of corn ethanol thin stillage was tested at thermophilic temperature (55 °C) in two CSTRs. The thin stillage was organically concentrated with 100 g COD_{tot}/L and 60 g VS/L and a low pH of approximately 4.0. Steady-state conditions were achieved at 30-, 20-, and 15-day HRTs, and digester failure was obtained at a 12-day HRT. A significant reduction in VS was achieved, with a maximum reduction (89.8%) at the 20-day HRT. Methane yield ranged from 0.6 to 0.7 L CH₄/g VS removed during steady-state operation. Effluent VFAs below 200 mg/L as acetic acid were achieved at 20- and 30-day HRTs ^[15]. Oosterkamp et al. ^[16] managed to shorten HRT to 10 days treating distillery stillage in the CSTR also under thermophilic (55 °C) conditions. The methane production was 0.43 L CH₄/(g COD·d), COD removal was 64%, soluble COD removal was 62%, and pH was 7.7.

Operating at a high OLR (>25 kg COD/(m³·d)) and short HRT (less than 5 days) is possible when the micro-organisms are retained inside the reactor. Andalib et al. ^[127] tested the anaerobic fluidized bed bioreactor (AFBR) employing zeolite with an average diameter (dm) of 425–610 µm and a specific surface area of the carrier media of 26.5 m²/g. Despite a very high concentration of distillery stillage with COD of 130 g COD/L and total suspended solids (TSS) of 47 g/L, the AFBR showed up to 88% COD and 78% TSS removal at a very high OLR of 29 kg COD/(m³·d) and HRT of 3.5 days. Methane production rates of up to 160 L/d at the steady-state equivalent to 40 L CH₄/L distillery stillage and biogas production rate per reactor volume of 15.8 L/(L·d) were achieved.

The reduction in biomass washout, higher solid retention time (SRT), and significantly improved phase separation can be achieved in the hybrid configuration of an anaerobic baffled reactor (ABR) where solid/liquid/gas separators were incorporated into the configuration of the conventional ABR ^[18]. The hybrid ABR achieved higher COD removal, sulfate removal, and methane yield of 97–94%, 94–97%, and 294–310 mL CH₄/g COD, respectively, at an OLR of 1.0–3.5 kg

COD/($m^3 \cdot d$) than conventional ABR, where 75–94% COD removal, 67–76% sulfate removal, and 140–240 mL CH₄/g COD were obtained at an OLR range of 1.1–1.8 kg COD/($m^3 \cdot d$).

Thin stillage from a dry-grind corn ethanol plant was evaluated as a carbon source for anaerobic digestion by batch and high-rate semi-continuous down-flow stationary fixed film (DSFF) reactors. Continuous studies employed two mesophilic DSFF anaerobic digesters treating thin stillage operated at HRTs of 20.0, 14.3, 8.7, 6.3, 5.0, and 4.2 d. Successful digestion was achieved up to an OLR of approximately 7.4 g COD/(L·d) at an HRT of 5 d, with a yield of 2.05 L CH₄/(L·d) and COD_{tot}, and VS removal efficiencies of 89% and 85%, respectively ^[19].

Besides the operational conditions, lipids in the lipid-rich distillery stillage cause operational problems in anaerobic digesters due to clogging and mass transfer problems because they are adsorbed to the microbial biomass surface. The flotation of biomass due to adhesion of fat may cause loss of active biomass because of washout. An excellent solution to biomass washout problems was reported for the treatment of lipid-rich wastewater in granular sludge bed reactors. The potential of anaerobic membrane bioreactors (AnMBRs) for the treatment of lipid-rich corn-to-ethanol thin stillage was investigated by Dereli et al. ^[20] at three different SRTs of 20, 30, and 50 days. The AnMBRs achieved up to 99% COD removal efficiencies and excellent effluent quality. Although higher OLRs up to 8.0 kg COD/(m³·d) could be applied in the reactors operated at shorter SRTs, better biological degradation efficiencies, i.e., up to 83%, were achieved at increased SRTs. Severe long-chain fatty acid (LCFA) inhibition was observed at 50-day SRT, possibly caused by the extensive dissolution of LCFA in the reactor, inhibiting the methanogenic biomass.

Maintaining stable anaerobic digestion, despite the rapid acidification and accumulation of intermediate VFAs lowering microbial activity and biomethane production, can be challenging. Therefore, more research is focused on how to recover anaerobic digestion performance after acidic shock (pH 5.5). The carbonaceous materials may function as an abiotic conductive conduit to stimulate microbial electron transfer and resist adverse effects on anaerobic digestion. Wu et al. ^[25] tested the nanomaterial graphene and more cost-effective pyrochar in their ability to recover anaerobic digestion performance after acidic shock (pH 5.5). Results showed that graphene addition (1.0 g/L) could lead to a biomethane yield of 250 mL/g COD; this was an 11% increase compared to the control. The recovered process was accompanied by faster propionate degradation (CH₃CH₂COO⁻ + 2H₂O \rightarrow CH₃COO⁻ + CO₂ + 6H⁺ + 6e⁻). The enhanced performance was possibly ascribed to the high electrical conductivity of graphene. In comparison, pyrochar addition (1 and 10 g/L) did not enhance the biomethane yield, though it reduced the digestion lag-phase time by 18.1 and 12.2% compared to the control, respectively. Microbial taxonomy analysis suggested that *Methanosarcina* (81.5% in abundance) with diverse metabolic pathways and OTU in the order DTU014 (6.4% in abundance) might participate in direct interspecies electron transfer, contributing to an effective recovery from acidic shock.

2.2. Effect of Polyphenols and Melanoidin on Biomethane Production

It was reported that distillery waste contains recalcitrant compounds, namely polyphenols and melanoidins, which exhibit toxicity towards micro-organisms [26][27][28]. Although the concentrations of polyphenols in some distillery wastes (molasses distillery wastewater) are more than two times lower [29] and they contribute less to the antimicrobial effect, at the same concentrations, polyphenols have a higher antimicrobial effect than melanoidins [26]. Figure 1 shows the structure of common polyphenols and melanoidins that are found in the distillery stillage.

Polyphenols are the compounds that particularly adversely affect methanogenesis, thus inhibiting the ability of methanogens to produce biofuels. According to Fedorak and Hrudey ^[30], this inhibition is visible at polyphenol concentrations above 1 g/L. The concentrations of phenolic compounds above 1 g/L decreased the biogas production from waste by 10%, and concentrations increased to 1.5, 2.0, and 4.0 g/L reduced the production by 29, 78, and 98%, respectively ^[31]. In other studies on anaerobic digestion, biogas production was decreased by phenol concentrations above 0.8 g/L ^[32]. On the other hand, at concentrations 120–594 mg/L, biogas production was decreased by up to 50%, depending on the polarity, type, molecular size, and amount of the phenolic compounds ^[33]. Melanoidins account for over 2% (m/v) of molasses distillery wastewater composition ^[34]. Although the toxicity of melanoidins is lower, under anaerobic conditions, its brown color is intensified ^[35], which impedes decolorization of the effluents.





glycine-glucose melanoidin

Figure 1. The structure of polyphenols and melanoidin (based on [36]) typical for the distillery stillage.

To improve biomethane production and to ensure the profitability of biogas plants, technologies for accelerating biomethane production from wastes that contain polyphenols should be developed. The antioxidative properties of polyphenols and melanoidins made them important for food, cosmetics, and pharmaceutical applications. Therefore, their recovery from distillery waste can bring two advantages: obtaining products of commercial interest and improving anaerobic digestion of this waste. For example, Kaushik et al. [37] used ultrafiltration, adsorption-desorption, and solvent extraction for recovering polyphenols and melanoidins from sugarcane molasses distillery wastewater. Methane content in produced biogas increased from 51% in the control sample to 70% after adsorption, which improved the methanation the most from the tested options. From molasses distillery effluents, melanoidins were removed with biological and physicochemical methods, as well as employing microbial fuel cells for electricity generation ^[38]. Biological methods included the use of a pure bacterial consortium comprising Proteus mirabilis, Bacillus sp., Raoultella planticola, and Enterobacter sakazakii [34], or phycoremediation [12]. Physicochemical methods included electrochemical degradation performed with ruthenium-oxide-coated titanium mesh (anode) and stainless steel (cathode) [39], or UV photodegradation [<u>40]</u>

2.3. Pretreatment of Distillery Stillage

To couple with anaerobic processing of distillery stillage, pretreatment techniques were used, including ozonation, ultrasound, thermal process, hydrodynamic cavitation, and fungal pretreatment. Methane yield coefficient and methane production rate were increased by about 13.6% and 41.16%, respectively, when using ozonation [41]. This pretreatment did not increase COD removal itself compared to anaerobic digestion alone; however, it converted polyphenols to other forms, thus increasing methanogenesis efficiency [41]. Hydrodynamic cavitation removed COD by 32.24%, TOC by 31.43%, and color by 48.00% ^[42]. Thermal pretreatment, ultrasound, and ozonation resulted in a 45.6% reduction in COD [43]. Fungal pretreatment with Trametes pubescens resulted in 53.3 and 72.5% removal of COD and polyphenols, respectively [44].

2.4. Post-Treatment of Distillery Stillage

To valorize distillery wastes, anaerobic digestion is mostly used to recover energy in the form of biogas. However, the effluent from anaerobic digestion still contains organic compounds and is dark in color. As an example, anaerobically digested stillage may contain 25,000-40,000 mg COD/L, 7000-10,000 mg BOD/L, and 22,000-34,000 mg TSS/L [12]. It was found that anaerobic processing does not decrease polyphenol content ^[26]. In addition, some polyphenols may be transformed from one form to another during different phases of the fermentation process [45], and, also, the transformation of polyphenols to less colored but more toxic products can proceed during the treatment of distillery waste with fungus Pleurotus sp. under aerobic conditions [46]. Therefore, to meet the environmental discharge standards, further treatment is necessary. Most often, when the BOD/COD ratio of the anaerobic effluent is greater than 0.25, the effluent is treated aerobically.

In the development of biological methods, the ability of some microbial strains or consortia to biodegrade anaerobically digested distillery stillage was examined. Efficient biodegradation was obtained when using such bacterial genera as *Pseudomonas, Bacillus, Microbacterium, Achromobacter, Staphylococcus,* and *Alcaligenes* ^{[47][48]}. According to Mohana et al. ^[49], *Pseudomonas, Stenotrophomonas,* and *Proteus* were able to remove COD (51%) and color (67%) within 72 h. The decolorization was possible by excretion of manganese peroxidase and laccase that removed the melanoidin by over 70% ^[34]. Removal of color was also achieved when employing yeast strains for the post-treatment of molasses distillery wastewater ^[50]; the removal efficiencies of color, COD, and BOD by *Citeromyces* sp. were 75, almost 100, and 76%, respectively. From the same type of wastewater, extracellular enzymes secreted by white-rot fungi (manganese peroxidase, lignin peroxidase, and phenol oxidase (laccase)) allowed efficient removal of melanoidin and polyphenols ^[51].

Apart from pure cultures, mixed cultures of activated sludge were reported to efficiently remove tannic acid polyphenolcontaining wastewater under aerobic conditions at dissolved oxygen concentrations above 1 mg/L ^[52]. To enhance microbial growth and improve polyphenol degradation, supplementation of carbon sources was carried out ^[53]. The studies of aerobic treatment of anaerobically digested distillery stillage focused on the optimization of the operating parameters, particularly OLR. In the sequencing batch reactor (SBR) operated at a constant HRT of 24 h, an increase in OLR from 1.8 to 9 kg COD/(m³·d) decreased the SBR performance ^[54]. The highest removal of COD (74%) and BOD (96%) was obtained at 3.6 kg COD/(m³·d). Apart from activated sludge reactors, biofilm in a rotating biological contactor was used after treating distillery stillage in microbial fuel cells ^[55]. The removal of COD and BOD was 84 and 81%, respectively.

The combination of activated sludge treatment with a biomass separation on a membrane in the technology of membrane bioreactors (MBR) results in a recovery of high-quality effluent when treating distillery stillage, a smaller footprint, and reduced sludge generation. In a lab-scale MBR, 95% COD reduction and 92% decolorization were achieved ^[56]. At an OLR between 3.0 and 5.7 kg COD/(m³·d), 41% COD removal ^[57] or 60% COD removal ^[58] was obtained, depending on the cut-off of the membrane used. In the study by Deschamps et al. ^[59], the membrane was directly incorporated into the anaerobic treatment, which produced a pilot-scale AnMBR. High biogas production of 1.36 NL_{biogas}/(L_{bioreactor}·d) was obtained at an OLR of 3.97 kg COD/(m³·d) and HRT of 3.5 d. By comparison, with the anaerobic packed-bed bioreactor, it was found that the higher COD removal efficiency (96.9%) and higher methane production (0.26 L CH₄/g COD) were obtained in the AnMBR with a shorter start-up period (21 d).

The limitations of aerobic processes for post-treatment of distillery stillage include the energy costs for aeration, high amount of excess sludge produced, necessity of nutrient supplementation, and operation at high dilution rates ^[26]. To make the post-treatment more energetically efficient, phycoremediation using microalgae was applied ^[12]. Particularly, effluents from the acidogenic process can be used by these photosynthetic organisms, also termed photobiocapture organisms. In this process, microalgae use nutrients present in the effluent and sunlight for growth. Moreover, carbon dioxide is absorbed by microalgae and converted into oxygen, thus reducing the energy requirements. Biomass produced may be further utilized for the production of biogas, biodiesel, or fertilizer. However, the feasibility of this technology depends on sufficient sunlight accessibility in a particular location. As an example, 83.2% of COD and 88.0% of BOD were removed in microalgae ponds with an HRT of 11 d $\frac{[60]}{10}$.

For post-treatment, physicochemical methods are also used; however, they are more effective for low-loaded effluents than biological processes. To recycle the water, reverse osmosis allowed for recovering 60% of water, with a permeate COD of 100 mg/L ^[12]. However, a high-pressure drop on the membrane under the conditions of high pollutant load and the necessity to utilize retentate increase the total operational cost.

The other solution that allows for water recovery from distillery thin stillage is evaporation that increases the solid content to 55-60% [61]. Burning stillage generates steam, which can be used as evaporation fuel, to generate electricity or run a turbine. The condensate from the evaporation system can be recycled back to the fermentation process. However, the process is highly energy-intensive; 550 kcal of energy is required to evaporate 1 L of water [12].

The other post-treatment process used is ultraviolet (UV) photodegradation. In the study by Apollo et al. ^[40], it was found that UV photodegradation is effective in color removal, but not effective in COD and BOD removal from distillery effluent. On the other hand, anaerobic digestion alone removed COD effectively, but the color was not sufficiently removed, or even increased because of the conversion of color imparting compounds, such as melanoidin. Therefore, using UV photodegradation as a post-treatment to the anaerobic digestion allowed COD removal of above 85% and 88% of color removal to be obtained.

References

- 1. Tolmasquim, M.T. Bioenergy for the future. In Proceedings of the Conference on Biofuels: "An Option for a Less Carbon -Intensive Economy", Rio de Janeiro, Brazil, 4–5 December 2007.
- Krzywonos, M.; Cibis, E.; Miskiewicz, T.; Ryznar-Luty, A. Utilization and biodegradation of starch stillage (distillery wast ewater). Electron. J. Biotechnol. 2009, 12, 6–7.
- 3. Krzywonos, M. Forecast for transport biofuels in Poland in 2020–2030. Przemysł Chem. 2015, 1, 168–172.
- 4. Fito, J.; Tefera, N.; van Hulle, S.W.H. Sugarcane biorefineries wastewater: Bioremediation technologies for environmen tal sustainability. Chem. Biol. Technol. Agric. 2019, 6, 6.
- Rajagopal, R.; Massé, D.I.; Singh, G. A critical review on inhibition of anaerobic digestion process by excess ammonia. Bioresour. Technol. 2013, 143, 632–641.
- Schnürer, A.; Nordberg, Å. Ammonia, a selective agent for methane production by syntrophic acetate oxidation at meso philic temperature. Water Sci. Technol. 2008, 57, 735–740.
- 7. Procházka, J.; Dolejš, P.; Máca, J.; Dohányos, M. Stability and inhibition of anaerobic processes caused by insufficienc y or excess of ammonia nitrogen. Appl. Microbiol. Biotechnol. 2012, 93, 439–447.
- Moestedt, J.; Nordell, E.; Schnürer, A. Comparison of operating strategies for increased biogas production from thin still age. J. Biotechnol. 2014, 175, 22–30.
- 9. Dai, X.; Hu, C.; Zhang, D.; Dai, L.; Duan, N. Impact of a high ammonia-ammonium-pH system on methane-producing a rchaea and sulfate-reducing bacteria in mesophilic anaerobic digestion. Bioresour. Technol. 2017, 245, 598–605.
- 10. Huertas, J.K.; Quipuzco, L.; Hassanein, A.; Lansing, S. Comparing hydrogen sulfide removal efficiency in a field-scale digester using microaeration and iron filters. Energies 2020, 13, 4793.
- 11. Erdirencelebi, D.; Kucukhemek, M. Control of hydrogen sulphide in full-scale anaerobic digesters using iron (III) chlorid e: Performance, origin and effects. Water SA 2018, 44, 176–183.
- 12. Sankaran, K.; Premalatha, M.; Vijayasekaran, M.; Somasundaram, V.T. Distillery wastewater treatment through anaero bic digestion and phycoremediation—A green industrial approach. Renew. Sustain. Energy Rev. 2014, 37, 634–643.
- 13. Ruiz-Herrera, J.; Martínez, A.I.; Sentandreu, R. Determination of the stability of protein pools from the cell wall of fungi. Res. Microbiol. 2002, 153, 373–378.
- Lee, P.H.H.; Bae, J.; Kim, J.; Chen, W.-H. Mesophilic anaerobic digestion of corn thin stillage: A technical and energetic assessment of the corn-to-ethanol industry integrated with anaerobic digestion. J. Chem. Technol. Biotechnol. 2011, 8 6, 1514–1520.
- 15. Schaefer, S.H.; Sung, S. Retooling the ethanol industry: Thermophilic anaerobic digestion of thin stillage for methane pr oduction and pollution prevention. Water Environ. Res. 2008, 80, 101–108.
- Oosterkamp, M.J.; Bauer, S.; Ibáñez, A.B.; Méndez-García, C.; Hong, P.; Cann, I.; Mackie, R.I. Identification of methan ogenesis and syntrophy as important microbial metabolic processes for optimal thermophilic anaerobic digestion of ene rgy cane thin stillage. Bioresour. Technol. Rep. 2019, 7, 100254.
- 17. Andalib, M.; Hafez, H.; Elbeshbishy, E.; Nakhla, G.; Zhu, J. Treatment of thin stillage in a high-rate anaerobic fluidized b ed bioreactor (AFBR). Bioresour. Technol. 2012, 121, 411–418.
- Sayedin, F.; Kermanshahi-Pour, A.; He, S. Anaerobic digestion of thin stillage of corn ethanol plant in a novel anaerobic baffled reactor. Waste Manag. 2018, 78, 541–552.
- 19. Wilkinson, A.; Kennedy, K.J. Anaerobic digestion of corn ethanol thin stillage in batch and by high-rate down-flow fixed f ilm reactors. Water Sci. Technol. 2012, 66, 1834–1841.
- 20. Dereli, R.K.; van der Zee, F.P.; Heffernan, B.; Grelot, A.; van Lier, J.B. Effect of sludge retention time on the biological p erformance of anaerobic membrane bioreactors treating corn-to-ethanol thin stillage with high lipid content. Water Res. 2014, 49, 453–464.
- 21. Melamane, X.L.; Tandlich, R.; Burgess, J.E. Treatment of wine distillery wastewater by high rate anaerobic digestion. W ater Sci. Technol. 2007, 56, 9–16.
- 22. Wolmarans, B.; de Villiers, G.H. Start-up of a UASB effluent treatment plant on distillery wastewater. Water SA 2002, 2 8, 63.
- 23. Blonskaja, V.; Menert, A.; Vilu, R. Use of two-stage anaerobic treatment for distillery waste. Adv. Environ. Res. 2003, 7, 671–678.

- 24. Cabrera-Díaz, A.; Reyes, I.P.; Merencio, D.O.; Lebrero, R.; Zaiat, M. Anaerobic digestion of sugarcane vinasse through a methanogenic UASB reactor followed by a packed bed reactor. Appl. Biochem. Biotechnol. 2017, 183, 1127–1145.
- 25. Wu, B.; Lin, R.; Kang, X.; Deng, C.; Xia, A.; Dobson, A.D.W.; Murphy, J.D. Graphene addition to digestion of thin stillag e can alleviate acidic shock and improve biomethane production. ACS Sustain. Chem. Eng. 2020, 8, 13248–13260.
- 26. M'Arimi, M.M.; Zhang, Y.; Götz, G.; Kiriamiti, K.H.; Geißen, S.-U. Antimicrobial colorants in molasses distillery wastewat er and their removal technologies. Int. Biodeterior. Biodegrad. 2014, 87, 34–43.
- Pereira, M.C.; Oliveira, D.A.; Hill, L.E.; Zambiazi, R.C.; Borges, C.D.; Vizzotto, M.; Mertens-Talcott, S.; Talcott, S.; Gom es, C.L. Effect of nanoencapsulation using PLGA on antioxidant and antimicrobial activities of guabiroba fruit phenolic e xtract. Food Chem. 2018, 240, 396–404.
- Elalami, D.; Carrere, H.; Abdelouahdi, K.; Garcia-Bernet, D.; Peydecastaing, J.; Vaca-Medina, G.; Oukarroum, A.; Zero ual, Y.; Barakat, A. Mild microwaves, ultrasonic and alkaline pretreatments for improving methane production: Impact o n biochemical and structural properties of olive pomace. Bioresour. Technol. 2020, 299, 122591.
- 29. Kaushik, A.; Basu, S.; Batra, V.; Balakrishnan, M. Fractionation of sugarcane molasses distillery wastewater and evalua tion of antioxidant and antimicrobial characteristics. Ind. Crop. Prod. 2018, 118, 73–80.
- 30. Fedorak, P.M.; Hrudey, S.E. The effects of phenol and some alkyl phenolics on batch anaerobic methanogenesis. Wate r Res. 1984, 18, 361–367.
- Chapleur, O.; Mazeas, L.; Godon, J.-J.; Bouchez, T. Asymmetrical response of anaerobic digestion microbiota to tempe rature changes. Appl. Microbiol. Biotechnol. 2015, 100, 1445–1457.
- Rosenkranz, F.; Cabrol, L.; Carballa, M.; Donoso-Bravo, A.; Cruz, L.; Ruiz-Filippi, G.; Chamy, R.; Lema, J. Relationship between phenol degradation efficiency and microbial community structure in an anaerobic SBR. Water Res. 2013, 47, 6739–6749.
- Hernandez, J.; Edyvean, R. Inhibition of biogas production and biodegradability by substituted phenolic compounds in anaerobic sludge. J. Hazard. Mater. 2008, 160, 20–28.
- 34. Yadav, S.; Chandra, R. Biodegradation of organic compounds of molasses melanoidin (MM) from biomethanated distill ery spent wash (BMDS) during the decolourisation by a potential bacterial consortium. Biodegradation 2012, 23, 609–6 20.
- 35. Peña, M.; Coca, M.; González, G.; Rioja, R.; García, M. Chemical oxidation of wastewater from molasses fermentation with ozone. Chemosphere 2003, 51, 893–900.
- Cämmerer, B.; Jalyschkov, V.; Kroh, L.W. Carbohydrate structures as part of the melanoidin skeleton. Int. Congr. Ser. 2 002, 1245, 269–273.
- 37. Kaushik, A.; Basu, S.; Raturi, S.; Batra, V.; Balakrishnan, M. Recovery of antioxidants from sugarcane molasses distille ry wastewater and its effect on biomethanation. J. Water Process. Eng. 2018, 25, 205–211.
- 38. Nayak, J.K.; Amit; Ghosh, U.K. An innovative mixotrophic approach of distillery spent wash with sewage wastewater for biodegradation and bioelectricity generation using microbial fuel cell. J. Water Process. Eng. 2018, 23, 306–313.
- Prasad, R.K.; Srivastava, S. Electrochemical degradation of distillery spent wash using catalytic anode: Factorial desig n of experiments. Chem. Eng. J. 2009, 146, 22–29.
- 40. Apollo, S.; Onyango, M.S.; Ochieng, A. An integrated anaerobic digestion and UV photocatalytic treatment of distillery wastewater. J. Hazard. Mater. 2013, 261, 435–442.
- 41. Siles, J.; García-García, I.; Martín, A. Integrated ozonation and biomethanization treatments of vinasse derived from et hanol manufacturing. J. Hazard. Mater. 2011, 188, 247–253.
- 42. Padoley, K.; Saharan, V.K.; Mudliar, S.; Pandey, R.; Pandit, A.B. Cavitationally induced biodegradability enhancement o f a distillery wastewater. J. Hazard. Mater. 2012, 219–220, 69–74.
- 43. Sangave, P.C.; Gogate, P.R.; Pandit, A.B. Ultrasound and ozone assisted biological degradation of thermally pretreated and anaerobically pretreated distillery wastewater. Chemosphere 2007, 68, 42–50.
- 44. Melamane, X.; Tandlich, R.; Burgess, J. Anaerobic digestion of fungally pre-treated wine distillery wastewater. Afr. J. Bi otechnol. 2007, 6, 1990–1993.
- 45. Romero, C.; Brenes, M.; García, P.; García, A.; Garrido, A. Polyphenol changes during fermentation of naturally black o lives. J. Agric. Food Chem. 2004, 52, 1973–1979.
- 46. Tsioulpas, A.; Dimou, D.; Iconomou, D.; Aggelis, G. Phenolic removal in olive oil mill wastewater by strains of Pleurotus spp. in respect to their phenol oxidase (laccase) activity. Bioresour. Technol. 2002, 84, 251–257.

- 47. Kumar, P.; Chandra, R. Decolourisation and detoxification of synthetic molasses melanoidins by individual and mixed c ultures of Bacillus spp. Bioresour. Technol. 2006, 97, 2096–2102.
- 48. Santal, A.R.; Singh, N.; Saharan, B.S. Biodegradation and detoxification of melanoidin from distillery effluent using an a erobic bacterial strain SAG5 of Alcaligenes faecalis. J. Hazard. Mater. 2011, 193, 319–324.
- 49. Mohana, S.; Desai, C.; Madamwar, D. Biodegradation and decolourization of anaerobically treated distillery spent wash by a novel bacterial consortium. Bioresour. Technol. 2007, 98, 333–339.
- 50. Sirianuntapiboon, S.; Zohsalam, P.; Ohmomo, S. Decolorization of molasses wastewater by Citeromyces sp. WR-43-6. Process. Biochem. 2004, 39, 917–924.
- 51. Asgher, M.; Bhatti, H.N.; Ashraf, M.; Legge, R. Recent developments in biodegradation of industrial pollutants by white rot fungi and their enzyme system. Biodegradation 2008, 19, 771–783.
- 52. Li, W.; Li, X.; Zeng, K. Aerobic biodegradation kinetics of tannic acid in activated sludge system. Biochem. Eng. J. 200 9, 43, 142–148.
- 53. Lin, J.; Reddy, M.; Moorthi, V.; Qoma, B.E. Bacterial removal of toxic phenols from an industrial effluent. Afr. J. Biotechn ol. 2008, 7, 2232–2238.
- 54. Kanimozhi, R.; Vasudevan, N. Effect of organic loading rate on the performance of aerobic SBR treating anaerobically digested distillery wastewater. Clean Technol. Environ. Policy 2014, 16, 467–476.
- 55. Anupama, S.; Pradeep, N.V.; Hampannavar, U.S. Anaerobic followed by aerobic treatment approaches for Spentwash using MFC and RBC. Sugar Tech 2013, 15, 197–202.
- 56. Sundararaman, S.; Kumar, J.L.; Kumar, N.G. Reduction of COD and decolourisation of UASB spent wash using E-MB R. Res. J. Pharm. Technol. 2015, 8, 845–848.
- 57. Satyawali, Y.; Balakrishnan, M. Treatment of distillery effluent in a membrane bioreactor (MBR) equipped with mesh filt er. Sep. Purif. Technol. 2008, 63, 278–286.
- 58. Gupta, R.; Satyawali, Y.; Batra, V.S.; Balakrishnan, M. Submerged membrane bioreactor using fly ash filters: Trials with distillery wastewater. Water Sci. Technol. 2008, 58, 1281–1284.
- 59. Deschamps, L.; Merlet, D.; Lemaire, J.; Imatoukene, N.; Filali, R.; Clément, T.; Lopez, M.; Theoleyre, M.-A. Excellent p erformance of anaerobic membrane bioreactor in treatment of distillery wastewater at pilot scale. J. Water Process. En g. 2021, 41, 102061.
- Travieso, L.; Benítez, F.; Sánchez, E.; Borja, R.; León, M.; Raposo, F.; Rincon, B. Assessment of a microalgae pond for post-treatment of the effluent from an anaerobic fixed bed reactor treating distillery wastewater. Environ. Technol. 2008, 29, 985–992.
- 61. Ray, S.G.; Ghangrekar, M.M. Comprehensive review on treatment of high-strength distillery wastewater in advanced ph ysico-chemical and biological degradation pathways. Int. J. Environ. Sci. Technol. 2019, 16, 527–546.

Retrieved from https://encyclopedia.pub/entry/history/show/38050