Integrated Photovoltaic-Fuel Cell Systems

Subjects: Energy & Fuels Contributor: Chukwuma Ogbonnaya

Integrated photovoltaic-fuel cell (IPVFC) system uses photovoltaics and fuel cells to majorly generate power and hydrogen, using solar energy as the prime mover. IPVFC amongst other integrated energy generation methodologies are renewable and clean energy technologies that have received diverse research and development attentions over the last few decades due to their potential applications in a hydrogen economy.

solar energy photovoltaic-fuel cell system power generation hydrogen economy

photovoltaics

fuel cells

1. Design Methodologies, Composition and Configurations

IPVFC systems have flexible configurations to accommodate different types of components which is an undeniable engineering advantage. The autonomous operation of the system is facilitated by an energy management system, which provides a logical algorithm that controls the flow of energy in the system ^[1]. The modularity in the design of IPVFC systems implies that they are easily scalable ^[2]. Thus, the system can be configured to meet users' requirements and satisfy specific use cases. Notwithstanding, to contextualize this study, there are four categories of design methodologies of IPVFC systems, although there could be variations in the composition of a category depending on the use case. The following are brief descriptions of the categories:

- Category 1: PV, fuel cell and batteries can supply power to the load.
- Category 2: PV and fuel cell supplies power to the battery bank/supercapacitor so that it can supply power to the load.
- Category 3: Combined heat and power (CHP) design in which the PV is replaced with photovoltaic-thermal (PV/T) component.
- Category 4: Compact design that replaces proton exchange membrane electrolyser (PEME) and proton exchange membrane fuel cell (PEMFC) components with a unitized regenerative proton exchange membrane fuel cell (URPEMFC) component.

The first category of IPVFC systems is typified by the configuration in **Figure 1**. This design methodology for power generation is composed of a photovoltaic module, DC/DC converter for the photovoltaic, battery, step-down converter for electrolyser, electrolyser, fuel cell, step-up for the fuel cell, and a DC/AC inverter ^[1]. In this

configuration, a DC/DC converter is used to connect the PV modules, electrolyser, fuel cell and battery to the DCbus bar. A DC/AC inverter is connected to the DC-bus bar to change the DC to AC for AC loads ^[3]. Integrating PV modules with batteries and FC stacks makes the integrated system more sustainable because the system can reliably satisfy load requirements, even in the absence of solar radiation ^[4]. This category may use a proton exchange membrane electrolyser to generate hydrogen and proton exchange membrane fuel cell to convert the stored hydrogen to meet power demanded ^[5]. PEMFC has a high energy density per unit area, zero greenhouse gas emission, modular design, noiseless operation, limited moving parts and it is not limited by the Carnot efficiency ^{[6][7]}. This configuration is suitable for buildings, stationary applications, grid-connected systems, and mobile applications. As a variation of this design, the system can be configured so that batteries can provide the basic power while peaks in demand for power can be met with the fuel cell. This feature is crucial in achieving optimal operational efficiency of renewable energy-based smart grids since the intermittency of solar energy could lead to excess electricity generation or shortage of it.



Figure 1. Schematic diagram of an IPVFC system including a PV, battery, electrolyser, and fuel cell.

The second category of IPVFC systems is shown in **Figure 2**. This is more suitable for automotive and unmanned aerial vehicle (UAV) applications. Integrated fuel cell hybrid electric vehicles and fuel cell electric vehicles are actively being investigated as potential replacements for internal combustion engines in the automotive industry ^[8], and the trend will likely continue onwards because the automotive sector is a major contributor of emissions ^[10].



Figure 2. Schematic diagram of IPVFC system as power source for automotive applications ^[11].

In this configuration, a PV module and an FC stack charge the battery bank which provides tractive power to drive the entire system. This configuration provides a more stable power source compared to configurations in which electrical energy is supplied to the load directly from the PV module. For shorter periods, batteries can supply constant direct current if charged, while fuel cells can provide direct current to keep the battery charged for a longer timeframe using hydrogen. In this category, hydrogen may be produced within or outside the system or obtained from hydrogen filling stations to reduce the weight of the electrolyser from the total weight of the system.

Lead acid batteries ^[5] have achieved technological maturity and most IPVFC systems use it. Nonetheless, Li-ion batteries are uniquely compatible with renewable energy resources ^[12], and their utilization will continue to increase until a more efficient and safer battery cell is innovated. Supercapacitors (SC) have high-power density, fast dynamics and a relatively longer lifetime compared to batteries, but they discharge fast. Supercapacitors have been used in this configuration to assist stabilize the power supplied by a PV module and a PEMFC stack ^[13]. Thus, combining batteries and SC have been reported to be beneficial for improving the reliability of the system ^[14] ^[15]. PV modules and FC stacks are used without batteries/SC to reduce the overall cost of the system when it is not necessary to store electrical energy ^[16]. Boost converters are used to adapt the low DC from the PV and the FC to a regulated bus bar DC ^[17]. The boosting and inversion of unregulated low-voltage output from the FC can be efficiently achieved at a low cost and compactness using a boost-inverter with a bidirectional backup battery storage ^[18]. A bidirectional converter and a boost converter can also be combined to manage the flow of current in IPVFC systems so that the current/voltage from the battery and supercapacitor ^[15]. Bus bars enable the electrical connection of the components to ensure that the DC sources and the DC supplies are properly integrated to facilitate an effective spatial topology of IPVFC systems.

The third category of IPVFC systems uses a photovoltaic-thermal (PV/T) module or solar thermal collectors ^[19] instead of a PV module to achieve a co-generation system (or combined heat and power (CHP)). Consequently, electricity and hot fluid can be generated as shown in **Figure 3**. This configuration is predicated on the preconception that harnessing the thermal energy from the PV module could lead to improved energy and exergy efficiency of the first category of IPVFC system. Further design variation of this category involves harnessing the waste heat from the PEME and PEMFC to perform additional thermal work such as heating of air, water, or other fluids since they operate between 70 and 100 °C.



Figure 3. Schematic diagram of an IPVFC system including a PV/T, battery, electrolyser and fuel cell ^[20].

The fourth category of design methodology of IPVFC systems replaces the electrolyser and fuel cell components with a unitized regenerative fuel cell. The electrolyser and fuel cell exist as separate components in categories 1, 2 and 3. Category four unifies the electrolyser and fuel cell as a URPEMFC system ^[21], so that it can perform the functions of an electrolyser and a fuel cell ^[22] as shown in **Figure 4**. This intimate unification implies lesser cost and complexity compared to discrete reversible proton exchange membrane fuel cell (DRPEMFC) systems in which the components exist separately.



Figure 4. Block diagram of an integrated IPVFC system in which the electrolyser and fuel cell components are replaced with a unitized regenerative fuel cell system ^[23].

In addition, to using PEMFC, solid oxide fuel cell (SOFC) has been proposed to build IPVFC systems as a potential replacement for diesel generators. This can use a liquid fuel, a solid fuel, or a natural gas reformer to process the fuel ^[24]. The reformation process may include a water gas shift reaction ^[25] to produce hydrogen that can be

utilized to generate power using PEMFC component. Tejwani and Suthar ^[26] investigated the use of PV and SOFC components for power generation using P-Q control approach. A 50 kW PV array served as the basic power source while a 30 kW SOFC acted as the backup. SOFC can be integrated with micro-turbine ^[27][28] and/or thermophotovoltaic (TPV) module ^[29] for co-generation or multi-generation systems because of the high operating temperature of SOFC. As an example, Arsalis et al. ^[30] integrated 70 kW PV arrays with 137.5 kW SOFC for CHP application. In addition, a TPV component can be used to recover exhaust heat from high temperature of SOFC (800–1000 °C) for power generation regardless of the weather conditions, unlike solar photovoltaic systems that depend on solar radiation ^[31]. Systems composed of TPV and SOFC components could evolve considering the renewed interests in TPV applications ^[32][33]. **Figure 5** shows a configuration in which waste heat from the SOFC component can be recovered for power generation using a thermophotovoltaic component. Although the integration of SOFC with PV or TPV could result in a multi-generation system, the steam reform process of solid, liquid, or gaseous fuels produces carbon dioxide unlike the use of PEME in conjunction with PEMFC or URPEMFC which are cleaner alternatives. Direct ammonia fuel cells (AFC) ^[34] is another type of fuel cell that has been proposed for IPVFC systems, although it has a complex fuel processing characteristics compared to a PEMFC component.



Figure 5. Block diagram of an IPVFC system including SOFC and TPV components.

An essential component which applies to all the categories of IPVFC systems is the maximum power point tracker (MPPT). It ensures that the maximum power is extracted from PV modules based on the available solar radiations, regardless of weather conditions. Examples of MPPT algorithm and implementation methodologies are perturb and observe method, incremental conductance method, short-circuit current method, open circuit voltage method, fuzzy logic controllers, and artificial neural network controllers ^{[35][36]}. Karami et al. ^[37] used MPPT and compensators to extract the maximum power from the PV modules and FCs as the demand for power varied with time. Padmanaban et al. ^[38] demonstrated how the Jaya-based MPPT method can be used to track the MPP of PV modules for an IPVFC system. Energy management system (EMS) or Power management system (PMS) is also necessary for controlling the energy flow in an integrated IPVFC system. Equally important for optimal operating conditions of IPVFC systems are the ancillaries and health monitoring of components such as compressors, pumps, fan/blowers, charge controller for the batteries, as well as sensors to measure temperature, pressure, mass flow rates, and humidity. The compressors are used to store gases from the PEME in tanks or for feeding the

reactant gases into the fuel cell component as illustrated in **Figure 3**. Pumps are required to feed water into the electrolyser or PV/T components. Fans/blowers are used to cool the temperature of the components such as the batteries, PEME and PEMFC. In the design phase of IPVFC systems, the power consumed by the ancillaries are discounted from the power produced by the system. The deductions are done to ensure that the power consumed by the ancillaries are considered during capacity sizing of an IPVFC system. Touati et al. ^[39] assumed that 20% of a 12 kW installed capacity is consumed by the ancillaries to cool the PEMFC and pressurize gases. To enhance the reliability of the system, power supply to the ancillaries were configured so that the ancillaries for the PEMFC are not connected to the PV modules since it is subject to intermittency; although the ancillaries of the PEME can be connected to the PV modules since electrolysis can take place during the day.

Sizing of IPVFC systems depends on the load profile of the application ^[40]. Accurate sizing is a major challenge with IPVFC system deployment due to the intermittency of solar radiation. The interrelationships between the dynamic load profile, power generation, hydrogen generation and solar radiation availability require reliable control strategies ^[41]. During operation of an IPVFC system, the amount of hydrogen consumed by an FC stack is proportional to the power drawn from the FC stacks; while the hydrogen produced from the electrolyser is proportional to the power supplied to the electrolyser ^[42]. The power available for hydrogen production depends on the solar availability, the power consumed by the loads, the power consumed by the ancillaries, the power used for charging batteries/SC components and the power lost due to conversion losses. Hourly load current can be multiplied by the number of hours of operation of an IPVFC system to get the daily load ^[41]. This means that the ampere-hour for all the load components/ancillaries can be added to estimate the expected capacity of the system.

Table 1 summarizes some studies to highlight the design intents and compositions of some IPVFC systems.

Year	References	Description of Project/Study	Photovoltaic Array Size	Electrolyser Capacity	Fuel Cell Capacity	Battery Capacity
2020	Lokar and Virtic ^[12]	IPVFC designed to be self-sufficient and independent of the grid.	24 polycrystalline PV modules (280 W each).	7 kW Alkaline electrolyser, 12.5 V and 400 A. Produces 1.66 m ³ h ⁻¹ .	70-celled 7 kW PEMFC with power density of 533.3 mW cm ⁻² and current density of 800 A cm ⁻²	6.6 kWh Li- ion battery.
2020	Hassani et al. ^[<u>43</u>]	Stand-alone IPVFC system with 500 W inverter, 0.02 m ³ and 30 Pa hydrogen tank.	640 Wp, 8 panels, 2 in series and 4 in parallel.	PEME is used as a reverse of PEMFC.	PEMFC with 510 W capacity.	100 Ah, 4 batteries, 2 in series and 2 in parallel.

 Table 1. Description of key studies on IPVFC systems.

Year	References	Description of Project/Study	Photovoltaic Array Size	Electrolyser Capacity	Fuel Cell Capacity	Battery Capacity
2019	Shaygan et al. ^[44]	Energy, exergy, and economic analysis of IPVFC system. Exergy efficiency is 21.8%; cost of electricity is USD 0.127 (kWh) -1.	64 PV modules with area of 2.16 m ² (329 W each).	PEME with daily output of 158 kg	5.5 kW PEMFC.	Not used
2010	Ganguly et al. ^[16]	IPVFC powers stand-alone 90 m ² floriculture Greenhouse.	51 PV module, 75 Wp each	3.3 kW PEME	2 PEMFC, 480 W each	Not used
2009	Cetin et al. [<u>45</u>]	Demonstration system at Pamukkale University in Denizli, Turkey	5 kWp PV array.	PEME consumes 6.7 kWh m ⁻³ power and produced 0.53 m ³ h ⁻¹ of hydrogen.	2.4 kWp PEMFC.	12 V; 150 Ah dry cell batteries.
2003	Ghosh et al. ^[1] and Meurer et al. ^[5]	PHOEBUS is an IPVFC system demonstration plant connected to 220 V DC-busbar.	Each PV contains 600 cells in series to give 220 V.	21-celled Alkaline (KOH) electrolyser with 26 kW capacity at 35– 37 V, 3000 A m ⁻² , 7 bar and 80 °C.	33-celled PEMFC with a capacity of 5.6 kW at 35 V and 200 A, 2– 2.3 bar, and 80 °C.	110 Lead acid battery at 138 Ah in series. Capacity is 303 kWh (at 10 A).

Within the categories of IPVFC systems, different types of PV cells, fuel cell and electrolyser can be used. For instance, Lead acid ^[5], Li-ion ^[12] batteries and supercapacitors ^[13] were considered as potential energy storage components for IPVFC systems. Hydrogen can be stored as a compressed gas in tanks ^[1] or in metal hydride storage ^[45]. Alkaline electrolyser ^[12] or PEME ^[43] can be used as a source of hydrogen. PEME is adapted to compensate for the possible fluctuations of solar energy because of its fast response to current fluctuations. The US Department of Energy found out that a PEME produces hydrogen at 99.99% of purity level for less than USD 10/kg. This high level of purity of hydrogen is suitable for the operation of PEMFC. The current density is 4–5 times that of an alkaline electrolyser and it uses no corrosive electrolyte unlike alkaline electrolyser, although alkaline electrolyser is more matured technologies ^{[46][47]}. PEMFC is widely used for IPVFC applications since it uses hydrogen ^[43] which can be generated from water electrolysis using excess electricity from the PV array. Polycrystalline solar cells.

2. Current and Emerging Applications of IPVFC Systems

2.1. Application of IPVFC Systems in Microgrids

Microgrids are important in the utilization of renewable energy resources because they can facilitate distributed energy infrastructures in which energy can be generated close to the end-users. Ghenai and Bettayeb ^[48] studied the integration of a 500 kW PV array and a 100 kW PEMFC with the grid to supply power to a University building in Sharjah, United Arab Emirate. The demand was met although 26% of the power consumed was purchased from the grid. The supply mix includes 42% of the power from the PV array and 32% from the PEMFC stack while 5% of the annual output was sold to the grid. Sharma and Mishra ^[49] proposed a dynamic power management scheme for stand-alone micro-grid in which all the sources, energy storage and loads were connected to a DC link. Hidaka and Kawahara ^[50] asserted that efficient application of the grid-connected PV arrays for domestic applications requires energy storage which can be facilitated by using solar hydrogen as energy vector to compensate for the fluctuations in power generation due to the intermittency of solar radiation and ambient temperature.

2.2. Off-Grid/Stand-Alone Applications of IPVFC Systems

The dependence of IPVFC systems on solar radiation makes them suitable for remote power sources for autonomous residential applications, telecommunication infrastructure, agro-processing, research activities, sporting facilities and leisure in remote locations. Ulleberg ^[51] posited that PV arrays, fuel cell and water electrolysis could play a major role in the future stand-alone power systems. Silva et al. [52] conducted a pilot study on the use of an IPVFC system in the National Park of Araguaia, Tocantins-Brazil. Based on their findings, the noiseless and clean attributes make it suitable for distributed generation applications in public spaces such as train stations, zoos, museums, libraries, motor parks/bus stations, markets, etc. This is particularly useful in many underdeveloped countries where public utilities operate without electricity, water, refrigeration of food and drinks, air-conditioning of spaces, lighting, and entertainment. Cordiner et al. ^[53] analyzed a full year of data collected from six remote off-grid Radio Based Stations (RBS) and found that an IPVFC system can meet 24 h/7 day high guality, autonomous and continuous power supply required by an off-grid RBS, particularly in developing countries where power grids are grossly underdeveloped. Another study by Silva et al. [54] showed that it was feasible to use an IPVFC system for power generation in an isolated community in the Amazon region of Brazil. The system was composed of a PV array of 124 W with 30.1 V, a PEMFC at 5 kW at 48 V; a PEME at 6 kW per Nm³ h⁻¹ of hydrogen produced; and a lead acid battery (220 Ah at 12 V). The study implied that the costs of the components are still high but using a battery for energy storage appeared to be favored since the cost of adding an electrolyser and a fuel cell will increase the cost of the system. Based on economic analysis, a PV-battery system is cheaper than an IPVFC system of similar capacity, but the inclusion of a fuel cell can protect the battery from stresses associated with the depth of discharge, thereby elongating the life of the battery, and reducing the overall replacement costs of the battery.

An IPVFC system can be used in the agricultural sector for all-year-round crop and animal production and agroprocessing given that it can be operated under distributed and off-grid modes. This allows farmers to meet shortterm needs using PV arrays, batteries/supercapacitors, and long-term needs with an electrolyser and fuel cell stacks. Since solar radiation is abundant during summer, excess electricity can be stored as hydrogen so that power can be supplied during winter when solar intensity usually dwindles. Ganguly et al. ^[16] studied how an IPVFC system can be used to power a greenhouse in a sustainable manner based on the climatic conditions of Kolkata, India. They used 51 solar PV modules to generate hydrogen with an electrolyser (3.3 kW) and charge a battery bank such that the battery bank and two PEM fuel cell stacks (480 W each) can meet the energy demand. IPVFC systems can be used for desalination to convert seawater, brackish water, or fresh water of unknown quality to potable water as well as generate electricity and hydrogen. A feasibility study of seawater electrolysis using an IPVFC system has been conducted to generate hydrogen and oxygen from salty water instead of using fresh water which is better used for domestic, agricultural, and industrial purposes ^[55]. The presence of NaCl was reported to enhance hydrogen production and the system also produced fresh water as a by-product. Touati et al. ^[39] studied the potential application of an IPVFC system to provide a stand-alone power source for a desalination plant.

References

- 1. Ghosh, P.C.; Emonts, B.; Janßen, H.; Mergel, J.; Stolten, D. Ten years of operational experience with a hydrogen-based renewable energy supply system. Sol. Energy 2003, 75, 469–478.
- Ogbonnaya, C.; Turan, A.; Abeykoon, C. Modularization of integrated photovoltaic-fuel cell system for remote distributed power systems. In Industry 4.0—Shaping The Future of The Digital World; Da Silva Bartolo, P.J., da Silva, F.M., Jaradat, S., Bartolo, H., Eds.; CRC Press: Manchester, UK, 2020; pp. 303–308. ISBN 9780367823085.
- 3. Gebre, T.S. Fuel Cell Assisted PhotoVoltaic Power Systems; Norwegian University of Science and Technology: Trondheim, Norway, 2012.
- Tlili, N.; Neily, B.; Ben Salem, F. Modeling and simulation of hybrid system coupling a photovoltaic generator, a PEM fuel cell and an electrolyzer (Part II). In Proceedings of the 2014 IEEE 11th International Multi-Conference on Systems, Signals and Devices, SSD 2014, Barcelona, Spain, 11–14 February 2014.
- Meurer, C.; Barthels, H.; Brocke, W.A.; Emonts, B.; Groehn, H.G. PHOEBUS—an autonomous supply system with renewable energy: Six years of operational experience and advanced concepts. Sol. Energy 1999, 67, 131–138.
- 6. Arshad, A.; Ali, H.M.; Habib, A.; Bashir, M.A.; Jabbal, M.; Yan, Y. Energy and exergy analysis of fuel cells: A review. Therm. Sci. Eng. Prog. 2019, 9, 308–321.
- 7. Ogbonnaya, C.; Turan, A.; Abeykoon, C. Energy and exergy e ffi ciencies enhancement analysis of integrated photovoltaic-based energy systems. J. Energy Storage 2019, 26, 101029.
- Sharaf, O.Z.; Orhan, M.F. An overview of fuel cell technology: Fundamentals and applications. Renew. Sustain. Energy Rev. 2014, 32, 810–853.

- Wilberforce, T.; El-Hassan, Z.; Khatib, F.N.; Al Makky, A.; Baroutaji, A.; Carton, J.G.; Olabi, A.G. Developments of electric cars and fuel cell hydrogen electric cars. Int. J. Hydrogen Energy 2017, 42, 25695–25734.
- 10. Das, H.S.; Tan, C.W.; Yatim, A.H.M. Fuel cell hybrid electric vehicles: A review on power conditioning units and topologies. Renew. Sustain. Energy Rev. 2017, 76, 268–291.
- 11. Whiteman, Z.S.; Bubna, P.; Prasad, A.K.; Ogunnaike, B.A. Design, operation, control, and economics of a photovoltaic/fuel cell/battery hybrid renewable energy system for automotive applications. Processes 2015, 3, 452–470.
- Lokar, J.; Virtič, P. The potential for integration of hydrogen for complete energy self-sufficiency in residential buildings with photovoltaic and battery storage systems. Int. J. Hydrogen Energy 2020, 45, 34566–34578.
- Thounthong, P.; Chunkag, V.; Sethakul, P.; Sikkabut, S.; Pierfederici, S.; Davat, B. Energy management of fuel cell/solar cell/supercapacitor hybrid power source. J. Power Sources 2011, 196, 313–324.
- Jayalakshmi, N.S. Study of hybrid photovoltaic/fuel cell system for stand-alone applications. In Current Trends and Future Developments on (Bio-) Membranes: Renewable Energy Integrated with Membrane Operations; Elsevier: Amsterdam, The Netherlands, 2018.
- Amin; Bambang, R.T.; Rohman, A.S.; Dronkers, C.J.; Ortega, R.; Sasongko, A. Energy management of fuel cell/battery/supercapacitor hybrid power sources using model predictive control. IEEE Trans. Ind. Inform. 2014, 10, 1992–2002.
- Ganguly, A.; Misra, D.; Ghosh, S. Modeling and analysis of solar photovoltaic-electrolyzer-fuel cell hybrid power system integrated with a floriculture greenhouse. Energy Build. 2010, 42, 2036– 2043.
- Jiang, Z. Power management of hybrid photovoltaic—Fuel cell power systems. In Proceedings of the 2006 IEEE Power Engineering Society General Meeting, PES, Montreal, QC, Canada, 18–22 June 2006.
- Jang, M.; Agelidis, V.G. A minimum power-processing-stage fuel-cell energy system based on a boost-inverter with a bidirectional backup battery storage. IEEE Trans. Power Electron. 2011, 26, 1568–1577.
- 19. Kalogirou, S.A. Solar thermal collectors and applications. Prog. Energy Combust. Sci. 2004, 30, 231–295.
- 20. Ogbonnaya, C.; Abeykoon, C.; Nasser, A.; Ume, C.S.; Damo, U.M.; Turan, A. Engineering risk assessment of photovoltaic-thermal-fuel cell system using classical failure modes, effects and criticality analyses. Clean. Environ. Syst. 2021, 2, 100021.

- 21. Burke, K.A.; Jakupca, I. Unitized Regenerative Fuel Cell System Gas Storage/Radiator Development; SAE Technical Papers 2004-01-3168; SAE: Warrendale, PA, USA, 2004.
- Millet, P.; Ngameni, R.; Grigoriev, S.A.; Fateev, V.N. Scientific and engineering issues related to PEM technology: Water electrolysers, fuel cells and unitized regenerative systems. Int. J. Hydrogen Energy 2011, 36, 4156–4163.
- 23. Ogbonnaya, C.; Abeykoon, C.; Nasser, A.; Turan, A. Unitized regenerative proton exchange membrane fuel cell system for renewable power and hydrogen generation: Modelling, simulation, and a case study. Clean. Eng. Technol. 2021, 4, 100241.
- 24. Ferrari, M.L.; Damo, U.M.; Turan, A.; Sanchez, D. Hybrid Systems Based on Solid Oxide Fuel Cells: Modelling and Design; Wiley: Hoboken, NJ, USA, 2017.
- 25. Holladay, J.D.; Hu, J.; King, D.L.; Wang, Y. An overview of hydrogen production technologies. Catal. Today 2009, 139, 244–260.
- 26. Tejwani, V.; Suthar, B. Power management in fuel cell based hybrid systems. Int. J. Hydrogen Energy 2017, 42, 14980–14989.
- 27. Damo, U.M.; Ferrari, M.L.; Turan, A.; Massardo, A.F. Solid oxide fuel cell hybrid system: A detailed review of an environmentally clean and efficient source of energy. Energy 2019, 168, 235–246.
- 28. Damo, U.M.; Ferrari, M.L.; Turan, A.; Massardo, A.F. Re-compression model for SOFC hybrid systems: Start-up and shutdown test for an emulator rig. Fuel Cells 2015, 15, 42–48.
- 29. Rajashekara, K. Hybrid fuel-cell strategies for clean power generation. IEEE Trans. Ind. Appl. 2005, 41, 682–689.
- 30. Arsalis, A.; Georghiou, G.E. Thermoeconomic optimization of a hybrid photovoltaic-solid oxide fuel cell system for decentralized application. Appl. Sci. 2019, 9, 5450.
- 31. Daneshvar, H.; Prinja, R.; Kherani, N.P. Thermophotovoltaics: Fundamentals, challenges and prospects. Appl. Energy 2015, 159, 560–575.
- 32. Ogbonnaya, C.; Abeykoon, C.; Nasser, A.; Turan, A. Radiation—Thermodynamic Modelling and Simulating the Core of a Thermophotovoltaic System. Energies. 2020, 13, 6157.
- 33. Bauer, T. Thermophotovoltaics: Basic principles and critical aspects of system design. Green Energy Technol. 2011, 7.
- 34. Siddiqui, O.; Dincer, I. Development and evaluation of a solar-based integrated ammonia synthesis and fuel cell system. J. Clean. Prod. 2020, 256, 120393.
- 35. Sumathi, S.; Ashok Kumar, L.; Surekha, P. Solar PV and Wind Energy Conversion Systems; Springer: Heidelberg, Germany, 2015; ISBN 978-3-319-14940-0.

- 36. Saravanan, S.; Ramesh Babu, N. Maximum power point tracking algorithms for photovoltaic system—A review. Renew. Sustain. Energy Rev. 2016, 57, 192–204.
- 37. Karami, N.; Moubayed, N.; Outbib, R. Energy management for a PEMFC-PV hybrid system. Energy Convers. Manag. 2014, 82, 154–168.
- Padmanaban, S.; Priyadarshi, N.; Bhaskar, M.S.; Holm-Nielsen, J.B.; Hossain, E.; Azam, F. A Hybrid Photovoltaic-Fuel Cell for Grid Integration with Jaya-Based Maximum Power Point Tracking: Experimental Performance Evaluation. IEEE Access 2019, 7, 82978–82990.
- Touati, S.; Belkaid, A.; Benabid, R.; Halbaoui, K.; Chelali, M. Pre-feasibility design and simulation of hybrid PV/fuel cell energy system for application to desalination plants loads. Procedia Eng. 2012, 33, 366–376.
- Hassani, H.; Rekioua, D.; Aissou, S.; Bacha, S.; Zaouche, F. Hybrid stand-alone photovoltaic/batteries/fuel cells system for green cities. In Proceedings of the 2018 6th International Renewable and Sustainable Energy Conference, IRSEC 2018, Rabat, Morocco, 5–8 December 2018.
- 41. Hwang, J.J.; Lai, L.K.; Wu, W.; Chang, W.R. Dynamic modeling of a photovoltaic hydrogen fuel cell hybrid system. Int. J. Hydrogen Energy 2009, 34, 9531–9542.
- 42. Lajnef, T.; Abid, S.; Ammous, A. Modeling, control, and simulation of a solar hydrogen/fuel cell hybrid energy system for grid-connected applications. Adv. Power Electron. 2013, 2013, 352765.
- 43. Hassani, H.; Zaouche, F.; Rekioua, D.; Belaid, S.; Rekioua, T.; Bacha, S. Feasibility of a standalone photovoltaic/battery system with hydrogen production. J. Energy Storage 2020, 31, 101644.
- 44. Shaygan, M.; Ehyaei, M.A.; Ahmadi, A.; Assad, M.E.H.; Silveira, J.L. Energy, exergy, advanced exergy and economic analyses of hybrid polymer electrolyte membrane (PEM) fuel cell and photovoltaic cells to produce hydrogen and electricity. J. Clean. Prod. 2019, 234, 1082–1093.
- 45. Cetin, E.; Yilanci, A.; Oner, Y.; Colak, M.; Kasikci, I.; Ozturk, H.K. Electrical analysis of a hybrid photovoltaic-hydrogen/fuel cell energy system in Denizli, Turkey. Energy Build. 2009, 41, 975–981.
- 46. Targets, T.; Barriers, T. II.H.1 Low-Cost, High-Pressure Hydrogen Generator. Program 2010, 190– 193.
- 47. Carmo, M.; Fritz, D.L.; Mergel, J.; Stolten, D. A comprehensive review on PEM water electrolysis. Int. J. Hydrogen Energy 2013, 38, 4901–4934.
- 48. Ghenai, C.; Bettayeb, M. Grid-Tied Solar PV/Fuel Cell Hybrid Power System for University Building. Energy Procedia 2019, 159, 96–103.

- 49. Sharma, R.K.; Mishra, S. Dynamic Power Management and Control of a PV PEM Fuel-Cell-Based Standalone ac/dc Microgrid Using Hybrid Energy Storage. IEEE Trans. Ind. Appl. 2018, 54, 526–538.
- 50. Hidaka, Y.; Kawahara, K. Modeling of a hybrid system of photovoltaic and fuel cell for operational strategy in residential use. In Proceedings of the 2012 47th International Universities Power Engineering Conference (UPEC), Uxbridge, UK, 4–7 September 2012.
- 51. Ulleberg, O. Stand-Alone Power Systems for the Future: Optimal Design, Operation and Control of Solar-Hydrogen Energy Systems; Norwegian University of Science and Technology Trondheim: Trondhein, Norway, 1998.
- 52. Silva, S.B.; De Oliveira, M.A.G.; Severino, M.M. Sizing and optimization of hybrid photovoltaic, fuel cell and battery system. IEEE Lat. Am. Trans. 2011, 9, 817–822.
- Cordiner, S.; Mulone, V.; Giordani, A.; Savino, M.; Tomarchio, G.; Malkow, T.; Tsotridis, G.; Pilenga, A.; Karlsen, M.L.; Jensen, J. Fuel cell based Hybrid Renewable Energy Systems for offgrid telecom stations: Data analysis from on field demonstration tests. Appl. Energy 2017, 192, 508–518.
- 54. Silva, S.B.; Severino, M.M.; De Oliveira, M.A.G. A stand-alone hybrid photovoltaic, fuel cell and battery system: A case study of Tocantins, Brazil. Renew. Energy 2013, 57, 384–389.
- 55. Srisiriwat, A.; Pirom, W. Feasibility Study of Seawater Electrolysis for Photovoltaic/Fuel Cell Hybrid Power System for the Coastal Areas in Thailand. In Proceedings of the IOP Conference Series: Materials Science and Engineering, Tokyo, Japan, 9–11 June 2017.

Retrieved from https://encyclopedia.pub/entry/history/show/36879