# **Plant-Based Meat Analogues from Alternative Protein**

Subjects: Food Science & Technology

Contributor: Izalin Zahari, Karolina Östbring, Jeanette K. Purhagen, Marilyn Rayner

Meat is a major source of dietary protein. It is frequently recognized as a high-quality protein source due to its nutritional qualities and favorable sensory properties such as texture and flavor. However, a rising global population has led to a rise in the production and consumption of meat around the world, which has raised environmental concerns regarding the usage of land and water, as well as the impact of pollution and climate change, greenhouse gas emissions, and the loss of biodiversity. Plant proteins seem to be a possible solution to these issues since they can replace meat through the creation of nutritionally and structurally equivalent meat-like products. These products are referred to as meat substitutes. Some terminology for meat substitutes includes meat replacers, meat analogues, meat imitations, nonmeat protein alternatives, meatless meats, man-made meats, artificial meats, meat-like meats, mock meats, faux meats, and fake meats. These can be partial or full substitutes for meat, and there is an extensive range of textures. The term "meat analogue" usually refers to products that have a similar look, texture, taste, and color to meat but do not include any meat.

Keywords: bibliometric analysis ; meat analogues ; meat substitutes ; high-moisture meat analogues (HMMA)

### 1. Type of Plant Proteins Used

#### Soy Protein as Primary Component

In this first sub-theme, it was discovered that experts had focused their attention on soy protein (either in the form of flour, concentrate, or isolate) as the primary component in textured protein products for years. Soy protein is used either by mixing it directly in the formulation of meat substitutes together with other ingredients, or by processing it via texturizing techniques into TVP or HMMA. Soy garnered interest for its protein quality and because it has satisfactory functional qualities (such as the ability to absorb water and oil and its emulsifying properties), and it has been used in the production of a variety of unique meat substitutes. As a result of the excellent features that soy has, it is usually used as a standard or benchmark to compare different protein materials <sup>[1]</sup> and as a model to explore many other aspects of meat analogues <sup>[2]</sup>, texturizing techniques <sup>[3]</sup>, extrusion parameters <sup>[4]</sup>, and product structure <sup>[5][6][2]</sup>. Dahl and Villota <sup>[8]</sup> used soy flour altered with acid (HCl) or base (NaOH) and studied the pH effects on the functional properties of soy protein. Liu and Hsieh <sup>[9]</sup> used two commercial soy protein isolates to study the fibrous meat analogues produced through high moisture extrusion or gels via heating and chilling, with different concentrations and/or temperatures. Due to its lower cost, soy protein concentrates (SPCs) are widely utilized as an alternative to soy protein isolate (SPI). Pietsch et al. <sup>[10]</sup> reported that SPCs may produce more prominent anisotropic (properties of materials depending on the direction) structures than SPI. Two other studies using high-moisture extrusion of soy meat analogues (SPCs) were conducted by Palanisamy et al. <sup>[11]</sup> and Chiang et al. <sup>[12]</sup>.

#### Soy Protein Combined with Other Plant Proteins

Researchers started to use commercial soy protein isolates/concentrate together with other protein sources in order to reduce the use of soy protein, and also to study their combination, establish texturization conditions, and to aim to diversify meat products in the market with different formulations, as discovered by many researchers <sup>[4][13][14][15]</sup>. Kozlowska et al. <sup>[16]</sup> used high- and low-pressure processing to texturize the flours and concentrates that were derived from soybean and rapeseed, as well as the blends of soybean and rapeseed (1:1). When combined with additional plant proteins, the extruded meat analogues were found to be of higher quality. Numerous researchers have found that by combining soy protein and wheat gluten, meat substitutes might match the texture, color, flavor, and function of red meat, as well as enhance the disulphide bonds to generate a fibrous structure <sup>[12][17][18]</sup>. In the investigation of the total heat transfer coefficient in extrusion processing conducted by Lee et al. <sup>[19]</sup>, meat analogues were mixed with another established protein and wheat starch. In a separate investigation, Liu and Hsieh <sup>[20]</sup> and Ranasinghesagara et al. <sup>[21]</sup> similarly co-extruded soy protein with wheat gluten and starch to produce fibrous meat analogues under high-moisture and high-temperature conditions. According to prior studies by Neumann et al. <sup>[22]</sup>, non-heated corn gluten (CG) demonstrated superior functional performance compared to heat-dried corn gluten meal. Thus, wet-milled corn gluten and

defatted soy flour (DSF) were combined and extruded to produce textured meals afterwards. Hemp protein could also be mixed with soy protein isolate up to 60% in the formulation of high moisture meat analogues, as reported in a previous study <sup>[4]</sup>. In the context of restructured meat analogues, mushrooms, which contain high levels of sulphur-containing amino acids, and glutamic acid, which implies a distinctive umami taste, are the materials that are mostly used, as they closely resemble those with a natural meaty flavor and texture.

#### **Alternative Proteins without Soy Protein**

The second sub-theme pertained to alternative plant proteins used in previous studies. Researchers examined other protein resources to completely replace soy protein in the formulations. This interest is due to other factors, including GMO issues, allergies, and an unfavorable climate for soy cultivation. However, in thermomechanical processing that involves texturizing equipment, it is impossible to make great meat analogues without the use of components that have a high percentage of protein. To develop a comprehensive fibrous structure similar to actual tissue, extrusion, shear cell, and spinning technologies, for example, need ingredients with a high protein concentration. Several studies showed promising protein ingredients such as pea protein [23][24], mucuna beans [25], peanut protein [26][27], and faba beans [28][29]. The majority of the plant-based proteins (such as those found in legumes and oilseeds, for example) contain undesirable components such as anti-nutrients (glucosinolates, phenolic compounds, and phytic acid) and inhibitors of digestive enzymes. These components reduce the nutritional value and acceptability of plant-based proteins and impart an unpleasant flavor such as bitterness. To be accepted by consumers as meat analogues, these undesirable components must be eliminated by certain pre-treatments before being used. Those treatments used together with the protein extraction process, on the other hand, lead to a loss of functional gualities as well as reduction of the protein's guality and quantity. This is by far the most challenging obstacle to overcome when researching and developing novel plant protein materials. Because various plants have varying protein types and qualities, numerous efforts have been made to create a novel blend of several plant proteins with the hope that some proteins may compensate for the drawbacks of other plant proteins during the texturization process. For example, Kozlowska et al. [16] and Zahari et al. [30] suggested that rapeseed protein would be a good source for supplementing other vegetable proteins, e.g., soybean and yellow pea. Arueya et al. [31] created meat analogues from Lima bean protein concentrate (LBPC) and African oil bean seed concentrate (AOBSPC), which are underutilized legumes with high nutritional potential grown mainly in Peru.

# 2. Product Type

Two sub-themes were developed under this theme: texturized vegetable protein (TVP), and meat analogues (MA). Regarding nomenclature, there is a considerable degree of disagreement among professionals, with some arguing that extrudates from extruders cannot be referred to be meat analogues, while others disagree. Some researchers suggest that the extrudates are not intended for immediate consumption but rather as meat extenders that will be sliced and combined with other substances to form a restructured meat substitute. Thus, depending on the publication, some of the studied research referred to the extruded product as extrudates or meat analogues, while others referred to it as TVP and utilized it as a replacement for meat. Researchers categorized the terms based on the information provided in the research, including the final restructured meat-substitute products, which are normally referred to as nuggets, sausages, or patties and may contain added ingredients according to the formulations.

#### **Texturized Vegetable Protein (TVP)**

In 1978, Hashizume <sup>[3]</sup> studied a traditional method of manufacturing Koritofu to convert protein into a textured product using a freezing method. In comparison to the other temperatures that were evaluated in the research, such as -5 and -70 °C, it was claimed that the temperature of -20 °C was the one that successfully created the spongy protein that could be utilized as a replacement for animal flesh. According to Kozlowska et al. <sup>[16]</sup>, who used two different models of extruder, the high-pressure technique produces a product with a specialized purpose as a meat extender, whereas the low-pressure technique produces a product that is suitable for developing meat analogues. However, Neumann et al. <sup>[22]</sup> defined the product as TVP when it was produced by low-pressure extrusion at pressures around 100–200 psi. On the other hand, according to Maung et al. <sup>[32]</sup>, TVP is often used as a meat extender or directly as meat analogues in hamburger patties, sausages, steak, sliced meats, and many other products. Bakhsh et al. <sup>[33]</sup> recently revealed that TVP, when used as a major ingredient in hamburgers, had characteristics comparable to those of hamburgers made from beef and pork. However, it was noted in his other study that the surface of the patties that were made from TVP and texturized SPI both had a granular look, which is a downside of employing those two ingredients <sup>[34]</sup>. While using chickpea flour and TVP, Sharima-Abdullah et al. <sup>[35]</sup> produced an imitation of chicken nuggets, which was stated to be a promising product.

In terms of meat analogues, several researchers developed the products directly as whole muscle meat (mostly from extrusion) with or without some added ingredients <sup>[28][36][37][38]</sup>, but others referred to meat analogues as restructured meat products such as Turkish dry fermented sausages ("sucuk") from wheat bulgur <sup>[39]</sup>, SPI sausage <sup>[40]</sup>, and edible mushroom sausages <sup>[41][42]</sup>. The study by Rousta et al. <sup>[43]</sup>, who investigated the culture of the fungus on oat flour and its use in the development of burger patties, demonstrated the productive potential of the fungus for the manufacture of nutrient-dense foods. Saldanha do Carmo and colleagues <sup>[29]</sup> used response surface methodology (RSM) to optimize the manufacturing of meat analogues made entirely of faba bean protein concentrate acquired by a dry-fractionation technique, which also showed promising results.

### 3. Added Ingredient Used to Improve Texturized Products

#### **Binding Agents**

When making textured vegetable protein products or meat substitutes, it is a common practice to use some amount of additives or chemicals in order to expand the range of raw materials suitable for use in production <sup>[19]</sup>. Many different binding agents have been utilized as fat replacers to increase the quality of TVP or restructured meat (for example, sausage, nugget, and patty). This has been done to improve the taste, juiciness, mouthfeel, and other sensory qualities. Examples of such additions are starch, fibers, soy and milk proteins, a variety of hydrocolloids, and egg solids. Because the scope is limited to plant-based products, researchers will not include any materials derived from animal sources; as a result, researchers will only count a few studies. Arora et al. [44] investigated the effect of various quantities of binding agents (carrageenan, soy protein concentrate, casein, and xanthan gum) on the qualitative features and nutritional qualities of mushroom-based sausage analogues prepared with 5% saturated fat. Carrageenan (0.8%) had the greatest outcomes in terms of minimizing purge loss, cook loss, and emulsion stability, all of which improved the process output. It was reported that methylcellulose (MC) is an effective binder, particularly for the meat analogues that do not need to be preheated for gel formation, because of its one-of-a-kind thermal gelling ability and emulsifying qualities [33]. Contradictorily, Sakai et al. [45] developed an alternative new binding mechanism, since chemicals are used in the production of methylcellulose. The results suggest that the protein-sugar beet pectin crosslink catalyzed by laccase may serve as a binding mechanism for the TVP patties. In addition, microbial transglutaminase (TG) and sodium alginate (AL) are two binding agents that are often employed in food preparation. Each of these binding agents functions in distinct ways for protein binding or gelling systems <sup>[39][45][46]</sup>. The researchers suggest that the combination of TG and AL may synergistically affect the eating quality of soy patties, although more improvements are required. While AL has an advantage in the creation of restructured meat because it can create a thermostable and irreversible gel (in the presence of Ca2+), TG has been used as a cold-set binder since it catalyzes covalent bonds between the ε-amino group (a primary amine) of peptide-bound lysine and the v-carboxamide group of peptide-bound glutamine [39][45].

#### Fat/Oil

In order to reduce the saturated fatty acid and cholesterol levels of certain restructured meat substitutes, animal fats were substituted by vegetable oils such as olive oil <sup>[39][45]</sup>, palm oil <sup>[47]</sup>, canola oil, and coconut oil <sup>[33][34]</sup>. Depending on the raw materials, oil is used in different amounts to obtain a more meat-like texture and to increase the flavor, juicy quality, tenderness, and several other qualities of MA related to sensorial experience. For example, Mazlan et al. <sup>[47]</sup> used 10% palm oil in the soy-mushroom extrusion mixture. Kamani et al. [40] used 8% oil in SPI-gluten sausage analogues, Bakhsh et al. [34] used a total of 7.5% of oil in the TVP patty formulation, while Saerens et al. [48] used fat emulsion from pea protein and rapeseed oil in the soy and pumpkin seed protein-based burger patty formulation. It has been observed that fat has an influence on thermal-mechanical processing as a lubricating agent and helps to accelerate the creation of protein alignment networks. Recent research conducted by Kendler and colleagues [49] investigated the impact that oil (0-6%) had on the extrusion-relevant parameters and structure-related properties of extruded wheat gluten. According to the results, using oil in the high-moisture extrusion led to a significant change in the process conditions, as well as in the rheological properties and product qualities. The oil concentration and addition point were discovered to have an impact on the size of the oil droplets. The size of the oil droplets became larger as the oil content increased, indicating that the fat droplets were subjected to coalescence. On the other hand, there was a difference in oil droplet size depending on where in the extruder the oil was injected, where injection at the end of the extruder resulted in smaller oil droplets [49]. The anticipation that oil droplet breakage is improved at greater matrix viscosities was supported by these findings. Some protein materials still contain a high content of oil, such as rapeseed protein concentrate <sup>[30]</sup>, which could thus enhance the final product characteristics without adding any fat during thermal-mechanical processing. Nevertheless, too much oil may contribute to the lubricating effect (slippery condition) within the barrel, hindering the protein denaturation process.

In addition to binders and lipids, there are a few other ingredients that are normally added into the formulation of meat analogues, especially restructured meat. For extruded meat analogues, added ingredients such as polysaccharides, colorants, flavoring, and seasoning were used during the cooking process. Exogenous polysaccharides are one of the key additions often employed in the food industry to increase the functional qualities of food proteins and optimize texture, and they were utilized to study the impact of polysaccharides in the meat analogues of peanut protein <sup>[50]</sup>. Since the majority of extruded meat analogues lack flavor and color, adding additional ingredients such as meat flavor powder and red yeast rice is required when incorporating them into restructured meat, as shown in <sup>[41]</sup>. Wen et al. <sup>[51]</sup> studied the effect of calcium stearyl lactylate (CSL) in extrusion processing and found that CSL has the potential to greatly improve the extrudates' textural qualities, including the number of fibrils present and the size of their pores. In terms of restructured meat, the taste of patties and sausages was improved by the addition of colorant, sugar and salt, flavoring, seasoning, herbs, and spices such as cumin, cinnamon, pepper, and garlic <sup>[34][39][41][42]</sup>. According to Yuliarti et al. <sup>[52]</sup>, the inclusion of calcium chloride and baking powder in the formulation of pea and wheat protein nugget was to boost the protein's ability to bind water and to create air cells in the dough, which might improve the fibrous structure. Carotene and anthocyanin are also being added to enhance the vegetarian sausage analogues; nevertheless, it has been noted that their levels drop with storage, thus requiring additional development <sup>[42]</sup>.

## 4. Type of Texturization Technique

#### Extrusion

Many texturization technique studies have been conducted in recent years, which were classified into five groups: single screw extrusion (SSE), twin screw extrusion (TSE), shear/Couette cell (SC), spinning (S), and mixing/other methods (M/O). For thermal-mechanical processing, high moisture extrusion technology has become a popular method compared to other texturizing methods due to its lower energy consumption, lack of waste to be disposed of, high efficiency, and higher textured product quality [6][28][30][36][37][49][53][54][55][56]. In the past, the production of TVP, which often has a lower moisture content, was mostly done using single-screw extruders [16][25][26][57]. A drawback with TVP is that it must first undergo a rehydration process before being included in the meat substitutes' formulas. Extrusion seems to be becoming increasingly popular since it can be utilized for both low- and high-moisture products. Because of these factors, several experiments were performed to gain an understanding of the relationship between the processing parameters of the extruder and the final product. According to Samard et al. [58], who examined the effect of extrusion type (low- and highmoisture extrusion cooking) on the physicochemical properties of meat substitutes, the cooling die region of HMMAs is thought to be crucial for the cross-link formation. As everyone know, for most plant proteins, a certain pre-treatment (acid or alkaline) is typically required during the extraction process in order to receive a higher yield as well as more desirable extrusion outcomes. Furthermore, extrusion was shown to partly break down phytates in a matrix-dependent way, improving the material's nutritional quality [38]. In addition to the composition of raw materials, various extrusion parameters (screw configuration, temperature set-up, screw speed, solid and liquid dosing, and moisture content), as well as diverse manufacturers, can result in dramatically different product structures and textures, even when using the same raw material. Each processing parameter will influence the product specification during extrusion processing. For instance, most studies investigated the effect of screw speed, water feed, extrusion temperature, and feed rate on the product characteristics [1][10][30][58][59]. Studies showed that water feed was the most influential factor in the extruder process and product qualities, followed by screw speed and barrel temperature [30][60]. Several blocks of barrels could be used in the high-moisture extruder, with the highest temperature ranging from 100 to 180 °C [10][26][58][59][60]. Earlier, Lee et al. [19] calculated the total heat transfer coefficient in a long slit cooling die and discovered that the projected product temperature at the die output was 6.8 °C of the observed experimental value, whereas several researchers investigated the effects of the specific mechanical energy (SME; kJ/kg) <sup>[10][30][61]</sup> and specific thermal energy (STE; kJ/kg) <sup>[62]</sup> on the physicochemical properties of texturized meat analogues. Increasing the screw speed required more energy, but the SME dropped as the moisture content increased [30][62].

#### Shear/Couette Cell

Several studies have suggested the shear cell as a suitable technique for meat analogues production. A cone–cone device (shear cell) and a concentric cylinder device (Couette cell) were created by Krintiras et al. <sup>[63][64][65]</sup> based on the notion of a flow-driven structure. In both devices, a model system of soy protein isolate (SPI) and vital wheat gluten mix was employed, resulting in anisotropic structures that may be used as meat replacers. In 2016, they invented a 7 L Couette cell system for making structured soy meat replacer, and high anisotropy fibers were developed. The up-scaled Couette cell can produce 30 mm thick flesh replacers that mimic meat, which means that the research found no impediments to scaling up the idea. The flexible design enables the manufacturing of meat substitute goods in sizes not previously possible, which might be beneficial in replacing chicken breast or beef <sup>[63]</sup>. According to Jia et al. <sup>[1]</sup>, the

formation of fibrous materials in shear cells is favored when plant materials have two different phases that deform and align when sheared. This can be done by mixing purified ingredients with different water holding capacities, such as soy protein isolate and wheat gluten, or they can be found naturally in a single but less purified ingredient, such as soy protein concentrate. They studied the structuring potential of rapeseed protein concentrate (RPC) with and without wheat gluten (WG) for meat analogues synthesis in a shear cell. Both RPC-only and RPC–WG combinations could become fibrous at 140 °C and 150 °C with 40% dry matter; in addition, WG could enhance the fibrous structure and lighten the color <sup>[1]</sup>.

#### Spinning

In 1972, Stanley et al. <sup>[66]</sup> studied the properties and ultrastructure of rehydrated spun soy fiber and identified structural differences between soy and beef. According to the study, meat contains repeated sarcomeres, connective tissue that affects texture, a sarcolemma or elastic cell membrane, and actin–myosin cross-bridges, whereas spun soy is a uniform, homogenous fiber with disulfide bonds. Byun and colleagues <sup>[67]</sup> designed bench-scale protein spinning equipment in the laboratory with some modifications to the prior approach in order to determine the viability of spinning mixes of soy protein isolates. The discovered method is based on the unfolding of peptide chains by alkali treatment and the molecular orientation of mechanically spun fiber. Electrospinning is one of the techniques investigated recently by Mattice et al. <sup>[68]</sup>, and they modified the electrospinning parameters to produce zein fibers with uniform width while minimizing ethanol consumption. Even though electrospinning produces tiny individual fibers, the technology used was reported to have a very low throughput and thus faced problems with efficiency.

#### **Other Texturization Methods**

In addition to all of the particular thermomechanical and texturizing procedures, there were also other methods being used in exploring and developing meat analogues, such as direct mixing  $^{[40]}$ , freezing  $^{[3]}$ , planetary roller extruder  $^{[11]}$ , mechanical elongation, and antisolvent precipitation  $^{[68]}$ . According to the findings, the majority of meat analogues that employed mixing techniques with other ingredients was restructured meat products such as nuggets, sausages, and patties  $^{[35][40][42][69][70][71]}$ . Furthermore, Nayak et al.  $^{[72]}$  developed a meaty-textured soybean by solid-state fermentation using *Rhizopus oligosporus* and dried *Agaricus* mushroom and compared the textural profile of the optimized fermented soybean with poultry meat.

# 5. Quality Assessment Considered

Improving the qualitative attributes of meat analogues has been the focus of several investigations over the last few decade. These quality efforts are important for developing excellent meat analogues, especially in understanding the formation of the fibrous structure and protein–protein interactions. Meat consumers were less tolerant to plant-based commodities compared to actual meat products a few years ago, and the main reason was the poorer sensory and nutritional value of the plant-based products. Following that, several novel meat substitutes with enhanced flavor and texture from a variety of plant-based sources can be found on the market, the most popular being based on pea and oat. Several elements of meat substitute characteristics, including chemical and functional properties, physical properties, fiber formation, nutritional properties, cooking quality, and sensory evaluation, are being addressed.

#### **Chemical/Functional Properties**

The most widely used approach in this sub-theme is proximate analysis. All protein powders and meat substitutes are proximately analyzed using international standard methods (AOAC, AACC, ISO), which include moisture, protein, fat, crude fiber, and ash. In extrusion processing, it is necessary to know the moisture content of the protein materials (feed powder) in order to determine the desired moisture content of the final extrudates. Most of the previous work used a conversion factor of 6.25 for soy protein and 5.7 for wheat gluten [9][20][23][27], and the protein was examined using either the Kjeldahl or Dumas combustion methods. In the future, additional conversion factors specific to each crop may need to be employed to obtain more accurate findings. For example, Mariotti et al. [73] proposed a collection of certain conversion factors for various meals, such as 5.5 for soybean, 5.4 for cereals and legumes pulses, and 5.6 for corn and other sources. The study suggested a more exact default conversion factor of 5.6 rather than 6.25, a scientific way to express nitrogen as protein, which is highly relevant when "protein" refers to "amino acids". Using flame atomic absorption spectrometry, the levels of the microelements such as iron (Fe), zinc (Zn), copper (Cu), and manganese (Mn) in the extrudate samples were analyzed. Many studies investigated protein-protein interactions using the protein solubility approach [9][20][27][74]. Osen et al. [74] studied the establishment of covalent peptide bonding during the extrusion process in order to evaluate the impact that high moisture extrusion cooking had on the protein changes that occurred within the extruder. Moreover, FTIR is commonly used for investigating protein conformation and is capable of accurately measuring the secondary structure of proteins, since each protein may be linked with a unique set of bands and wavenumber

intensities <sup>[27][50][51][56][71]</sup>. SDS–PAGE analysis was commonly used to investigate the degree of crosslinking, thus could determine the molecular weight distribution <sup>[18][45][55][61]</sup>. Proteins may polymerize into larger aggregates, rendering those proteins too large to penetrate the flowing gel <sup>[61]</sup>. As explained by Kaleda et al. <sup>[38]</sup>, changes in the content and conformation of proteins significantly impact the capacity of proteins to hold water. Water holding is highly dependent on the presence of polar hydrophilic groups, while the nonpolar side chains of proteins are responsible for determining the oil holding capacity of a material. Oil holding capacity also relies on the physical trapping of oil and may be explained by the material's microstructure. Because it impacts the quality and production of meat analogues, water, and oil holding capacity are important factors. The greater the holding capacity of a product, the juicier it will be. The water solubility index (WSI) measures the total quantity of a substance that can be extracted using water. Multiple variables, including powder composition and particle size, conformational state of proteins, molecular size, and cross-linking, may impact WSI <sup>[38]</sup>. Using carrageenan (0.8%) as a binding agent, mushroom sausages exhibited the lowest amount of purge loss (3.56%) after being frozen, which led to a reduction in drip losses caused by the thawing process <sup>[44]</sup>.

Thermal analysis is usually conducted using differential scanning calorimetry (DSC), thermogravimetric (TG), and differential thermal analysis (DTA) to measure the thermal denaturation of protein, as used in several studies <sup>[9][27][28][28]</sup>. This also helps in setting the correct barrel temperature during the extrusion process and increases knowledge of the raw materials. The barrel temperature must be high enough to allow protein denaturation during the extrusion process. A rheology study may provide some insight into the flow and deformation of protein materials. Many studies reported the rheology results previously <sup>[8][27][75]</sup>. It can assess the behavior of proteins under shear stress and strain during heating– cooling cycles and act as a predictor of the quality of the finished product (meat analogues) following thermal–mechanical processing <sup>[4][10][28]</sup>. Emin et al. <sup>[7]</sup> employed a closed cavity rheometer (with a specified extrusion-like environment) to investigate the critical process parameters that contribute to a substantial change in the response behavior of a plant protein model system, employing vital wheat gluten as a model system. The findings reveal that temperature, water content, shear, and a step change in shear significantly impact the response behavior of proteins.

#### **Physical Properties**

Physical attributes consist of analyses performed on TVP or meat substitutes. Textural and structural properties using a texture profile analyzer (TPA), cutting strength and tensile strength, and ultrastructural characteristics such as scanning electron microscopy (SEM) and light microscopy analysis are among the most typical tests performed to determine how the texture or morphology are formed inside the product and how they are connected to other properties such as chemical composition, SME, and sensory attributes. researchers mostly used SEM to comprehend the structural properties of meat analogues [11][16][22][63][70]. The important characteristics highlighted using TPA were hardness and chewiness. As a result of cutting through the fibrous meat analogues, it was discovered that the values for the longitudinal cutting strength were significantly higher than the values for the transversal cutting strength [30]. In most cases, the researchers either compared the physical characteristics of meat analogues to a reference product of chicken meat and beef or commercial meat analogues. The degree of texturization of SPI-based meat substitutes rises as the SME decreases, according to several studies [12][61]. Kaleda et al. [38] discovered that this is not the case when employing a screw configuration with several kneading and reverse blocks, resulting in greater mechanical treatment. Lower hardness and chewiness in meat analogues were, on the other hand, reported by Fang et al. [61], being correlated with lower SME, contrary to Chiang et al. [12] and Zahari et al. <sup>[30]</sup>. In the extruder barrel, protein molecules exhibited major structural changes and unfolding, creating ideal circumstances for molecular rearrangement in the subsequent extruder zones. The meat-like fibrous structure was reported to be formed at the cooling die zone junction due to protein phase separation and rearrangement [<u>5]</u>

When determining color, the results are always associated with the color of the raw materials used, and the temperatures at which the food was cooked might influence the product. For instance, meat analogues from soy protein had a lighter color compared to hemp, and the *L*\* values decreased as the proportion of hemp powder in the formulation increased <sup>[4]</sup>. Some researchers agreed that *L*\* and *a*\* values were dependent on extrusion temperature and moisture during extrusion cooking <sup>[38][60]</sup>. Raising the moisture content would increase the *L*\* values owing to the lower rates of chemical reactions in the protein composite produced with greater water content <sup>[28][60]</sup>. Other physical properties applied by the researchers on TVP and meat analogues are lateral expansion <sup>[25]</sup>, bulk density <sup>[36]</sup>, porosity <sup>[31]</sup>, expansion index <sup>[8][15]</sup>, and rehydration <sup>[15]</sup>.

#### **Fiber Formation**

Yao and colleagues <sup>[76]</sup> devised a technique for determining fiber formation in soy protein extrudates with high moisture content. To assess fiber growth, many polarization measurements are required. Because the fluorescence signal is weak, ambient light must be blocked, which is problematic on a production line. Ranasinghesagara and colleagues <sup>[2]</sup> refined the

technology by establishing an image processing method to automatically quantify fiber creation using digital imaging and by inventing a non-destructive imaging approach with real-time quality control <sup>[77]</sup>. Later in 2009, more sophisticated technology was applied by incorporating it into a rapid laser scanning system, which permits real-time 2D mapping of fiber production and orientation across the sample <sup>[21]</sup>. Another interesting study was published by Zhang et al. <sup>[27]</sup>, who employed a multiscale approach paired with emerging techniques such as atomic force microscopy-based infrared spectroscopy and X-ray microscopy to make the entire extrusion process visible to illustrate the process of generating a meat-like fibrous structure. Moreover, simulations show that phase separation under temperature or velocity gradients may lead to multilayer structures <sup>[24]</sup>.

#### **Nutritional Analysis**

In addition to functional and textural qualities, the nutritional composition of meat substitutes is an essential factor to be considered when substituting meat with plant-based analogues. Regarding amino acids, researchers are exploring alternative approaches to meet the FAO's requirements for meat. Proteins derived from plants are considered nutritionally insufficient because cereals often lack lysine, and legumes typically have low levels of the sulphur-containing essential amino acids methionine and cysteine. As a result, the quality of the nutrients could be increased by mixing two or more protein sources, which enable the mix to meet FAO standards for a particular age group. Several publications [15][28][31][74] [78] reported the amino acid composition; however, no publication was found that analyzed the protein quality or protein digestibility-corrected amino acid score (PDCAAS) of the produced meat analogues. This demonstrates that there is currently a lack of information that is readily available. Previously, it was reported that the amino acid composition of soy and sunflower mixed flours may complement each other [15]. According to Osen et al. [74], extrusion did not influence hydrolysis or amino acid composition, possibly because high feed moisture minimized shear stress and mechanical energy loss in the extruder. The main amino acids in the WG/SPI meat analogues were glutamic acid, proline, leucine, and aspartic acid, according to Chiang's study [78], and the amount of cysteine in the meat replacements was higher than that of firm tofu and steamed chicken. It has also been discovered that adding green tea to TVP improved texturization and antioxidant properties but had a negative effect on the expansion and NSI <sup>[29]</sup>. Recently, Sakai et al. <sup>[45]</sup> and Chen et al. [53] investigated the in vitro gastrointestinal digestibility of meat analogues. It was reported that HME could improve protein digestibility in several protein materials [53]. It seems that the extrusion field in this phase focused on finding approaches to mimic the structure of the meat. The next phase will also consider the amino acid profile or protein quality (PDCAAS), but people are not there yet. This follows a logical order, since there is no need to optimize the nutrition profile if the materials do not fulfill the texture criteria.

#### **Cooking Quality**

Cooking quality was related to analyses performed before and after extrusion, such as cooking loss or frying loss, swelling index, water absorption capacity (WAC), and breakage rate. The percentage difference between the weight of the sample before and after cooking is referred to as "cooking loss", and it is an essential indicator in determining the quality of the meat analogues in relation to the amount of juice it retains and the amount of product it produces overall <sup>[45]</sup>. In general, preparation factors such as composite materials affect cooking loss in processed meat products <sup>[75]</sup>. For instance, in mushroom sausage, the addition of all types of binding agents decreased cooking losses, with carrageenan giving the best results, followed by xanthan gum, soy protein concentrates, and casein <sup>[44]</sup>. According to Neumann <sup>[22]</sup>, the water absorption capacity of a product correlated with its texture after rehydration. Lin and colleagues <sup>[14]</sup> studied water absorption capacity in the extruded meat analogues and discovered that samples extruded at the high moisture content (70%) and high cooking temperatures (149 °C and 160 °C) had the highest WAC. Furthermore, the researchers reported that the porosity of meat analogues influenced the WAC, since extrudates with comparable physical structures and similar moisture contents did not significantly vary in WAC.

#### **Sensory Evaluation**

Another important test that many researchers employed to confirm that the products are acceptable from the consumer's perspective is the sensory evaluation. The sensory qualities of the generated meat analogues can be evaluated using descriptive sensory analysis and the hedonic scale. A scale or a test using hedonic 7-point, 9-point, and 11-point scales was used to achieve this by untrained, semi-trained, or trained panelists. De Angelis et al. <sup>[36]</sup> used an 11-point structured scale ranging from 0 to 10, and the sensory assessment emphasized a powerful odor and taste profile of dry-fractionated pea protein and oat protein (PDF–OP), whereas the extrudates generated by protein isolates had neutral sensory features. It was found that sensory assessment is not included in many investigations of meat analogues; most of them are studies on restructured meat substitutes. Sensory evaluation was conducted by Grahl et al. <sup>[80]</sup> using conventional profiling on spirulina and soy-based meat analogues to measure the intensities and amplitudes of the feelings as well as to subjectively characterize the samples. Rousta et al. <sup>[43]</sup> evaluated the texture of patties manufactured from *Aspergillus* 

*oryzae* biomass (edible fungi) and compared them with two other commercial patties in Sweden, namely, Beyond and Quorn. The study also revealed that restructured meat could give a different taste because of the chemicals and enzymes used in the pre-treatments, which degrade carbohydrates, proteins, and fats into parts <sup>[43]</sup>.

#### **Other Assessments**

In this sub-theme, several assessments were found to be used in the studies, such as volatile compounds <sup>[38]</sup>, microbiological evaluation of meat analogues <sup>[81]</sup>, and life cycle assessment of products produced from meat analogues <sup>[48]</sup>. Kaleda et al. <sup>[38]</sup> found that extrusion decreased volatile compounds due to high temperature (150 °C). The microbiological evaluation of meat analogues products was discovered to be a crucial assessment to regulate the microbial growth of the meat analogues and at all stages of processing as well as to estimate the product's shelf life. Filho et al. <sup>[81]</sup> analyzed the properties of raw materials, evaluated the microbial limit testing of the canned product before retorting it, and investigated the most critical processing stages to exert control over the growth of microorganisms. However, to go on to the next phase, researchers must first complete the assessments described above, and that will provide a good understanding of each material and the fundamental processing approach.

#### References

- 1. Jia, W.; Curubeto, N.; Rodríguez-Alonso, E.; Keppler, J.K.; van der Goot, A.J. Rapeseed Protein Concentrate as a Potential Ingredient for Meat Analogues. Innov. Food Sci. Emerg. Technol. 2021, 72, 102758.
- 2. Ranasinghesagara, J.; Fu-Hung, H.; Gang, Y. An Image Processing Method for Quantifying Fiber Formation in Meat Analogs under High Moisture Extrusion. J. Food Sci. 2005, 70, E450–E454.
- 3. Hashizume, K. Preparation of a New Protein Food Material by Freezing. JARQ Jpn. Agric. Res. Q. 1978, 12, 104–108.
- Zahari, I.; Ferawati, F.; Helstad, A.; Ahlström, C.; Östbring, K.; Rayner, M.; Purhagen, J.K. Development of High-Moisture Meat Analogues with Hemp and Soy Protein Using Extrusion Cooking. Foods 2020, 9, 772.
- 5. Wittek, P.; Zeiler, N.; Karbstein, H.P.; Emin, M.A. High Moisture Extrusion of Soy Protein: Investigations on the Formation of Anisotropic Product Structure. Foods 2021, 10, 102.
- Wittek, P.; Ellwanger, F.; Karbstein, H.P.; Emin, M.A. Morphology Development and Flow Characteristics during High Moisture Extrusion of a Plant-Based Meat Analogue. Foods 2021, 10, 1753.
- 7. Emin, M.A.; Quevedo, M.; Wilhelm, M.; Karbstein, H.P. Analysis of the Reaction Behavior of Highly Concentrated Plant Proteins in Extrusion-like Conditions. Innov. Food Sci. Emerg. Technol. 2017, 44, 15–20.
- Dahl, S.R.; Villota, R. Twin-Screw Extrusion Texturization of Acid and Alkali Denatured Soy Proteins. J. Food Sci. 1991, 56, 1002–1007.
- 9. Liu, K.S.; Hsieh, F.-H. Protein-Protein Interactions in High Moisture-Extruded Meat Analogs and Heat-Induced Soy Protein Gels. J. Am. Oil Chem. Soc. 2007, 84, 741–748.
- Pietsch, V.L.; Bühler, J.M.; Karbstein, H.P.; Emin, M.A. High Moisture Extrusion of Soy Protein Concentrate: Influence of Thermomechanical Treatment on Protein-Protein Interactions and Rheological Properties. J. Food Eng. 2019, 251, 11–18.
- 11. Palanisamy, M.; Topfl, S.; Aganovic, K.; Berger, R.G. Influence of lota Carrageenan Addition on the Properties of Soya Protein Meat Analogues. LWT—Food Sci. Technol. 2018, 87, 546–552.
- 12. Chiang, J.H.; Loveday, S.M.; Hardacre, A.K.; Parker, M.E. Effects of Soy Protein to Wheat Gluten Ratio on the Physico-Chemical Properties of Extruded Meat Analogues. Food Struct. 2019, 19, 100102.
- Lin, S.; Huff, H.E.; Hsieh, F. Texture and Chemical Characteristics of Soy Protein Meat Analog Extruded at High Moisture. J. Food Sci. 2000, 65, 264–269.
- 14. Lin, S.; Huff, H.E.; Hsieh, F. Extrusion Process Parameters, Sensory Characteristics, and Structural Properties of a High Moisture Soy Protein Meat Analog. J. Food Sci. 2002, 67, 1066–1072.
- 15. Brückner, J.; Mieth, G.; Zdziennicki, A.K.; Gwiazda, S. Influence of Sunflower Flour on the Extrusion Behaviour of Soya Grits and the Functional Properties of the Extrudates (Short Communication). Food Nahr. 1987, 31, 1037–1039.
- 16. Kozlowska, H.; Elkowicz, K.; Lossow, B.; Smith, O.B. The Structural Modification of Vegetable Protein Preparations by High and Low Pressure Extrusion-Cooking Processes. Acta Aliment. Pol. 1979, 5, 81–85.
- 17. Samard, S.; Ryu, G.H. A Comparison of Physicochemical Characteristics, Texture, and Structure of Meat Analogue and Meats. J. Sci. Food Agric. 2019, 99, 2708–2715.

- Wu, M.; Sun, Y.; Bi, C.H.; Ji, F.; Li, B.R.; Xing, J.J. Effects of Extrusion Conditions on the Physicochemical Properties of Soy Protein/Gluten Composite. Int. J. Agric. Biol. Eng. 2018, 11, 230–237.
- 19. Lee, G.; Huff, H.E.; Hsieh, F. Overall Heat Transfer Coefficient between Cooling Die and Extruded Product. Trans. Am. Soc. Agric. Eng. 2005, 48, 1461–1469.
- Liu, K.S.; Hsieh, F.-H. Protein-Protein Interactions during High-Moisture Extrusion for Fibrous Meat Analogues and Comparison of Protein Solubility Methods Using Different Solvent Systems. J. Agric. Food Chem. 2008, 56, 2681– 2687.
- 21. Ranasinghesagara, J.; Hsieh, F.H.; Huff, H.; Yao, G. Laser Scanning System for Real-Time Mapping of Fiber Formations in Meat Analogues. J. Food Sci. 2009, 74, E39–E45.
- 22. Neumann, P.E.; Jasberg, B.K.; Wall, J.S.; Walker, C.E. Uniquely Textured Products Obtained by Coextrusion of Corn Gluten Meal and Soy Flour. Cereal Chem. 1984, 61, 439–445.
- Osen, R.; Toelstede, S.; Wild, F.; Eisner, P.; Schweiggert-Weisz, U. High Moisture Extrusion Cooking of Pea Protein Isolates: Raw Material Characteristics, Extruder Responses, and Texture Properties. J. Food Eng. 2014, 127, 67–74.
- 24. Murillo, J.L.S.; Osen, R.; Hiermaier, S.; Ganzenmueller, G. Towards Understanding the Mechanism of Fibrous Texture Formation during High-Moisture Extrusion of Meat Substitutes. J. Food Eng. 2019, 242, 8–20.
- 25. Omohimi, C.I.; Sobukola, O.P.; Sarafadeen, K.O.; Sanni, L.O. Effect of Thermo-Extrusion Process Parameters on Selected Quality Attributes of Meat Analogue from Mucuna Bean Seed Flour. Niger. Food J. 2014, 32, 21–30.
- 26. Rehrah, D.; Ahmedna, M.; Goktepe, I.; Jianmei, Y. Extrusion Parameters and Consumer Acceptability of a Peanut-Based Meat Analogue. Int. J. Food Sci. Technol. 2009, 44, 2075–2084.
- 27. Zhang, J.; Liu, L.; Jiang, Y.; Faisal, S.; Wei, L.; Cao, C.; Yan, W.; Wang, Q. Converting Peanut Protein Biomass Waste into a "Double Green" Meat Substitutes Using a High-Moisture Extrusion Process: A Multiscale Method to Explore a Process for Forming a Meat-like Fibrous Structure. J. Agric. Food Chem. 2019, 67, 10713–10725.
- 28. Ferawati, F.; Zahari, I.; Barman, M.; Hefni, M.; Ahlström, C.; Witthöft, C.; Östbring, K. High-Moisture Meat Analogues Produced from Yellow Pea and Faba Bean Protein Isolates/Concentrate: Effect of Raw Material Composition and Extrusion Parameters on Texture Properties. Foods 2021, 10, 843.
- Saldanha do Carmo, C.; Knutsen, S.H.; Malizia, G.; Dessev, T.; Geny, A.; Zobel, H.; Myhrer, K.S.; Varela, P.; Sahlstrøm, S. Meat Analogues from a Faba Bean Concentrate Can Be Generated by High Moisture Extrusion. Future Foods 2021, 3, 100014.
- Zahari, I.; Ferawati, F.; Purhagen, J.K.; Rayner, M.; Ahlström, C.; Helstad, A.; Östbring, K. Development and Characterization of Extrudates Based on Rapeseed and Pea Protein Blends Using High-Moisture Extrusion Cooking. Foods 2021, 10, 2397.
- Arueya, G.L.; Owosen, B.S.; Olatoye, K.K. Development of Texturized Vegetable Protein from Lima Bean (Phaseolus lunatus) and African Oil Bean Seed Pentaclethra macrophylla (Benth): Optimization Approach. Acta Univ. Cibiniensis Ser. E Food Technol. 2017, 21, 61–68.
- Maung, T.T.; Gu, B.Y.; Kim, M.H.; Ryu, G.H. Fermentation of Texturized Vegetable Proteins Extruded at Different Moisture Contents: Effect on Physicochemical, Structural, and Microbial Properties. Food Sci. Biotechnol. 2020, 29, 897–907.
- 33. Bakhsh, A.; Lee, S.-J.; Lee, E.-Y.; Sabikun, N.; Hwang, Y.-H.; Joo, S.-T. A Novel Approach for Tuning the Physicochemical, Textural, and Sensory Characteristics of Plant-Based Meat Analogs with Different Levels of Methylcellulose Concentration. Foods 2021, 10, 560.
- 34. Bakhsh, A.; Lee, S.-J.; Lee, E.-Y.; Hwang, Y.-H.; Joo, S.-T. Evaluation of Rheological and Sensory Characteristics of Plant-Based Meat Analog with Comparison to Beef and Pork. Food Sci. Anim. Resour. 2021, 41, 983–996.
- Sharima Abdullah, N.; Hassan, C.Z.; Arifin, N.; Huda Faujan, N. Physicochemical Properties and Consumer Preference of Imitation Chicken Nuggets Produced from Chickpea Flour and Textured Vegetable Protein. Int. Food Res. J. 2018, 25, 1016–1025.
- 36. De Angelis, D.; Kaleda, A.; Pasqualone, A.; Vaikma, H.; Tamm, M.; Tammik, M.-L.; Squeo, G.; Summo, C. Physicochemical and Sensorial Evaluation of Meat Analogues Produced from Dry-Fractionated Pea and Oat Proteins. Foods 2020, 9, 1754.
- 37. Immonen, M.; Chandrakusuma, A.; Sibakov, J.; Poikelispää, M.; Sontag-Strohm, T. Texturization of a Blend of Pea and Destarched Oat Protein Using High-Moisture Extrusion. Foods 2021, 10, 1517.
- 38. Kaleda, A.; Talvistu, K.; Tamm, M.; Viirma, M.; Rosend, J.; Tanilas, K.; Kriisa, M.; Part, N.; Tammik, M.-L. Impact of Fermentation and Phytase Treatment of Pea-Oat Protein Blend on Physicochemical, Sensory, and Nutritional

Properties of Extruded Meat Analogs. Foods 2020, 9, 1059.

- 39. Bayram, M.; Bozkurt, H. The Use of Bulgur as a Meat Replacement: Bulgur-Sucuk (a Vegetarian Dry-Fermented Sausage). J. Sci. Food Agric. 2007, 87, 411–419.
- Kamani, M.H.; Meera, M.S.; Bhaskar, N.; Modi, V.K. Partial and Total Replacement of Meat by Plant-Based Proteins in Chicken Sausage: Evaluation of Mechanical, Physico-Chemical and Sensory Characteristics. J. Food Sci. Technol. 2019, 56, 2660–2669.
- Yuan, X.; Jiang, W.; Zhang, D.; Liu, H.; Sun, B. Textural, Sensory and Volatile Compounds Analyses in Formulations of Sausages Analogue Elaborated with Edible Mushrooms and Soy Protein Isolate as Meat Substitute. Foods 2022, 11, 52.
- 42. Stephan, A.; Ahlborn, J.; Zajul, M.; Zorn, H. Edible Mushroom Mycelia of Pleurotus Sapidus as Novel Protein Sources in a Vegan Boiled Sausage Analog System: Functionality and Sensory Tests in Comparison to Commercial Proteins and Meat Sausages. Eur. Food Res. Technol. 2018, 244, 913–924.
- 43. Rousta, N.; Hellwig, C.; Wainaina, S.; Lukitawesa, L.; Agnihotri, S.; Rousta, K.; Taherzadeh, M.J. Filamentous Fungus Aspergillus Oryzae for Food: From Submerged Cultivation to Fungal Burgers and Their Sensory Evaluation—A Pilot Study. Foods 2021, 10, 2774.
- 44. Arora, B.; Kamal, S.; Sharma, V.P. Effect of Binding Agents on Quality Characteristics of Mushroom Based Sausage Analogue. J. Food Process. Preserv. 2017, 41, e13134.
- 45. Sakai, K.; Sato, Y.; Okada, M.; Yamaguchi, S. Improved Functional Properties of Meat Analogs by Laccase Catalyzed Protein and Pectin Crosslinks. Sci. Rep. 2021, 11, 16631.
- 46. Lee, E.J.; Hong, G.P. Effects of Microbial Transglutaminase and Alginate on the Water-Binding, Textural and Oil Absorption Properties of Soy Patties. Food Sci. Biotechnol. 2020, 29, 777–782.
- 47. Mazlan, M.M.; Talib, R.A.; Chin, N.L.; Shukri, R.; Taip, F.S.; Nor, M.Z.M.; Abdullah, N. Physical and Microstructure Properties of Oyster Mushroom-Soy Protein Meat Analog via Single-Screw Extrusion. Foods 2020, 9, 1023.
- 48. Saerens, W.; Smetana, S.; Van Campenhout, L.; Lammers, V.; Heinz, V. Life Cycle Assessment of Burger Patties Produced with Extruded Meat Substitutes. J. Clean. Prod. 2021, 306, 127177.
- 49. Kendler, C.; Duchardt, A.; Karbstein, H.P.; Emin, M.A. Effect of Oil Content and Oil Addition Point on the Extrusion Processing of Wheat Gluten-Based Meat Analogues. Foods 2021, 10, 697.
- Zhang, J.; Liu, L.; Jian, Y.; Shah, F.; Xu, Y.; Wang, Q. High-Moisture Extrusion of Peanut Protein-/Carrageenan/Sodium Alginate/Wheat Starch Mixtures: Effect of Different Exogenous Polysaccharides on the Process Forming a Fibrous Structure. Food Hydrocoll. 2020, 99, 105311.
- Wen, Y.; Xin-Sheng, Q.; Shui-Zhong, L.; Yan-Yan, Z.; Xi-Yang, Z.; Dong-Dong, M.; Shao-Tong, J.; Zhi, Z. Effect of Calcium Stearyl Lactylate on Physicochemical Properties of Texturized Wheat Gluten. Food Sci. Technol. Res. 2017, 23, 203–211.
- 52. Yuliarti, O.; Kovis, T.J.K.; Yi, N.J. Structuring the Meat Analogue by Using Plant-Based Derived Composites. J. Food Eng. 2021, 288, 110138.
- Chen, Q.; Zhang, J.; Zhang, Y.; Meng, S.; Wang, Q. Rheological Properties of Pea Protein Isolate-Amylose/Amylopectin Mixtures and the Application in the High-Moisture Extruded Meat Substitutes. Food Hydrocoll. 2021, 117, 106732.
- Liu, Y.; Liu, M.; Huang, S.; Zhang, Z. Optimisation of the Extrusion Process through a Response Surface Methodology for Improvement of the Physical Properties and Nutritional Components of Whole Black-Grained Wheat Flour. Foods 2021, 10, 437.
- 55. Pöri, P.; Nisov, A.; Nordlund, E. Enzymatic Modification of Oat Protein Concentrate with Trans- and Protein-Glutaminase for Increased Fibrous Structure Formation during High-Moisture Extrusion Processing. LWT 2022, 156, 113035.
- 56. Xia, S.; Xue, Y.; Xue, C.; Jiang, X.; Li, J. Structural and Rheological Properties of Meat Analogues from Haematococcus Pluvialis Residue-Pea Protein by High Moisture Extrusion. LWT 2022, 154, 112756.
- 57. Parmer, E.L., Jr.; Wang, B.; Aglan, H.A.; Mortley, D. Physicochemical Properties of Texturized Meat Analog Made from Peanut Flour and Soy Protein Isolate with a Single-Screw Extruder. J. Texture Stud. 2004, 35, 371–382.
- Samard, S.; Gu, B.Y.; Ryu, G.H. Effects of Extrusion Types, Screw Speed and Addition of Wheat Gluten on Physicochemical Characteristics and Cooking Stability of Meat Analogues. J. Sci. Food Agric. 2019, 99, 4922–4931.
- 59. Alonso, R.; Orúe, E.; Zabalza, M.J.; Grant, G.; Marzo, F. Effect of Extrusion Cooking on Structure and Functional Properties of Pea and Kidney. J. Sci. Food Agric. 2000, 80, 397–403.

- 60. Palanisamy, M.; Franke, K.; Berger, R.G.; Heinz, V.; Topfl, S. High Moisture Extrusion of Lupin Protein: Influence of Extrusion Parameters on Extruder Responses and Product Properties. J. Sci. Food Agric. 2019, 99, 2175–2185.
- 61. Fang, Y.; Zhang, B.; Wei, Y. Effects of the Specific Mechanical Energy on the Physicochemical Properties of Texturized Soy Protein during High-Moisture Extrusion Cooking. J. Food Eng. 2014, 121, 32–38.
- Caporgno, M.P.; Bocker, L.; Mussner, C.; Stirnemann, E.; Haberkorn, I.; Adelmann, H.; Handschin, S.; Windhab, E.J.; Mathys, A. Extruded Meat Analogues Based on Yellow, Heterotrophically Cultivated Auxenochlorella Protothecoides Microalgae. Innov. Food Sci. Emerg. Technol. 2020, 59, 102275.
- 63. Krintiras, G.A.; Diaz, J.G.; van der Goot, A.J.; Stankiewicz, A.I.; Stefanidis, G.D. On the Use of the Couette Cell Technology for Large Scale Production of Textured Soy-Based Meat Replacers. J. Food Eng. 2016, 169, 205–213.
- 64. Krintiras, G.A.; Gobel, J.; Bouwman, W.G.; van der Goot, A.J.; Stefanidis, G.D. On Characterization of Anisotropic Plant Protein Structures. Food Funct. 2014, 5, 3233–3240.
- 65. Krintiras, G.A.; Gobel, J.; van der Goot, A.J.; Stefanidis, G.D. Production of Structured Soy-Based Meat Analogues Using Simple Shear and Heat in a Couette Cell. J. Food Eng. 2015, 160, 34–41.
- 66. Stanley, D.W.; Cumming, D.B.; deMan, J.M. Texture-Structure Relationships in Texturized Soy Protein. I. Textural Properties and Ultrastructure of Rehydrated Spun Soy Fibers. Can. Inst. Food Technol. J. 1972, 5, 118–123.
- 67. Byun, S.M.; Kwon, J.H.; Kim, C.J.; Lee, Y.H. Soyprotein Fiber Formation. Korean J. Food Sci. Technol. 1978, 10, 143– 150.
- 68. Mattice, K.D.; Marangoni, A.G. Comparing Methods to Produce Fibrous Material from Zein. Food Res. Int. 2020, 128, 108804.
- 69. Husain, H.; Huda-Faujan, N. Potential Application of Grey Oyster Mushroom Stems as Halal Meat Replacer in Imitation Chicken Nuggets. Food Res. 2020, 4, 179–186.
- Kim, K.; Choi, B.; Lee, I.; Lee, H.; Kwon, S.; Oh, K.; Kim, A.Y. Bioproduction of Mushroom Mycelium of Agaricus Bisporus by Commercial Submerged Fermentation for the Production of Meat Analogue. J. Sci. Food Agric. 2011, 91, 1561–1568.
- 71. Lindriati, T.; Herlina, H.; Arbiantara, H.; Asrofi, M. Optimization of Meat Analog Production from Concentrated Soy Protein and Yam (Xanthosoma sagittifolium) Powder Using Pasta Machine. Food Res. 2020, 4, 887–895.
- 72. Nayak, B.; Panda, B.P. Modelling and Optimization of Texture Profile of Fermented Soybean Using Response Surface Methodology. AIMS Agric. Food 2016, 1, 409–418.
- 73. Mariotti, F.; Tomé, D.; Mirand, P.P. Converting Nitrogen into Protein—Beyond 6.25 and Jones' Factors. Crit. Rev. Food Sci. Nutr. 2008, 48, 177–184.
- 74. Osen, R.; Toelstede, S.; Eisner, P.; Schweiggert-Weisz, U. Effect of High Moisture Extrusion Cooking on Protein-Protein Interactions of Pea (Pisum sativum L.) Protein Isolates. Int. J. Food Sci. Technol. 2015, 50, 1390–1396.
- 75. Gihyun, W.; Junhwan, B.; Honggyun, K.; Youngjae, C.; Mi-Jung, C. Evaluation of the Physicochemical and Structural Properties and the Sensory Characteristics of Meat Analogues Prepared with Various Non-Animal Based Liquid Additives. Foods 2020, 9, 461.
- 76. Yao, G.; Liu, K.S.; Hsieh, F. A New Method for Characterizing Fiber Formation in Meat Analogs during High Moisture Extrusion. J. Food Sci. 2004, 69, E303–E307.
- 77. Ranasinghesagara, J.; Hsieh, F.; Yao, G. A Photon Migration Method for Characterizing Fiber Formation in Meat Analogs. J. Food Sci. 2006, 71, E227–E231.
- Chiang, J.H.; Tay, W.; Ong, D.S.M.; Liebl, D.; Ng, C.P.; Henry, C.J. Physicochemical, Textural and Structural Characteristics of Wheat Gluten-Soy Protein Composited Meat Analogues Prepared with the Mechanical Elongation Method. Food Struct. 2021, 28, 100183.
- 79. Ma, X.; Ryu, G. Effects of Green Tea Contents on the Quality and Antioxidant Properties of Textured Vegetable Protein by Extrusion-Cooking. Food Sci. Biotechnol. 2019, 28, 67–74.
- Grahl, S.; Palanisamy, M.; Strack, M.; Meier-Dinkel, L.; Toepfl, S.; Mörlein, D. Towards More Sustainable Meat Alternatives: How Technical Parameters Affect the Sensory Properties of Extrusion Products Derived from Soy and Algae. J. Clean. Prod. 2018, 198, 962–971.
- 81. Filho, G.C.S.; Vessoni Penna, T.C.; Schaffner, D.W. Microbiological Quality of Vegetable Proteins during the Preparation of a Meat Analog. Ital. J. Food Sci. 2005, 17, 269–283.