Trends of Current LNG Cold Energy Utilization

Subjects: Engineering, Chemical

Contributor: Muhammad Haziq Noor Akashah , Nor Erniza Mohammad Rozali , Shuhaimi Mahadzir , Peng Yen Liew

Liquified natural gas (LNG) is a clean primary energy source that is growing in popularity due to the distance between natural gas (NG)-producing countries and importing countries. The large amount of cold energy stored in LNG presents an opportunity for sustainable technologies to recover and utilize this energy. This can enhance the energy efficiency of LNG regasification terminals and the economic viability of the LNG supply chain. The energy stored in LNG in the form of low temperatures is referred to as cold energy. When LNG is regasified, or converted back into its gaseous form, this cold energy is released. This process involves heating the LNG, which causes it to vaporize and release its stored energy. LNG cold energy has been mostly utilized for power generation, air separation, traditional desalination, and cryogenics carbon dioxide capture. Other potential applications are also emerging such as for data center cooling and cold energy storage. The commercialization of sustainable technologies, such as improvement strategies for LNG cold energy utilization, is becoming increasingly important in the energy industry.

LNG

cold energy utilization

power generation

exergy analysis

1. Introduction

The increasing demand for energy has been driven by factors such as increasing population and economic growth. As the demand for energy continues to rise, it is important to consider the environmental impact of different energy sources. While fossil fuels, such as coal and oil, have traditionally been the primary sources of energy, natural gas (NG) is becoming increasingly popular ^[1] due to its cleaner burning properties ^[2]. NG emits lower levels of harmful greenhouse gases ^[3], such as CO_2 ^[4] and sulfur dioxide, compared to other fossil fuels, making it a more environmentally friendly option ^[5]. NG is a convenient energy source that is easy to transport due to its specific density. It is also a high-energy source, making it an efficient choice for many uses. NG is often considered a clean and efficient energy source due to its low carbon emissions when compared to other fossil fuels. According to data from major gas companies, NG is expected to continue growing in popularity, with a projected increase of 1.7–2.2% per year ^[6]. It is projected that by 2030, it will become the second primary energy resource ^[7].

The transportation of NG is a critical aspect of the supply chain, and two main methods are currently used: pipelines and liquified natural gas (LNG). Pipelines are the traditional option and are most effective for shorter distances, usually less than 1000 km. LNG is better suited for longer distances, typically more than 3500 km ^[B]. In addition to traditional methods of natural gas transportation, there are new methods, such as Gas to Liquid (GTL),

Gas to Wire (GTW) ^[9], Gas to Tank (GTT or CNG), and Gas to Solid (GTS), being developed, but they are not yet practical due to the need for further research and technological advancements.

LNG is produced by cooling NG to cryogenic temperatures, resulting in a liquid form that is easier to transport and store than NG in its gaseous form. LNG is primarily composed of methane, with a heating value of around 21–24 MJ/L ^[10]. Its density ranges between 400 and 500 kg/m³ ^[11], resulting in a lower density than water, and its volume is significantly reduced when compared to NG in its gaseous form. The LNG supply process involves the extraction, liquefaction, transportation, and regasification of NG ^[12], with the traditional method involving pipelines and LNG carriers. More recently, the use of floating liquefied natural gas (FLNG) has emerged as a way to extract, transport, and import LNG from offshore reserves, offering convenience and efficiency compared to traditional methods ^[13]. The safety of LNG has also been extensively researched ^[14], with no recorded incidents of accidents or spills in the transportation of LNG. Overall, LNG has the potential to play a significant role in meeting the increasing global energy demand while mitigating greenhouse gas emissions.

In order to deliver LNG to consumers, it is first shipped from the production location to a receiving terminal, where it is unloaded from carriers and transferred to storage tanks. **Figure 1** illustrates the essential process of an LNG receiving terminal. From the terminal, LNG is pumped through a pipeline to vaporizers, where it is heated and returned to a gaseous state. This process, known as regasification, is important for ensuring the safe and efficient delivery of LNG to consumers. The regasification process is used to convert LNG back into its gaseous state so it can be transported through pipelines and used as a source of energy. The process involves heating the LNG to a temperature above its boiling point, typically around -162 °C, using a variety of methods, such as ambient air, seawater, or waste heat. The heat is transferred to the LNG, causing it to vaporize and release its stored cold energy. It is carried out in specialized facilities known as LNG receiving terminals, which are equipped with specialized equipment such as LNG arms ^[8] and vaporizers ^[15]. The regasification process is also carefully monitored to ensure safety, with measures in place to handle any excess gas that may be produced during the process.



Figure 1. Overall LNG processing from refinery to end user.

While LNG is a clean and efficient energy source, the cold energy produced during the regasification process is often released into the environment through vaporizers and warmed by external substances. Furthermore, releasing cold energy into the surrounding environment can be problematic because it may harm aquatic life and the wasted energy could have been used to power other systems or processes instead ^[16]. This wasted energy can contribute to inefficiencies ^[17] in the overall energy system and increase the environmental impact of the LNG supply chain. By capturing and making use of the cold energy, it is possible to enhance the energy efficiency of LNG regasification terminals and the economic viability of the LNG supply chain. Additionally, utilizing cold energy can help to reduce greenhouse gas emissions ^[18] and contribute to a more sustainable energy system ^[19]. There have been many studies that reported applying this cold energy from the LNG regasification process ^[16].

2. Trends of Current LNG Cold Energy Utilization

The cold energy in LNG holds unique properties that make it useful in various applications, especially in the oil and gas industry ^[20]. Cold energy is a valuable resource that is produced during the regasification of LNG. The process of vaporizing LNG in vaporizers generates a large amount of cold energy, which can be used in a variety of applications, such as power generation, air separation, desalination, CO₂ capture, data center cooling, and cold storage ^[16]. However, it is important to consider the distribution pressure of natural gas when utilizing LNG cold energy, as the required pressure values can vary depending on the intended use of the gas. Additionally, while the amount of LNG cold energy produced is generally higher in larger systems, it is more beneficial to consider LNG cold exergy when designing cold utilization systems due to the inclusion of destruction and loss terms in the exergy concept ^[21].

2.1. Power Generation

The trade of LNG has seen a rapid growth in the past two decades ^[22]; however, with global warming on the rise, there is an increased need for sustainable solutions. Environmental policies are also becoming stricter, making it imperative to find ways to reduce greenhouse gas emissions. LNG cryogenic technology presents a solution to this problem, as it allows for the capture and utilization of the cold energy stored in LNG. This can be achieved by using cold energy to vaporize a working fluid, such as R-141b, which then expands through a turbine to generate electricity. This process can significantly increase the efficiency of the power generation process and reduce the overall costs, making it a promising opportunity for sustainable and cost-effective power generation. This not only increases the energy efficiency of LNG regasification terminals but also the economic benefit of the LNG supply chain. It can also be used for power generation ^[23], further reducing the dependence on fossil fuels and contributing to the reduction in greenhouse gas emissions.

2.2. Air Separation

A distillation column is used in the cryogenic air separation process to lower the temperature of the air to the cryogenic temperature (below -195 °C at atmospheric pressure) and then separates the air into its component gases, such as oxygen and nitrogen. Because the procedure takes place at such a subzero temperature, the

refrigeration cycle requires a substantial amount of power in order to function properly. Therefore, the exploitation of LNG cold energy in the air separation process can decrease the amount of energy that is consumed while concurrently reconverting LNG to NG.

Figure 2 illustrates the air separation process that makes use of the cold energy provided by LNG. By taking the place of the traditional refrigeration cycle, LNG is now employed to bring the temperature of the air down.



Figure 2. Air separation with LNG cold energy utilization ^[24].

A study by Kim and coworkers ^[25] looked into incorporating an air separation unit (ASU) with LNG vaporization at import terminals as a method for utilizing the cold energy from LNG. Two different options for integration were proposed by the researchers, and the performance was evaluated based on the energy and exergy analyses. The findings indicate that utilizing an LNG stream for precooling results in a decrease in specific power consumption and a higher exergy efficiency in comparison to the alternative, which utilizes a liquid nitrogen production cycle. This suggests that the integration of an ASU with LNG vaporization can be a useful way to utilize LNG cold energy and improve energy efficiency. In 2019, a study by Chen and colleagues proposed the use of a vapor recompression column (VRC) in an air ASU that utilizes the cryogenic energy of LNG ^[26]. The study compared the thermodynamic characteristics of three different types of cryogenic rectification columns for air separation using the first and second laws of thermodynamics. The outcome of the study revealed that the VRC (variable reflux column) was the most appropriate column for the ASU when utilizing LNG cold energy, as it had the lowest energy demand for shaft work and the lowest energy consumption during the separation process. Furthermore, it was found that by utilizing cryogenic energy from the product to cool the reflux and feed air, the efficiency can be increased. The proposed process had the potential to produce liquid oxygen and had a lower power consumption of 6.9% and 11.1% in comparison to earlier studies [27] when producing both vapor and liquid product. The use of LNG cryogenic energy also resulted in an improvement in the minimum energy of separation.

A study by Wu et al. ^[28] proposed a new method for producing high-purity oxygen through a cryogenic air separation process that utilizes the cold energy released during LNG regasification. The proposed system

employed strategies such as utilizing waste N₂ fully, cascading heat transfer, and multi-column air distillation to reduce power consumption. The results of the thermodynamic analysis show that the specific power consumption of liquid oxygen and liquid nitrogen are 0.252 kWh/kg and 0.258 kWh/kg, respectively, and the overall exergy efficiency and LNG cold exergy utilization efficiency are 0.7165 and 0.5318, respectively. The study also includes an analysis of the sensitivity of the system to changes in the outlet temperature of sub-coolers and the number of stages in the low-pressure column in order to assess their impact on the total power consumption and equipment investment. Overall, the proposed process has the potential to be cost-effective for producing high-purity oxygen in the industrial field. Han et al. ^[29] proposed various design options and evaluated them to combine LNG regasification and air separation, as a way to harness the low-grade cold energy of LNG and decrease power consumption. Four external circulation designs were compared, using energy and exergy thermodynamic models, to traditional and existing systems using the Linde cycle with LNG precooling. The results show that these proposed schemes were able to greatly decrease the energy consumption per unit of liquid product, with the most efficient design consuming 0.189 kW·h·kg⁻¹. According to the study, the external circulation scheme utilizing highpressure LNG and low-pressure circulating nitrogen was found to be the most efficient option. It had the smallest demand for LNG, the least exergy loss, and the highest exergy efficiency of 0.869, as well as the best utilization rate of LNG cold energy.

He et al. ^[30] proposed an air separation unit with energy storage and air recovery (ASU-ESAR) that was designed to fully recycle the high-purity air produced during energy release from LAES technology, as well as energy in the form of low temperature and high pressure. The ASU-ESAR was expected to improve the energy conservation efficiency and economic benefits of air separation processes, and potentially reduce the peak-valley ratio of China's power grid and CO₂ emissions by 13% and 12.53–27.71 Mt per year, respectively. The payback period for an LAES system with a power capacity of 70.70–74.38 MWh/day is estimated to be 2.2–2.9 years.

In 2022, Hamayun et al. ^[31] proposed a new process for the production of high-purity nitrogen by harnessing the cold energy from LNG regasification. Results show that the integrated process between ASU and cold energy from LNG regasification was more efficient in terms of power consumption and exergy destruction compared to the standalone process. An advanced exergy analysis also revealed that 44.3% of the total exergy destruction in the process was preventable, and 91.7% of this destruction was of endogenous nature, suggesting that improving the efficiency of individual pieces of equipment should be the top priority for process improvement. This study highlights the potential for integrating LNG regasification with air separation as a way to recover cold energy and improve the efficiency of nitrogen production.

Other recent studies that consider cold energy from LNG regasification for air separation process are tabulated in **Table 1**.

Table 1. Other works on standalone and integrated ASU systems.

System	Working Fluid	References
ASU	Neon, argon, oxygen, and nitrogen	[32]

System	Working Fluid	References
LNG powered ship with ASU	Nitrogen and oxygen	[<u>33]</u>
ASU	Nitrogen and oxygen	[<u>34]</u>
ASU and hydrocarbon recovery	Nitrogen, oxygen, and argon.	[<u>35</u>]
ASU with power cycle	Oxygen	[<u>36</u>]
ASU	Oxygen	[<u>37</u>]

2.3. Desalination of Seawater

Desalination is a process that involves the removal of mineral components found in seawater through the use of a significant amount of energy ^[38]. Because both the desalination facility and the regasification terminal of LNG are situated near the shore, it is possible to make use of the LNG cold energy during the desalination process, which in turn will lower the amount of energy that is required ^[39]. The desalination process can be achieved through two common methods, reverse osmosis (RO) ^[40] and multi-stage flash distillation (MSF) ^[41], each with their own advantages and disadvantages. In addition to these two methods, there is a third technique known as freeze desalination (FD) ^[42], which involves the creation of ice crystals that are resistant to the effects of salt. This method is used to remove minerals from saltwater. Because the latent heat of ice formation (335 kJ/kg) is approximately seven times lower than the heat of vaporization (2260 kJ/kg), FD is more effective in terms of the utilization of energy when compared to the thermal desalination processes ^[43].

Figure 3 presents the FD process, which makes use of the cold energy provided by LNG based on work carried out by ^[44]. As shown in **Figure 3**, LNG cold energy can be used to precool saltwater and provide a low-temperature working environment for the freeze tower.



Figure 3. Diagram of FD process utilizing LNG cold energy [16].

Using LNG as a source of cold energy, Ong et al. ^[45] assessed the technical and economic feasibility of a directcontact type of seawater freezing desalination (SFD) process, in which cold energy from the regasification of LNG is used to generate freshwater ice from seawater. The researchers carried out process analysis, integration, and optimization using detailed material and energy balance models. They also looked at the influence of various operating variables on the efficiency of the process, such as inlet temperatures and flow rates. The study found that the optimized process was able to produce 1.64 kg/s of freshwater using 7.83 kg/s of seawater, while consuming 1.66 kW of electric power. The researchers also examined the effect of electricity and water prices on the cost and income of the process in different regions. Overall, the results suggest that the SFD process using LNG regasification cold energy as a technically and economically feasible option for seawater desalination. Ghorbani et al. ^[46] presented a report on an integrated system that generates electricity and fresh water simultaneously by utilizing a multi-stage thermal water desalination system and an ORC. The system utilizes parabolic trough solar collectors and the regasification of LNG to provide input heat and condenser cooling for the ORC, respectively. The system, which was simulated based on climatic data from Tehran and Iran, can produce 3628 kgmol/h of fresh water and 459.9 MW of electricity, with an ORC efficiency of 12.47% and a gain output ratio of 2.918 for the multi-effect desalination system. An exergy analysis revealed that the total exergy efficiency of the system is 87.11%, with heat exchangers and collectors contributing the largest shares of exergy destruction at 50.23% and 38.18%, respectively.

Lee et al. [47] proposed a dual-expander organic Rankine cycle hydrate-based desalination (ORC-HBD) process as a hybrid desalination system that uses LNG cold energy to generate electricity and pure water. The process consists of two expanders and a reverse osmosis system and can be optimized for use with various liquid-phase and gas-phase hydrate formers, including propane, R125A, R141B, and cyclopentane. The process was found to be highly energy and exergy efficient, with a negative product cost and profit of up to 3.095 USD/ton of pure water when using free external heat. Based on the research conducted, it holds significant potential as a solution for addressing water shortages and energy crises. Recently, Salakhi et al. [48] examined the feasibility of using the cold energy from LNG to desalinate seawater through FD. By directly utilizing the cold energy of LNG in an appropriate temperature range, the process eliminates the need for a secondary refrigerant and its refrigeration cycle. The optimization aimed to find the optimal conditions for maximizing ice production while minimizing the salt content in the resulting ice. The results indicate that as the LNG inlet temperature decreased from -10 to -60 °C, the ice mass production increased from 60.9 to 977.6 g, but also decreased the quality by 90%. Increasing the Reynolds number of LNG from 4000 to 32,000 also increased the ice production by 492 g, but also increased the ice salinity from 1.22 to 1.56%. It was also found that potable water could be produced through three-stage desalination with Reynolds numbers below 16,000. These findings suggest that the use of LNG cold energy has the potential to be a sustainable solution for desalination. Several other similar works on integrating seawater desalination with cold energy from LNG regasification are as tabulated in Table 2.

Table 2. Other works on desalination system using cold energy from LNG regasification.

System	References
FD plant integrated with combined gas power cycle plant	[<u>49</u>]
FD plant integrated with floating storage regasification unit (FSRU)	[<u>50</u>]

System	References
Desalination unit integrated with compressed air energy storage (CAES)	[<u>51</u>]
Integration of Kalina cycle, Stirling engine, desalination unit, and magnetic refrigeration system	[52]
Desalination and power generation	[<u>53]</u>

It is clear from the studies reviewed that the use of cold energy from LNG in desalination processes has the potential to be a sustainable and cost-effective solution to the increasing demand for fresh water. By utilizing the cold energy from LNG in processes such as FD, it is possible to produce high-purity water with low energy consumption. However, further research is needed to optimize and commercialize these technologies in order to make them a viable option for large-scale desalination.

2.4. CO₂ Capture Using Cryogenic Process

Liquification is the first step in the cryogenic CO_2 capture process, which is a method for extracting CO_2 from exhaust gas ^[54]. The standard cryogenic CO_2 capture method calls for an external refrigeration cycle to be used in order to chill and liquefy CO_2 , which necessitates a large power consumption ^[55]. Using NG or LNG as a fuel source for power plants, by merging the regasification process of LNG with cryogenic CO_2 capture, could lead to substantial energy savings while simultaneously reducing the plant's carbon footprint ^[56]. **Figure 4** depicts a cryogenic method for the extraction of CO_2 that also makes use of the cold energy that LNG provides. In order to obtain liquid CO_2 , LNG is used to cool the flue gas that is emitted from the boiler to a temperature that is lower than the temperature at which CO_2 will condense in the condenser. The regasified NG is then introduced as combustion fuel into the boiler at this point.



Figure 4. Cryogenic CO_2 capture using LNG cold energy [16].

A cryogenic CO_2 capture system for small-scale power generation systems was proposed by Kanbur et al. in 2018 [57]. The system captures liquid CO_2 during the regasification process of LNG and produces byproducts such as condensed water and a mixture of nitrogen and oxygen. The proposed system was simulated for microturbines

with capacities of 30, 65, and 200 kW. The results of thermodynamic, environmental, and enviroeconomic evaluations show that the system is feasible for the 30 and 65 kW models, with low power decrement rates of 1.81% and 3.15%, respectively. The 200 kW model was found to be infeasible due to higher power decrement rates. The proposed system was also evaluated in a case study for Singapore, showing annual money savings through the capture of liquid CO_2 and production of water. Later in 2019, Wang et al. ^[58] proposed a system for utilizing the cryogenic exergy of LNG in a cascade nested ORC. The system captures CO_2 from flue gas while also producing power and utilizing LNG as a heat sink. The performance of the system was evaluated based on exergy efficiency, cold energy utilization efficiency, power generation, and CO_2 capture. The research found that the utilization of an appropriate mixed working fluid and the inclusion of a regenerator can greatly improve the system's performance, but also discovered that increasing the LNG regasification pressure leads to higher exergy efficiency and cold energy utilization efficiency, but also a decrease in CO_2 capture quantity and power generation.

Ghorbani et al. ^[59] developed a novel approach for simultaneous power generation, cooling, and production of fresh water using solar energy and heat loss. The approach involves the use of a hybrid system consisting of an ORC, a refrigeration cycle using a mixture of ammonia and water to produce LNG and liquid CO_2 , a CO_2 capture process, and a multiple-effect distillation desalination system. The system has the capacity to produce 14.5 tons/h of LNG, 1.693 tons/h of desalinated water, and 2.611 tons/h of liquid CO_2 . The exergy analysis showed that the overall exergy efficiency of the process was 88.97%, with the highest exergy destruction occurring in the towers and the lowest in valves and drums. The economic analysis of the hybrid system determined that the investment would be recouped within 6 years and the cost of the product would be 24.2 cents/kg LNG. A sensitivity analysis was also conducted to identify the key parameters that impact the performance of the developed hybrid system.

Kim et al. ^[60] recently presented a new method for capturing and storing CO_2 using the cold energy from LNG in a NG combined cycle (NGCC) power plant. The proposed process is a cryogenic solid-phase method that uses LNG cold energy to reduce the energy-intensive thermal treatment of the monoethanolamine-based absorption process and the power consumption needed to compress CO_2 to 150 bar. The process also requires minimal equipment installation in the NGCC power plant by integrating the LNG cold energy utilization and CO_2 capture processes. The proposed method reduces the efficiency penalty of the NGCC power plant from 14.34% to 3.51% and has a 99.93% CO_2 capture rate. The study offers a potential solution for reducing the efficiency penalty of cryogenic CO_2 capture and storage (CCS) processes and overcoming the challenges of conventional methods. Several other similar works on integrating CO_2 capture with cold energy from LNG regasification are as tabulated in **Table 3**.

Table 3. Other works on CO	02 capture system	using cold energy	from LNG regasification.
----------------------------	-------------------	-------------------	--------------------------

System	References
ASU integrated with CO ₂ capture	[<u>61</u>]
Solar dish collectors with CO ₂ capture	[62]
Power generation with CO ₂ capture	[63]

System	References
CO ₂ capture and storage	[<u>64]</u>
Power generation with CO ₂ capture	[65]
Allam cycle power plant with CO ₂ capture	[<u>66</u>]

In summary, using LNG cold energy for CO_2 capture has the potential to effectively reduce the energy consumption and efficiency penalty associated with traditional CO_2 capture processes. By integrating LNG cold energy utilization and CO_2 capture processes, the equipment installation requirements for CO_2 capture can be minimized. The cryogenic solid-phase CCS process using LNG cold energy has been shown to be effective in reducing the efficiency penalty in NG combined cycle power plants, with a 99.93% CO_2 capture rate and a reduction in the efficiency penalty from 14.34% to 3.51%. This approach can provide a promising solution for mitigating CO_2 emissions while also utilizing a readily available energy source.

References

- 1. Şevik, S. An Analysis of the Current and Future Use of Natural Gas-Fired Power Plants in Meeting Electricity Energy Needs: The Case of Turkey. Renew. Sustain. Energy Rev. 2015, 52, 572–586.
- 2. Lim, W.; Choi, K.; Moon, I. Current Status and Perspectives of Liquefied Natural Gas (LNG) Plant Design. Ind. Eng. Chem. Res. 2013, 52, 3065–3088.
- 3. Mac Kinnon, M.A.; Brouwer, J.; Samuelsen, S. The Role of Natural Gas and Its Infrastructure in Mitigating Greenhouse Gas Emissions, Improving Regional Air Quality, and Renewable Resource Integration. Prog. Energy Combust. Sci. 2018, 64, 62–92.
- 4. Brown, S.P.; Krupnick, A.; Walls, M.A. Natural Gas: A Bridge to a Low-Carbon Future. Issue Br. 2009, 9–11.
- 5. Tilagone, R.; Venturi, S.; Monnier, G. Natural Gas—An Environmentally Friendly Fuel for Urban Vehicles: The SMART Demonstrator Approach. SAE Tech. Pap. 2005, 61, 155–164.
- 6. Smil, V. Natural Gas: Fuel for the 21st Century; Wiley: New York, NY, USA, 2015; ISBN 9781119012849.
- Lochner, S.; Bothe, D. The Development of Natural Gas Supply Costs to Europe, the United States and Japan in a Globalizing Gas Market—Model-Based Analysis until 2030. Energy Policy 2009, 37, 1518–1528.
- 8. Mokhatab, S.; Mak, J.Y.; Valappil, J.V.; Wood, D.A. Handbook of Liquefied Natural Gas; Elsevier: Amsterdam, The Netherlands, 2013; ISBN 9780124046450.
- 9. Ojijiagwo, E.; Oduoza, C.F.; Emekwuru, N. Economics of Gas to Wire Technology Applied in Gas Flare Management. Eng. Sci. Technol. Int. J. 2016, 19, 2109–2118.

- Kumar, S.; Kwon, H.T.; Choi, K.H.; Hyun Cho, J.; Lim, W.; Moon, I. Current Status and Future Projections of LNG Demand and Supplies: A Global Prospective. Energy Policy 2011, 39, 4097– 4104.
- 11. Kumar, S.; Kwon, H.T.; Choi, K.H.; Lim, W.; Cho, J.H.; Tak, K.; Moon, I. LNG: An Eco-Friendly Cryogenic Fuel for Sustainable Development. Appl. Energy 2011, 88, 4264–4273.
- 12. Liu, Y.; Wang, Y.; Huang, D. Supercritical CO2 Brayton Cycle: A State-of-the-Art Review. Energy 2019, 189, 115900.
- 13. Won, W.; Lee, S.K.; Choi, K.; Kwon, Y. Current Trends for the Floating Liquefied Natural Gas (FLNG) Technologies. Korean J. Chem. Eng. 2014, 31, 732–743.
- 14. Kim, S.K.; Park, S.-I.; Paik, J.K. Collision-Accidental Limit States-Based Safety Studies for a LNG-Fuelled Containership. Ocean Eng. 2022, 257, 111571.
- 15. Wang, M.; Zhang, J.; Xu, Q. A Novel Conceptual Design by Integrating NGL Recovery and LNG Re-Gasification Process for Maximum Energy Savings. AIChE J. 2013, 59, 4673–4685.
- 16. He, T.; Chong, Z.R.; Zheng, J.; Ju, Y.; Linga, P. LNG Cold Energy Utilization: Prospects and Challenges. Energy 2019, 170, 557–568.
- 17. Le, S.; Lee, J.Y.; Chen, C.L. Waste Cold Energy Recovery from Liquefied Natural Gas (LNG) Regasification Including Pressure and Thermal Energy. Energy 2018, 152, 770–787.
- 18. Guo, L.N.; An, B.L.; Chen, L.B.; Chen, J.X.; Wang, J.J.; Zhou, Y. Progress of Liquefied Natural Gas Cold Energy Utilization. IOP Conf. Ser. Mater. Sci. Eng. 2019, 502, 012148.
- 19. Jamali, S.; Yari, M. Recovery of Liquefied Natural Gas Cold Energy in a Clean Cogeneration System Utilizing Concentrated Photovoltaics. J. Clean. Prod. 2022, 350, 131517.
- 20. Hirakawa, S.; Kosugi, K. Utilization of LNG Cold. Int. J. Refrig. 1981, 4, 17–21.
- 21. Kanbur, B.B.; Xiang, L.; Dubey, S.; Choo, F.H.; Duan, F. Cold Utilization Systems of LNG: A Review. Renew. Sustain. Energy Rev. 2017, 79, 1171–1188.
- 22. Zou, Q.; Yi, C.; Wang, K.; Yin, X.; Zhang, Y. Global LNG Market: Supply-Demand and Economic Analysis. IOP Conf. Ser. Earth Environ. Sci. 2022, 983, 12051.
- 23. Dutta, A.; Karimi, I.A.; Farooq, S. Economic Feasibility of Power Generation by Recovering Cold Energy during LNG (Liquefied Natural Gas) Regasification. ACS Sustain. Chem. Eng. 2018, 6, 10687–10695.
- Baek, S.; Choi, W.; Kim, G.; Seo, J.; Lee, S.; Jeong, H.; Sung, Y. Liquefied Natural Gas Cold Energy Utilization for Land-Based Cold Water Fish Aquaculture in South Korea. Energies 2022, 15, 7322.

- 25. Kim, D.; Giametta, R.E.H.; Gundersen, T. Optimal Use of Liquefied Natural Gas (LNG) Cold Energy in Air Separation Units. Ind. Eng. Chem. Res. 2018, 57, 5914–5923.
- 26. Chen, S.; Dong, X.; Xu, J.; Zhang, H.; Gao, Q.; Tan, C. Thermodynamic Evaluation of the Novel Distillation Column of the Air Separation Unit with Integration of Liquefied Natural Gas (LNG) Regasification. Energy 2019, 171, 341–359.
- 27. Nakaiwa, M.; Huang, K.; Endo, A.; Ohmori, T.; Akiya, T.; Takamatsu, T. Internally Heat–Integrated Distillation Columns: A Review. Chem. Eng. Res. Des. 2003, 81, 162–177.
- Wu, Y.; Xiang, Y.; Cai, L.; Liu, H.; Liang, Y. Optimization of a Novel Cryogenic Air Separation Process Based on Cold Energy Recovery of LNG with Exergoeconomic Analysis. J. Clean. Prod. 2020, 275, 123027.
- 29. Han, F.; Wang, Z.; Jiang, Y.; Ji, Y.; Li, W. Energy Assessment and External Circulation Design for LNG Cold Energy Air Separation Process under Four Different Pressure Matching Schemes. Case Stud. Therm. Eng. 2021, 27, 101251.
- 30. He, X.; Liu, Y.; Rehman, A.; Wang, L. Feasibility and Performance Analysis of a Novel Air Separation Unit with Energy Storage and Air Recovery. Renew. Energy 2022, 195, 598–619.
- Hamayun, M.H.; Ramzan, N.; Hussain, M.; Faheem, M. Conventional and Advanced Exergy Analyses of an Integrated LNG Regasification–Air Separation Process. Ind. Eng. Chem. Res. 2022, 61, 2843–2853.
- Saedi, M.; Mehrpooya, M.; Shabani, A.; Zaitsev, A.; Nikitin, A. Proposal and Investigation of a Novel Process Configuration for Production of Neon from Cryogenic Air Separation Unit. Sustain. Energy Technol. Assess. 2022, 50, 101875.
- Wang, Z.; Han, F.; Jiang, Y.; Yu, S.; Ji, Y.; Cai, W. Conceptual Design and Assessment of a Novel Energy Management System for LNG Fueled Ships with Air Separation. Therm. Sci. Eng. Prog. 2021, 26, 101111.
- Huo, C.; Sun, J.; Song, P. Energy, Exergy and Economic Analyses of an Optimal Use of Cryogenic Liquid Turbine Expander in Air Separation Units. Chem. Eng. Res. Des. 2023, 189, 194–209.
- 35. Zhang, R.; Wu, C.; Song, W.; Deng, C.; Yang, M. Energy Integration of LNG Light Hydrocarbon Recovery and Air Separation: Process Design and Technic-Economic Analysis. Energy 2020, 207, 118328.
- Mehrpooya, M.; Ansarinasab, H.; Sharifzadeh, M.M.M.; Rosen, M.A. Conventional and Advanced Exergoeconomic Assessments of a New Air Separation Unit Integrated with a Carbon Dioxide Electrical Power Cycle and a Liquefied Natural Gas Regasification Unit. Energy Convers. Manag. 2018, 163, 151–168.

- Joy, J.; Singla, R.; Chowdhury, K. Safe Design of Liquid Oxygen Plant That Absorbs LNG Cold Energy and Offsets Supply Disruption by Injecting Liquid Nitrogen. Sustain. Energy Technol. Assess. 2022, 53, 102501.
- 38. Mujtaba, I.M.; Sowgath, M.T. (Eds.) Chapter 2—Desalination Processes. In Desalination Technologies; Elsevier: Amsterdam, The Netherlands, 2022; pp. 29–67. ISBN 978-0-12-813790-1.
- 39. Cao, W.; Beggs, C.; Mujtaba, I.M. Theoretical Approach of Freeze Seawater Desalination on Flake Ice Maker Utilizing LNG Cold Energy. Desalination 2014, 355, 22–32.
- 40. Lee, S.; Choi, J.; Park, Y.G.; Shon, H.; Ahn, C.H.; Kim, S.H. Hybrid Desalination Processes for Beneficial Use of Reverse Osmosis Brine: Current Status and Future Prospects. Desalination 2019, 454, 104–111.
- Zhao, J.; Wang, M.; Lababidi, H.M.S.; Al-Adwani, H.; Gleason, K.K. A Review of Heterogeneous Nucleation of Calcium Carbonate and Control Strategies for Scale Formation in Multi-Stage Flash (MSF) Desalination Plants. Desalination 2018, 442, 75–88.
- 42. Janajreh, I.; Zhang, H.; El Kadi, K.; Ghaffour, N. Freeze Desalination: Current Research Development and Future Prospects. Water Res. 2023, 229, 119389.
- 43. Williams, P.M.; Ahmad, M.; Connolly, B.S.; Oatley-Radcliffe, D.L. Technology for Freeze Concentration in the Desalination Industry. Desalination 2015, 356, 314–327.
- Xie, C.G.; Sun, J.; Lv, Q.C.; Miao, C.; Chu, S.P.; Zhang, L.P. High Efficient Seawater Freezing Desalination Technology by Utilizing Cold Energy of LNG. IDA J. Desalin. Water Reuse 2014, 6, 5–9.
- 45. Ong, C.W.; Chen, C.-L. Technical and Economic Evaluation of Seawater Freezing Desalination Using Liquefied Natural Gas. Energy 2019, 181, 429–439.
- 46. Ghorbani, B.; Mahyari, K.B.; Mehrpooya, M.; Hamedi, M.-H. Introducing a Hybrid Renewable Energy System for Production of Power and Fresh Water Using Parabolic Trough Solar Collectors and LNG Cold Energy Recovery. Renew. Energy 2020, 148, 1227–1243.
- Lee, S.H.; Lee, J.D.; Lim, D.-H.; Park, K. Conceptual Design of a Sustainable Hybrid Desalination Process Using Liquefied Natural Gas Cold Energy. ACS Sustain. Chem. Eng. 2021, 9, 13559– 13572.
- 48. Salakhi, M.; Eghtesad, A.; Afshin, H. Heat and Mass Transfer Analysis and Optimization of Freeze Desalination Utilizing Cold Energy of LNG Leaving a Power Generation Cycle. Desalination 2022, 527, 115595.
- 49. Kiwan, S.; Alali, A.; Al-Safadi, M. A Novel Water Freezing Desalination Plant Integrated into a Combined Gas Power Cycle Plant. Energy 2023, 263, 125983.

- Yao, S.; Wang, M.; Yan, L.; Zhang, Q.; Ye, Y. Construction and Optimization of Liquefied Natural Gas Regasification Cold Energy Comprehensive Utilization System on Floating Storage Regasification Unit. J. Therm. Sci. 2022, 31, 1853–1867.
- Alirahmi, S.M.; Gundersen, T.; Yu, H. An Innovative Polygeneration System Integrating Compressed Air Energy Storage (CAES) and Multi-Effect Desalination for Efficient LNG Cold Energy Utilization. Chem. Eng. Trans. 2022, 94, 127–132.
- 52. Ansarinasab, H.; Hajabdollahi, H.; Fatimah, M. Life Cycle Assessment (LCA) of a Novel Geothermal–Based Multigeneration System Using LNG Cold Energy–Integration of Kalina Cycle, Stirling Engine, Desalination Unit and Magnetic Refrigeration System. Energy 2021, 231, 120888.
- 53. Lee, S.H.; Park, K. Conceptual Design and Economic Analysis of a Novel Cogeneration Desalination Process Using LNG Based on Clathrate Hydrate. Desalination 2021, 498, 114703.
- 54. Khan, M.S.; Karimi, I.A.; Wood, D.A. Retrospective and Future Perspective of Natural Gas Liquefaction and Optimization Technologies Contributing to Efficient LNG Supply: A Review. J. Nat. Gas Sci. Eng. 2017, 45, 165–188.
- 55. Fu, L.; Ren, Z.; Si, W.; Ma, Q.; Huang, W.; Liao, K.; Huang, Z.; Wang, Y.; Li, J.; Xu, P. Research Progress on CO2 Capture and Utilization Technology. J. CO2 Util. 2022, 66, 102260.
- Zhao, L.; Dong, H.; Tang, J.; Cai, J. Cold Energy Utilization of Liquefied Natural Gas for Capturing Carbon Dioxide in the Flue Gas from the Magnesite Processing Industry. Energy 2016, 105, 45– 56.
- Kanbur, B.B.; Xiang, L.; Dubey, S.; Choo, F.H.; Duan, F. Mitigation of Carbon Dioxide Emission Using Liquefied Natural Gas Cold Energy in Small Scale Power Generation Systems. J. Clean. Prod. 2018, 200, 982–995.
- 58. Wang, X.; Zhao, L.; Zhang, L.; Zhang, M.; Dong, H. A Novel Combined System for LNG Cold Energy Utilization to Capture Carbon Dioxide in the Flue Gas from the Magnesite Processing Industry. Energy 2019, 187, 115963.
- 59. Ghorbani, B.; Mehrpooya, M.; Omid, E. Hybrid Solar Liquefied Natural Gas, Post Combustion Carbon Dioxide Capture and Liquefaction. Energy Convers. Manag. 2020, 207, 112512.
- Kim, Y.; Lee, J.; Cho, H.; Kim, J. Novel Cryogenic Carbon Dioxide Capture and Storage Process Using LNG Cold Energy in a Natural Gas Combined Cycle Power Plant. Chem. Eng. J. 2023, 456, 140980.
- Kim, J.; Park, J.; Qi, M.; Lee, I.; Moon, I. Process Integration of an Autothermal Reforming Hydrogen Production System with Cryogenic Air Separation and Carbon Dioxide Capture Using Liquefied Natural Gas Cold Energy. Ind. Eng. Chem. Res. 2021, 60, 7257–7274.

- Moradi, M.; Ghorbani, B.; Ebrahimi, A.; Ziabasharhagh, M. Process Integration, Energy and Exergy Analyses of a Novel Integrated System for Cogeneration of Liquid Ammonia and Power Using Liquefied Natural Gas Regasification, CO2 Capture Unit and Solar Dish Collectors. J. Environ. Chem. Eng. 2021, 9, 106374.
- 63. Kanbur, B.B.; Xiang, L.; Dubey, S.; Choo, F.H.; Duan, F. Thermoeconomic Analysis and Optimization of the Small Scale Power Generation and Carbon Dioxide Capture System from Liquefied Natural Gas. Energy Convers. Manag. 2019, 181, 507–518.
- 64. Lim, J.; Kim, Y.; Cho, H.; Lee, J.; Kim, J. Novel Process Design for Waste Energy Recovery of LNG Power Plants for CO2 Capture and Storage. Energy Convers. Manag. 2023, 277, 116587.
- 65. Esfilar, R.; Mehrpooya, M.; Moosavian, S.M.A. Thermodynamic Assessment of an Integrated Biomass and Coal Co-Gasification, Cryogenic Air Separation Unit with Power Generation Cycles Based on LNG Vaporization. Energy Convers. Manag. 2018, 157, 438–451.
- Yu, H.; Gundersen, T.; Gençer, E. Optimal Liquified Natural Gas (LNG) Cold Energy Utilization in an Allam Cycle Power Plant with Carbon Capture and Storage. Energy Convers. Manag. 2021, 228, 113725.

Retrieved from https://encyclopedia.pub/entry/history/show/93246