Production of Ultra-High-Performance Concrete

Subjects: Engineering, Civil

Contributor: Gregor Kravanja, Ahmad Rizwan Mumtaz, Stojan Kravanja

Ultra-high-performance concrete (UHPC) is defined as a type of concrete that exhibits compressive strength greater than 120 MPa, a nominal maximum aggregate size of less than 5 mm, and flowability between 200 mm and 250 mm. UHPC exhibits a tensile strength greater than 5 MPa. According to the Federal Highway Administration (FHWA), USA, UHPC is characterized by the use of a combination of Portland cement and supplementary cementitious materials, an optimised gradation of granular materials, a high volume of discontinuous internal fibres, and a low water-to-cementitious materials ratio of less than 0.25. The microstructure of UHPC is characterized irregular pores, which control liquid evaporation and enhance durability in comparison to conventional and highperformance concretes.

ultra-high-performance concrete (UHPC) compressive strength

curing

durability production

mixture

1. Introduction

The development of UHPC can be traced back to the early 1980s ^[1]. After decades of research, UHPC has emerged as a highly innovative product in the field of concrete technology, distinguished by its exceptional mechanical properties and superior durability. The service life of reinforced concrete structures is largely dependent on the durability of the concrete, and the excellent durability properties of UHPC can lead to a significant increase in service life, thus reducing maintenance costs.

In addition to its durability properties, UHPC also exhibits high flowability, allowing it to meet a wide range of structural requirements. UHPC has also been reported to possess high impermeability against carbon dioxide, chlorides, and sulphates ^[2]. The inclusion of steel fibres in the mix design of UHPC can further enhance its compressive and tensile strength, which can exceed 150 MPa and 20 MPa, respectively ^[3]. The ductility and energy absorption capacity of UHPC, due to the presence of steel fibres, are typically 300-times greater than that of high-performance concrete [4].

Workability, compressive strength, durability and economy are the key factors and priorities of conventional concrete (CC) based on the ACI mixture design method ^[5]. Portland cement (PC) is the main ingredient in the production of UHPC as a cementitious binder, accompanied by other supplementary cementitious materials (SCM); in most cases, silica fume (SF) is used as an SCM ^[6]. Mechanical consistency, maximum particle packing density and the lowest number of defects are the fundamental basis for the production of UHPC, considering both micro and macro characteristics of the design mix materials ^{[7][8][9]}. In addition to the micro and macro properties of the design mix materials, it is also crucial to consider the physical and chemical properties of the materials ^[9]. To produce UHPC with durable, viable, economical and excellent mechanical properties, it is crucial to develop scientifically efficient mix design methods ^[5].

Nonetheless, there are some disadvantages associated with UHPC, particularly concerning shrinkage and cracking during the early stages of concreting due to autogenous and drying shrinkage. Consequently, there has been limited research conducted on the long-term behaviour of this concrete. Additionally, UHPC is more costly than normal concrete, raising concerns about its viability when unconventional concrete can economically meet design requirements. The primary limitation to the broader utilization of UHPC is the high cost of several expensive raw materials in the mix ^[4].

Nowadays, the UHPC mixture is mixed, cast and vibrated like conventional concrete. The production procedural steps are as follows ^{[8][10]}:

- Mixing of all dry materials for about 10 min.
- Add water and superplasticizer into dry mixture and mix for approximately 5–10 min.
- Fibres are added if required.
- Finish the mixing when mixture shows enough flowability for good workability and sufficient viscosity.

The mixing procedure for UHPC appears to take a longer time than that for conventional concrete and consumes more energy. Due to the absence of coarse aggregates and the low W/B ratio, a specific sequence needs to be followed to prevent the UHPC mixture from overheating ^[11]. **Table 1** represents the different compositions of UHPC mixtures, including the quantity of cement utilised in producing one cubic meter of UHPC, along with the fibre type and percentage.

Composition	Sequence	Type of Fibre	Length and Diameter	Amount of Fibres Vol. % or kg/m ³	Cement kg/m ³	Ref.
PC + SF + Q		Steel Fibre	13 mm × 0.16 mm ∅ 6 mm × 0.16 mm ∅	2–2.5	788	[<u>12</u>]
PC + FA + SF		Steel Fibre	13 mm × 0.20 mm ∅	1–3	642–662	[<u>13</u>]

Table 1. Typical composition of UHPC.

Composition	Sequence	Type of Fibre	Length and Diameter	Amount of Fibres Vol. % or kg/m ³	Cement kg/m ³	Ref.
PC + FS+ SF		Steel Fibre		0–2	712	[<u>12</u>]
PC + SF + FA		Steel Fibre	20 mm × 0.20 mm ∅ 25 mm × 0.30 mm ∅	1	360–900	[<u>12</u>]
PC + FA + GGBS		Steel Fibre		0	582.1– 896.3	[<u>14</u>]
PC + SF + QP		Glass Fibre	6 mm × 0.015 mm ∅	12 *	750	[<u>15</u>]
PC + SF + UFSP		Polypropylene	12 mm × 0.050 mm Ø	0-78	737–1005	[<u>16</u>]
PC + MK + NMK					720-800	[<u>12</u>]
PC + MK+ FA					482	[<u>17</u>]
PC + MK + LS					608	[<u>17</u>]
PC + GGBS + QP + FS	GGBS 30%	Steel Fibre	13 mm × 0.20 mm Ø	2	630	[<u>18</u>]
PC + GGBS + QP + FS	GGBS 40%	Steel Fibre		2	540	[<u>18</u>]
PC + GGBS + QP + FS	GGBS 50%	Steel Fibre		2	450	[<u>18</u>]
PC + FA + QP + SF	FA 20%	Steel Fibre		2	720	[<u>18</u>]
PC + FA + QP + SF	FA 25%	Steel Fibre		2	675	[<u>18</u>]
PC + FA + QP + SF	FA 50%	Steel Fibre		2	630	[<u>18</u>]
PC + MK + SF	MK 15%	Steel Fibre		2	765	[<u>18</u>]
PC + MK + SF	MK 20%	Steel Fibre		2	720	[<u>18</u>]
PC + MK + SF	MK 25%	Steel Fibre		2	675	[<u>18</u>]
PC + SF		Metal fibre	13 mm × 160 µm	138 *	691	[<u>19</u>]

Composition	Sequence	Type of Fibre	Length and Diameter	Amount of Fibres Vol. % or kg/m ³	Cement kg/m ³	Ref.	
			Ø	5			
PC + MK		Metal fibre		138 *	691	[<u>19</u>]	
PC + FA + SF		Straight steel fibre	13 mm × 0.20 mm ∅	156 *	754	[<u>20</u>]	
PC + FA + SF + MK				156 *	754	[<u>20</u>]	
PC + FA + MK				156 *	754	[<u>20</u>]	oerties
PC + SF + QS		Basalt Fibre	12 mm × 15 µm Ø	0, 0.5, 1.0, 2.5	706	[<u>21</u>]	
PC + SF + QP + QS		Basalt Fibre	12 mm × 18 µm Ø	6 *	876	[22]	Constr.
PC + GP + SF + WG		Basalt Fibre	24 mm × 16 + 0.2 µm Ø	8.1 *	720–400	[23]	ersity of

5. Zhou, M.; Wu, Z.; Ouyang, X.; Hu, X.; Shi, C. Mixture design methods for ultra-high-performance concrete—A review. Cem. Concr. Compos. 2021, 124, 104242.

PC is Portland cement, SF is silica fume, Q is quartz, FA is fly ash, FS is fine sand, GGBS is granulated blast furnact slag; GPGs quartz powerter, UPSP is utra-Fixte silica powerter, in the Effection of Alternative Great ability is line source of the state of the

7. Schmidt, M.; Fehling, E. Ultra High Performance Concrete: Research, Development and

2p Samphingppe. Am. Concr. Inst. ACI Spec. 2005, 228, 51–77.

8. Shi, C.; Wu, Z.; Xiao, J.; Wang, D.; Huang, Z.; Fang, Z. A review on ultra high performance The preparation of UHPC samples for testing purposes is no different from that for conventional concrete. Both concrete: Part I. Raw materials and mixture design. Constr. Build. Mater. 2015, 101, 741–751. cubes and cylinders can be used for sampling or to perform compression tests. Nevertheless, advanced studies

19avazmaan Nallcustaatig, Abrytuaabighoperfapmense concurate chinanerty milamental to applications.

Case Stud. Constr. Mater. 2018, 9, e00197.



Concrete (UHPC) with efficient cement and mineral admixtures uses. Cem. Concr. Compos.

3.º10 uting-394.

15. He, J.; Chen, W.; Zhang, B.; Yu, J.; Liu, H. The Mechanical Properties and Damage Evolution of A suitable curing process is crucial for optimizing the performance of any concrete. UHPC requires less additional UHPC Reinforced with Glass Fibers and High-Performance Polypropylene Fibers. Materials 2021, curing compared to other concretes because it is designed based on rheological behaviours and optimised gradation of granular materials. However, UHPCs still require proper hydration ^[11]. Design mix ratios of each

- 16 Chen H J. Yu Y L Tang C W Mechanical Properties of Ultra-High Performance Concrete before and after Exposure to High Temperatures. Materials 2020, 13, 770.
- 19. Khatib, J.M. Metakaolin Concrete at a Low Water to Binder Ratio. Constr. Build. Mater. 2008, 22, water outflow before the hydration process. Therefore, the freshly cast exposed surface of UHPC needs to be 1691–1700.

carefully packed immediately to prevent surface dehydration. Materials such as metal, plastic or wood sheets are 18 Abdellatief, M.: Ale Tam, S.M.; Eleman, W.E.; Alanazi, H.; Elgendy, G.M.; Tahwia, A.M.

Development of Ultra-High-Performance Concrete with Low Environmental Impact Integrated with

BelMetakaolis and holustrial Wasten Grase Stud. Constr. Mater. 2023, 18, e01724.

- 19. Tafraoui, A.; Escadeillas, G.; Vidal, T. Durability of the Ultra High Performances Concrete
 Standard room temperature curing; containing metakaolin. Constr. Build. Mater. 2016, 112, 980–987.
- 20. Seatigy Oug VodeR at Sheek Eric Wang with; Rao, S.; Wu, S.; He, Y. Physical and chemical coupling effect of metakaolin induced chloride trapping capacity variation for Ultra High Performance Fibre
- Renciaveedreencrete (UHPFRC). Constr. Build. Mater. 2019, 223, 765–774.
- 21. Xie, H.; Yang, L.; Li, J.; Chen, Z.; Zhang, F.; Liu, Y.; Sui, Z.; Zhang, Q. Research on Mode-I Fracture Characteristics of Basalt Fiber Reactive Powder Concrete. J. Build. Eng. 2023, 80,
 - **\$108**1159.

22. Kočí, V.; Vejmelková, E.; Koňáková, D.; Pommer, V.; Grzeszczyk, S.; Matuszek-Chmurowska, A.; The most economical and eco-friendly method is a standard room temperature curing. However, better Mordak, A.; Černý, R. Basic physical, mechanical, thermal and hygric properties of reactive compressive strength results can be achieved with a 24 h steam curing method than with a 28-day standard room powder concrete with basalt and polypropylene fibers after high-temperature exposure. Constr. temperature method [8][27]. It was also found that the compressive strength of UHPC was higher when cured in an Build. Mater. 2023, 374, 130922. autoclave for 8 h compared to standard curing at room temperature and heat curing [28]. The effects of different
 23. IriAbAteathors. In Engine prima in the standard curing at room temperature and heat curing [28]. The effects of different
 23. IriAbAteathors. In Engine prima in the standard curing at room temperature and heat curing [28]. The effects of different
 23. IriAbAteathors. In Engine prima in the standard curing at room temperature and heat curing [28]. The effects of different
 23. IriAbAteathors. In Engine prima in the standard curing at room temperature and heat curing [28]. The effects of different

- 24. Yang, L.; Shi, C.; Liu, J.; Wu, Z. Factors affecting the effectiveness of internal curing: A review. Constr. Build. Mater. 2021, 267, 121017.
- 25. Li, W.; Huang, Z.; Hu, G.; Hui Duan, W.; Shah, S.P. Early-age shrinkage development of ultrahigh-performance concrete under heat curing treatment. Constr. Build. Mater. 2017, 131, 767– 774.
- 26. Alkaysi, M.; El-Tawil, S.; Liu, Z.; Hansen, W. Effects of silica powder and cement type on durability of ultra high performance concrete (UHPC). Cem. Concr. Compos. 2016, 66, 47–56.

- 27. Yunsheng, Z.; Wei, S.; Sifeng, L.; Chujie, J.; Jianzhong, L. Preparation of C200 green reactive powder concrete and its static-dynamic behaviors. Cem. Concr. Compos. 2008, 30, 831–838.
- Yang, S.L.; Millard, S.G.; Soutsos, M.N.; Barnett, S.J.; Le, T.T. Influence of aggregate and curing regime on the mechanical properties of ultra-high performance fibre reinforced concrete (UHPFRC). Constr. Build Mater. 2009. 23, 2291–2298
- 29. Kang, S.H.; Jeong Y.; Tan, K.H.; Moon, J. High-volume use of limestone in ultra-high performance fiber-reinforced concrete for reducing cement correct and autogenous shrinkage. Constr. Build. Mater. 2019, 213, 292-305.
- 30. Wang, C.; Yang, C.; Liu, F.; Wan, C., Pu, X. Preparation of Ultra-High Performance Concrete with common technology and materials. Cem. Concr. Compos. 2012, 34, 538-544.
- Wu, Z.; Shi, Current and Comparative study on flexural properties of ultra-high performance concrete with supplementary cementitious materials under different curing regimes. Constr. Build. Mater. 2017, 136, 307–313.

Figure 2. Effects of curing methods on compressive strength.

- 32. Yazici, H.; Yiğiter, H.; Karabulut, A.Ş.; Baradan, B. Utilization of fly ash and ground granulated blast furnace slag as an alternative silica source in reactive powder concrete. Fuel 2008, 87, 2401–2407.
- 33. Van Tuan, N.; Ye, G.; Van Breugel, K.; Copuroglu, O. Hydration and microstructure of ultra high performance concrete incorporating rice husk ash. Cem. Concr. Res. 2011, 41, 1104–1111.
- 34. Yazici, H.; Yardimci, M.Y.; Yiğiter, H.; Aydin, S.; Türkel, S. Mechanical properties of reactive powder concrete containing high volumes of ground granulated blast furnace slag. Cem. Concr. Compos. 2010, 32, 639–648.
- Van, V.T.A.; Rößler, C.; Bui, D.D.; Ludwig, H.M. Rice husk ash as both pozzolanic admixture and internal curing agent in ultra-high performance concrete. Cem. Concr. Compos. 2014, 53, 270– 278.
- 36. Yoo, D.Y.; Banthia, N. Mechanical properties of ultra-high-performance fiber-reinforced concrete: A review. Cem. Concr. Compos. 2016, 73, 267–280.
- 37. Ahmad, S.; Hakeem, I.; Maslehuddin, M. Development of UHPC mixtures utilizing natural and industrial waste materials as partial replacements of silica fume and sand. Sci. World J. 2014, 2014, 1–8.
- 38. Li, Z. Drying shrinkage prediction of paste containing meta-kaolin and ultrafine fly ash for developing ultra-high performance concrete. Mater. Today Commun. 2016, 6, 74–80.
- Kim, H.; Koh, T.; Pyo, S. Enhancing flowability and sustainability of ultra high performance concrete incorporating high replacement levels of industrial slags. Constr. Build. Mater. 2016, 123, 153–160.

- 40. Van Tuan, N.; Ye, G.; Van Breugel, K. Effect of rice husk ash on autogenous shrinkage of ultra high performance concrete. In Proceedings of the International RILEM Conference on Use of Superabsorbent Polymers and Other New Additives in Concrete, Lyngby, Denmark, 15–18 August 2010.
- 41. Schießl, P.; Mazanec, O.; Lowke, D. SCC and UHPC-Effect of Mixing Technology on Fresh Concrete Properties; Springer: Berlin/Heidelberg, Germany, 2007.
- 42. Yigiter, H.; Aydin, S.; Yazici, H.; Yardimci, M.Y. Mechanical performance of low cement reactive powder concrete (LCRPC). Compos. B Eng. 2012, 43, 2907–2914.
- Lee, N.K.; Koh, K.T.; Park, S.H.; Ryu, G.S. Microstructural investigation of calcium aluminate cement-based ultra-high performance concrete (UHPC) exposed to high temperatures. Cem. Concr. Res. 2017, 102, 109–118.
- 44. Randl, N.; Steiner, T.; Ofner, S.; Baumgartner, E.; Mészöly, T. Development of UHPC mixtures from an ecological point of view. Constr. Build. Mater. 2014, 67, 373–378.
- 45. Sharma, R.; Jang, J.G.; Bansal, P.P. A comprehensive review on effects of mineral admixtures and fibers on engineering properties of ultra-high-performance concrete. J. Build. Eng. 2022, 45, 103314.
- 46. Yalçınkaya, Ç.; Çopuroğlu, O. Hydration heat, strength and microstructure characteristics of UHPC containing blast furnace slag. J. Build. Eng. 2021, 34, 101915.
- 47. Mousavinejad, S.H.G.; Sammak, M. Strength and chloride ion penetration resistance of ultra-highperformance fiber reinforced geopolymer concrete. Structures 2021, 32, 1420–1427.
- 48. Alsalman, A.; Dang, C.N.; Martí-Vargas, J.R.; Micah Hale, W. Mixture-proportioning of economical UHPC mixtures. J. Build. Eng. 2020, 27, 100970.
- 49. Ganesh, P.; Murthy, A.R. Tensile behaviour and durability aspects of sustainable ultra-high performance concrete incorporated with GGBS as cementitious material. Constr. Build. Mater. 2019, 197, 667–680.
- 50. Nadiger, A.; Madhavan, M.K. Influence of Mineral Admixtures and Fibers on Workability and Mechanical Properties of Reactive Powder Concrete. J. Mater. Civ. Eng. 2019, 31, 04018394.
- 51. Vigneshwari, M.; Arunachalam, K.; Angayarkanni, A. Replacement of silica fume with thermally treated rice husk ash in Reactive Powder Concrete. J. Clean. Prod. 2018, 188, 264–277.
- 52. Bahedh, M.A.; Jaafar, M.S. Ultra high-performance concrete utilizing fly ash as cement replacement under autoclaving technique. Case Stud. Constr. Mater. 2018, 9, e00202.
- 53. Zhang, J.; Zhao, Y.; Li, H. Experimental Investigation and Prediction of Compressive Strength of Ultra-High Performance Concrete Containing Supplementary Cementitious Materials. Adv. Mater. Sci. Eng. 2017, 2017, 1–8.

- 54. Huang, W.; Kazemi-Kamyab, H.; Sun, W.; Scrivener, K. Effect of replacement of silica fume with calcined clay on the hydration and microstructural development of eco-UHPFRC. Mater. Des. 2017, 121, 36–46.
- 55. Ferdosian, I.; Camões, A.; Ribeiro, M. High-Volume Fly Ash Paste for Developing Ultra-High Performance Concrete (UHPC). Ciênc. Tecnol. Mater. 2017, 29, 157–161.
- 56. Azreen, N.M.; Rashid, R.S.M.; Mugahed Amran, Y.H.; Voo, Y.L.; Haniza, M.; Hairie, M.; Alyousef, R.; Alabduljabbar, H. Simulation of ultra-high-performance concrete mixed with hematite and barite aggregates using Monte Carlo for dry cask storage. Constr. Build. Mater. 2020, 263, 120161.

Retrieved from https://encyclopedia.pub/entry/history/show/123850