Closed Ecological Life Support Systems

Subjects: Green & Sustainable Science & Technology Contributor: Alex Ellery

Closed ecological life support systems (CELSS) requires agricultural production for food, CO2removal, O2generation (human respiratory quotient ofCO2/[O2= 0.84–0.87 depending on the percentage formation of carbohydrate, fat and protein in the food consumed) and water recycling with bioreactors for recycling waste. Plants consume CO2and H2O for photosynthesis under the action of sufficient PAR to produce carbohydrate food, regenerate oxygen and filter water through evapotranspiration. There have been several bioregenerative life support system programmes including Biosphere 2 (US), CELSS (NASA), Bios-3 (Roscosmos) and its predecessors and MELiSSA (ESA).

Keywords: bioregenerative life support ; closed ecological life support ; in-situ resource utilization ; lunar industrial ecology

1. Introduction

On Earth, human life is supported by a complex and deep biosphere with material recycling including hydrological and biogeochemical processes through the lithosphere, hydrosphere, cryosphere, atmosphere and biosphere. The key features of natural ecosystems are bio-material turnover and energy flows ^[1]. They are closed to matter permitted by material recycling through biogeochemical (CNPSK) cycles but open to energy from the Sun. Buckminster Fuller characterised the Earth's biosphere as spaceship Earth in his Operating Manual for Spaceship Earth (1968). Artificial life support systems generally lack the large buffering capacity of the Earth 's biosphere so they require much higher degrees of precision control.

Biosphere 2 was a 12,700 m 2 glass biospheric enclosure sealed with silicone sealant in the Arizona desert housing a crew of 8 people for two years (1991–1993) with effectively 100% material closure ^[2]. Energy was input to Biosphere 2 as solar energy and electric generators supplying 700 kW (average) to 1500 kW (peak). The biosphere included 7 modules of 1900 m 2 tropical rainforest, 1300 m 2 savanna, 1400 m 2 desert, 450 m 2 tidal (freshwater and saltwater) marshes, 850 m 2 ocean, 2500 m 2 agricultural system and a 2400 m 2 human habitat. The habitat comprised a galley, living quarters, an analytic laboratory, computing facilities, machine shop and sickbay facilities. A system of cooling water towers, chilled water and a water boiler-controlled Biosphere 2's air temperature ^[3]. Biosphere 2 incorporated 6 × 10 6 litres of water including fish/rice paddies and hosted 3800 different species including three domestic animals (pigmy goat, feral swine and chicken) which consumed inedible crop residue and worms in return for milk, eggs and tilapia meat. Waste was processed through composting and bacterial processing. Food production consumed the majority of the crew's time. The facility incorporated two large expansion chambers ("lungs") to accommodate temperature variations to ensure low gas leakage rates ~10%/year ^[4]. The most challenging issues were O 2/CO 2 level fluctuations which required periodic intervention and the calorie-restricted diet imposed on the crew. Obviously, the scale of Biosphere 2 renders it impractical for space application (except perhaps O'Neill colonies ^[5]). Nevertheless, experiments to date suggest that 100% closure is feasible for up to 6 months but the precise means to achieve this has yet to be demonstrated.

2. Role of Ecologies

Crucially, in space or planetary surfaces, we are transplanting the human from the environment in which we have evolved to an entirely alien one in which we have not. In this regard, it is crucial to consider evolutionary medicine as a factor in designing life support systems for long duration missions—diet (with implications for diabetes), microbiome (with implications for autoimmune disease), radiation exposure (with implications for cancer), infectious disease exposure (with implications for virulence), emotional isolation (with implications for mental disorders) ^[6].

Environmental control and life support systems (ECLSS) involve control of atmospheric pressure, temperature, humidity and composition with most other resources supplied. In the early days of spaceflight, life support systems stored oxygen, water and food for astronaut consumption and returned waste back to Earth. A more comprehensive life support system also requires: (i) air quality including the maintenance of buffering gases, CO 2 removal and O 2 generation; (ii) food production and storage; (iii) water management through waste-water recovery; and (iv) solid waste management through bacterial processing. There are several approaches to such life support: (i) open loop life support systems in which all consumables are supplied and stored as adopted in early space missions of short duration; (ii) physicochemical recycling life support systems that recycle bulk consumables; (iii) bioregenerative life support systems that exploit biological mechanisms; (iv) in-situ resource utilisation supply of consumed material; (v) hybrid life support systems that are combinations thereof.

A human being requires 38.5 kg of consumables per day including 24.8 kg of water for showering, toilet flushing, cleaning and clothes washing per day including tankage. Water is the primary human consumption requirement—it is the main constituent of electrolytes of the human body (blood plasma, interstitial fluid and intracellular fluid) regulated by the kidneys through urine production ^[2]. Grey water is readily recycled so 13.7 kg of water consumables per day is more realistic. Recycling of water and oxygen may be implemented through physicochemical processes, the two components that can be readily sourced and supplied from lunar resources. Water at 5.6 ± 2.9% concentration (plus associated vapours of H 2S, ethylene, CO 2 and methanol) was detected by the LCROSS (lunar crater observation and sensing satellite) mission (2009) in an ejecta plume generated by a Centaur rocket stage impacting into the Cabeus crater (B) (Table 1). However, there are considerably greater resources in lunar regolith minerals which may be extracted through a handful of processes (Figure 1). The closed loop lunar industrial ecology system (CLIES) extracts other resources from lunar minerals and impacted asteroidal material ^[9]. Industrial ecology is an approach to organising industrial chemical processors such that the waste of one process becomes feedstock for another , i.e., recycling to minimize waste. CLIES presents an interlocking set of closed recycling loops that extract ceramics and ultimately metals from common rockforming lunar minerals. Some of these metals might be exploited as input supplies to CELSS beyond water/oxygen. Scarce lunar volatiles may also be extracted but should serve only as recycled reagents so they are not consumed but their scarcity renders them untenable as a source of CNPS in CELSS. Similarly, CLIES does not exploit lunar volatiles for consumption. One notable exception was the carbon resources-this was proposed to manufacture silicone (siloxane) products as elastomeric electrical insulation plastic for wiring harnesses and silicone oils for lubrication ^[10] but we have readdressed this issue and concluded that silicone is unnecessary as glass cloth and porcelain may be substituted for this purpose ^[11] and tungsten disulphide (WS 2) is a high temperature lubricant used in place of molybdenum disulphide (MoS 2) which may substitute for silicone oils. Hence, all extracted volatiles are recycled with CLIES. The implication is that, although H 2O resources can be replenished from lunar resources, CNPS elements cannot be supplied from lunar volatile sources but must be recycled within CELSS. However, CLIES can supply a limited set of resources for input to CELSS but the majority of nutrients including most metal micro-nutrients specified later must be recycled within CELSS. Water and oxygen supplies are available on the Moon but current proposals for mining local water ice are focused on its use as cryogenic propellant/oxidiser. We proffer a view that extraction and consumption of water consumables for burning as propellant/oxidiser wastes finite and valuable resources which would otherwise support human survival on the Moon over future generations.

Volatile Species.	% Relative to Water	% by Mass
H ₂ O	100	5.60
H ₂ S	16.75	0.94
NH ₃	6.03	0.34
SO ₂	3.19	0.18
C ₂ H ₄	3.12	0.17
CO ₂	2.17	0.12
CH ₃ OH	1.55	0.09
CH ₄	0.65	0.04
ОН	0.03	0.002

Table 1. LCROSS ejecta plume show the paucity of volatile species [8].



CO₂ + 4H₂ → CH₄ + 2H₂O at 300 °C (Sabatier reaction) → CH₄ → C + 2H₂ at 1400 °C → FFC anode regeneration Ni catalvst

Figure 1. Near closed loop lunar industrial ecology (emboldened materials are pure metal oxides for direct reduction using the Metalysis FFC process). This summarises the sustainable closed loop lunar industrial ecology system (CLIES) presented in ^[9]. Energy generation and storage issues required to support CLIES are discussed in ^[12].

Material closure and openness to energy flow fundamental facets of any closed loop biospheric ecology with the latter driving it to far-from-equilibrium conditions ^[13]. So, it is with life support systems—material closure (with the exception of water/oxygen) will be essential. However, closed loop food production and nutrient recovery from waste can only be provided by biological processes employing living organisms in plant cultivation which is volume intensive. Closed biological regeneration involves the production of food, recycling of waste, recycling of water and air regeneration.

3. Bioregenerative Methods

The carbon loop, due to the scarcity of carbon on the Moon, cannot be recycled through physicochemical processes but the bioregenerative recycling loop has a long time constant. An agricultural system requires an infrastructure to support the growth of higher plants including providing a nutrient supply to roots, the recovery of water of transpiration (20 litre/day/m 2) and provide a photosynthetically active radiation (PAR) lighting system [14][15]. Light may be supplied through solar collector mirrors to provide 0.5-1.0 kW/m 2 of full spectrum sunlight. Fresnel lenses may also be used as solar concentrators to transmit light energy through optical fibres and distributed in a controlled manner that is independent of direct sunlight. However, during the lunar night, artificial lighting is essential. PAR may be supplied by kW-output lampshigh-pressure sodium lamps or fluorescent xenon lamps have been superseded by LEDs but they are limited in their light intensities for some plants such as spinach, tomato and bell pepper. However, sulphur-microwave lamps offer bright visible light with a near-solar spectrum---it comprises a quartz envelope filled with small amounts of S and Ar ionised by microwaves with high efficiency. Exposure to sunlight is also essential for the production of vitamin D for human health which may require vitamin supplementation during the lunar night. There is other life support hardware required including heat-generating motors, pumps, fans, etc with recirculating hydroponic fluid loops in the case of hydroponic agriculture. Environmental parameters must be monitored reliably and controlled for optimal growth. A system of distributed sensors is required to monitor temperature, fluid pressure, fluid pH, conductive or thermal moisture and electrochemical dissolved oxygen levels, e.g., MELiSSA (micro-ecological life support system alternative) compartments measure temperature, pO 2 and solution pH. The implication is that such autonomous control must be robust to external perturbations, reliable without functional failure and stable to feedback time delays.

Closed ecological life support systems (CELSS) requires agricultural production for food, CO 2 removal, O 2 generation (human respiratory quotient of [CO 2]/[O 2] = 0.84–0.87 depending on the percentage formation of carbohydrate, fat and protein in the food consumed) and water recycling with bioreactors for recycling waste. Plants consume CO 2 and H 2O for photosynthesis under the action of sufficient PAR to produce carbohydrate food, regenerate oxygen and filter water through evapotranspiration. There have been several bioregenerative life support system programmes including Biosphere 2 (US), CELSS (NASA), Bios-3 (Roscosmos) and its predecessors and MELiSSA (ESA) ^[16]. CELSS require bioregenerative approaches which are characterised by significantly longer lags in recycling than physicochemical methods ^[17]. CELSS architectures are hierarchically modular, separating human habitation, plant cultivation, animal husbandry and microbial waste treatment which can be further subdivided ^[18]. They should be highly functionally redundant with multiple approaches to any specific function, i.e., there should always be physicochemical backup systems as far as possible ^[19]. A three-tiered architecture with planning–reactive-servo levels is considered suitable for controlling a complex life support system ^[20]. It is crucial to develop autonomous ecosystem control that includes mass and energy exchange measurements and models ^[16].

Crop growth rates may be modelled using the S-shaped Lotka-Volterra predator-prey logistics equations but their nonlinearities can give rise the chaotic behaviours ^[21]: (1) d m i n d t = r i n m i n (1 - m i n m i n (f)) (2) d m e d d t = r e d m i n (m e d (0) + m e d m e d (f)) (1 - m e d m e d (f)) where m ed = edible biomass, m in = inedible biomass, r = growth rates, m (0) = initial (minimum) biomass, m(f) = final (maximum) biomass. This may be broken down into a mass flow model of growth of edible plant, growth of inedible plant, human consumption of edible plant, waste processing of inedible plant and waste processing of human waste ^[22].

ESA's MELISSA is a microorganism-based artificial ecosystem centred in Barcelona Spain to create a closed loop bioregenerative system for space application including microbial recycling of human waste. It exploits microbial bioreactors in which bacteria, yeast and algae can recycle all the major biochemical elements and degrade complex organic molecules in waste into usable materials. Microbial bioreactors with bacteria fixed to a filter bed can also act as biofilters to filter air. They are well-suited to carbon recycling in closed life support systems, e.g., cellulase degrades cellulose into its components such as edible glucose. MELiSSA comprises five (of which four are microbial) interconnected functional bioreactor compartments inspired by aquatic ecosystems with closed loop fluid flow ^{[23][24][25]}. A multi-bacterial species anaerobic composter (including species from the complex human microbiome of which many bacterial strains resist culturing) that breaks down human and plant waste; it must also suppress methanogenesis (combusted methane imposes a loss of carbon and methane-consuming sulphate-reducing bacteria are sensitive to environmental conditions), e.g., Fibrobacter succinogenes is an anaerobic thermophilic bacteria whose fermentation degrades plant waste into CO 2 and volatile fatty acids; Stirred tank bioreactor with photoheterotrophic anaerobic bacteria (purple non-sulphur bacteria Rhodobacteriaceae rubrum) that absorbs fatty acid volatiles and converts them into edible biomass; Packed bed reactor with immobilised aerobic nitrifying bacteria (involving two bacterial steps by Nitrosomonas europaea from NH 4+ into NO 2– and Nitrobacter winogradsky from NO 2– into NO 3– that oxidises urea-produced

ammonium NH 4+ into nitrate NO 3- in a culture medium; Gas-lift bioreactor with edible higher plant hydroponic system supplemented by edible cyanobacteria (Arthrospira/Spirulina platensis) in a culture medium for photosynthesis to generate food, purify water and recycle air; Human habitation compartment.

4. Robotics and Automation

A typical crew 24-h day might comprise 8.5 h sleep, 1.5 h personal and habitat cleaning, 3 h communal meal breaks, 8 h work, 2 h exercise and 1 h personal time. Given the tight work schedule, it is of high importance to automate as much habitat activities as possible. It is expected that robotics will play a significant role within the lunar base to relieve astronaut workloads. Robotics and automation in agriculture will have the largest impact on astronaut workload as this involves monitoring large-area crop status and the ability to react to enhance crop productivity to yield high quality, healthy crops. This will require large-scale persistent environmental monitoring using sensor networks in a challenging environment ^[26]. Data muling involves collecting data from fixed sensor nodes as the mobile rover passes within communication range of the node. Environmental variables to be monitored-temperature, pressure, airflow, light intensity, pH and biochemical sensing. Rather than complex molecular analytic instrumentation, biochemical sensing can be implemented using electrochemical cells, turbidity nephelometry, cytometers, and gas microsensors though with diminished capability. The employment of distributed sensing permits the employment of multisensor Kalman filters to robustify estimates. Agricultural measurements ^[27] include monitoring of soil parameters—moisture (electrical conductivity), pH, compaction (strain gauge-based mechanical impedance) and nitrogen/carbon load (near infrared spectroscopy)-and monitoring of vegetation status-weed control (visual identification), crop maturity through sugar and acid content (near-infrared imaging) and crop health through normalised difference vegetation index (multispectral imaging). The robotics aspect requires sophisticated autonomous tractors in coordinated multirobot teams capable of following complex paths through a crop field map constructed via visual navigation as well as complex interaction with the crops such as seeding, cutting, grafting, transplanting, weeding, harvesting, etc. Hydroponics eases the complexity of some of these requirements but seeding, transporting, transplanting and harvesting are still complex robotic processes. Bioreactors that are employed extensively in CELSS require autonomous monitoring and control of multiple physical and biochemical parameters-medium temperature, photosynthetic active radiation exposure, pumped fluid flow circulation rate, motorised fluid stirring rate, gas input valve flow rate (NO x and CO 2), nephelometric cell density (microbial growth), medium pH levels ^[28]. Inherent time delays and complex dependencies in the bioreactor impose the requirement for intelligent feedback control with feedforward predictive capability.

References

- 1. Pechurkin, N. Key factors in development of man-made and natural ecosystems. Adv. Space Res. 1999, 24, 377–381.
- 2. Allen, J.; Nelson, M. Biospherics and Biosphere 2, mission one (1991–1993). Ecol. Eng. 1999, 13, 15–29.
- Zabel, B.; Hawes, P.; Stuart, H.; Marino, B. Construction and engineering of a created environment: Overview of the Bi osphere 2 closed system. Ecol. Eng. 1999, 13, 43–63.
- 4. Dempster, W. Biosphere 2 engineering design. Ecol. Eng. 1999, 13, 31-42.
- 5. O'Neill, G. Colonisation of space. Phys. Today 1974, 27, 32-40.
- 6. Nesse, R.; Stearns, S. Great opportunity: Evolutionary applications to medicine and public health. Evol. Appl. 2008, 1, 28–48.
- 7. Hager, P.; Czupalla, M.; Walter, U. Dynamic human water and electrolyte balance model for verification and optimizatio n of life support systems in space flight applications. Acta Astronaut. 2010, 67, 1003–1024.
- Colaprete, A.; Schultz, P.; Heldmann, J.; Wooden, D. Detection of water in the LCROSS ejecta plume. Science 2010, 3 30, 463–468.
- 9. Ellery, A. Sustainable in-situ resource utilisation on the Moon. Planet Space Sci. 2020, 184, 104870.
- 10. Ellery, A. Are self-replicating machines feasible? AIAA J. Spacecr. Rocket. 2016, 53, 317–327.
- 11. Ellery, A. Leveraging in-situ resources for lunar base construction. Can. J Civ. Eng. 2021, 184, 104870.
- 12. Ellery, A. Generating and storing power on the moon using in situ resources. J. Aerosp. Eng. 2021.
- Morowitz, H.; Allen, J.; Nelson, M.; Alling, A. Closure as a scientific concept and its application to ecosystem ecology an d the science of the biosphere. Adv. Space Res. 2005, 36, 1305–1311.

- 14. Monje, O.; Stutte, G.; Goins, G.; Portfield, D.; Bingham, G. Farming in space: Environmental and biophysical concerns. Adv. Space Res. 2003, 31, 151–167.
- 15. Kliss, M.; MacElroy, R.; Borchers, B.; Farrance, M.; Nelson, T.; Blackwell, C.; Yendler, B.; Tremor, J. Controlled ecologic al life support systems (CELSS) flight experimentation. Adv. Space Res. 1994, 14, 61–69.
- Escobar, C.; Nabity, J. Past, present and future of closed human life support ecosystems–a review. In Proceedings of t he 47th International Conference Environmental Systems, Charleston, SC, USA, 16 July 2017.
- 17. Schwartzkopf, S. Design of a controlled ecological life support system. BioScience 1992, 42, 526–535.
- 18. Nitta, K. Basic design concept of closed ecology experiment facilities. Adv. Space Res. 1999, 24, 343–350.
- Sadler, P.; Giacomelli, G.; Patterson, R.; Kacira, M.; Lobascio, C.; Bischeri, G.; Lamiantea, M.; Grizzaffi, L.; Rossignoli, S.; Pirolli, M.; et al. Bio-regenerative life support systems for space surface applications. In Proceedings of the 41st AIA A International Conference Environmental Systems, Portland, OR, USA, 17–21 July 2011.
- Schreckenghost, D.; Bonasso, P.; Ryan, D. Three tier architecture for controlling space life support systems. In Procee dings of the IEEE International Joint Symp Intelligence & Systems, Cambridge, MA, USA, 17 September 1998; p. 6854 44.
- 21. May, R. Simple mathematical models with very complicated dynamics. Nature 1976, 261, 459-467.
- 22. Volk, T.; Rummel, J. Mass balances for a biological life support system simulation model. Adv. Space Res. 1987, 7, 141 –148.
- Godia, F.; Albiol, J.; Perez, J.; Creus, N.; Cabello, F.; Montras, A.; Masot, A.; Lasseur, C. MELISSA pilot plant facility as an integration test-bed for advanced life support systems. Adv. Space Res. 2004, 34, 1483–1493.
- 24. Lasseur, C.; Brunet, J.; de Weever, H.; Dixon, M.; Dussap, G.; Godia, F. MELiSSA: The European project of closed life support system. Gravit. Space Biol. 2010, 23, 3–12.
- Hendricks, L.; de Wever, H.; Hermans, V.; Mastroleo, F.; Morin, N.; Wilmotte, A.; Janssen, P.; Mergeay, M. Microbial ec ology of the closed artificial ecosystem MELiSSA (micro-ecological life support system alternative): Reinventing and co mpartmentalising the Earth's food and oxygen regeneration system for long-haul space exploration missions. Res. Micr obiol. 2006, 157, 77–86.
- 26. Dunbabin, M.; Marques, L. Robotics for environmental monitoring. IEEE Robot. Autom. Mag. 2012, 3, 24–33.
- 27. Grift, T.; Zhang, Q.; Kondo, N.; Ting, K. Review of automation and robotics for the bio-industry. J Biomech. Eng. 2008, 1, 37–54.
- Smernoff, D.; Mancinelli, R. Development of autonomous control in a closed microbial bioreactor. Adv. Space Res. 199 9, 24, 319–328.

Retrieved from https://encyclopedia.pub/entry/history/show/30893